



One good printing experience is all it takes to set a new standard. The Epson SureColor™ SC-P10070 and SC-P20070 professional production printers are designed to give you the best results. Epson's Advanced $\label{eq:precisionCore} {\sf PrecisionCore^{\sf TM}\ MicroTFP^{\it @}\ printhead\ technology\ yields\ high\ speeds\ of\ up\ to}$ 17.5 m2/h*, with accurate dot placement for stand-out visuals. To top it all, Epson's UltraChrome™ PRO nine-colour pigment ink system delivers vibrant prints with lasting durability, while a high-precision media feeding system ensures smooth, reliable operations.







SC-P20070



2.64"

64" Wide*





Handling



Thick





ENGINEERED FOR BUSINESS

Rapid Speeds For Maximum Output

New PrecisionCore MicroTFP printhead utilises 8000 nozzles for class-leading print speeds of up to 17.5 m2/h*.

Affordable Prints with Peace of Mind

Epson's UltraChrome PRO ink with four levels of grey produces brilliant prints that last up to 200 years. Cost-effective 700ml ink cartridges ensure low printing costs.

Precision Media Feeding System

Maximum output with Realtime Media Adjustment & Feedback System, a Media Inductive Roller System and a unique Roll Media Skew Reduction System.







Model Number SC-P1	0070 SC-P20070		
Printer Width	44"	64"	
Printing Technology		<u> </u>	
Printing rechnology Printhead	PrecisionCore™ MicroTEP Printhoad		
	PrecisionCore™ MicroTFP Printhead		
Printing Method	Nozzle Verification System		
Nozzle Configuration	Black colour ink: 4,000 nozzles (PK, MK, DGY, GY, LGY 800 nozzles each colour)		
	Colour ink: 4,000 nozzles (C, VM, Y, LC, VLM 800 nozzles each colour)		
Print Direction	Bi-directional printing, uni-directional printing		
	Auto Head Alignment technology		
Print Quality			
Maximum Resolution	2400x1200 dpi		
Minimum Ink Droplet Volume	3.5pl		
Performance*1	-		
Draft Mode	600 x 600dpi, 1.9 minutes		
Normal Mode	1200 x 1200dpi, 3.0 minutes		
Fine Mode			
	2400 x 1200dpi, 5.6 minutes		
Ink System	Engan Lillius Chuana aTM DEO La La		
Ink Type	Epson UltraChrome™ PRO Ink		
Colours	Cyan, Vivid Magenta, Yellow, Photo Black, Matte Black, Dark Grey, Grey, Light Grey, Light Cyan,		
	Vivid Light Magenta		
Ink Capacity	700ml/110ml (Bundled)		
Printer Software on CD-ROM			
Printer Driver	WindowsXP/Vista/7/8/8.1/10 (32/64bit) or later / MacOSX10.6.8 or later		
	Windows Server 2003 Standard/Standard *64bit, 2008 Standard/Standard *64bit /R2, 2012 or later		
	2003/2003 *64bit, 2008/2008R2 *64bit/2012 or later (Certification/Logo: Windows Server 2008/2008R2)		
Paper Handling			
Paper Feed Method	Friction Feed		
Roll Dimensions	170mm		
Paper Size & Thickness	Roll paper : 254mm (10") - 1118mm (44")	Roll paper : 254mm (10") - 1626mm (64")	
raper Size & THICKNESS			
Davidadaaa	Cut sheet: 210mm (A4)- 1118mm (44") 0.08-1.50mn		
Borderless	254mm(10in.), 300mm(11.8in.), 329mm(A3+/A3++),	254mm(10in.), 300mm(11.8in.), 329mm(A3+/A3++),	
	406mm(16in.), 432mm(17in./USC), 508mm(20in.),	406mm(16in.), 432mm(17in./USC), 508mm(20in.),	
	515mm(20.3in./B2), 594mm(A1), 610mm(24in./A1+),	515mm(20.3in./B2), 594mm(A1), 610mm(24in./A1+),	
	728mm(29in./B1), 841mm(A0), 914(36in./A0+),	728mm(29in./B1), 841mm(A0), 914(36in./A0+),	
	1030mm(B0), 1118mm(44in/B0+)	1030mm(B0), 1118mm(44in/B0+), 1270mm(50in.),	
		1372mm(54), 1524(60in.)	
Roll Paper Remaining	The remaining amount is managed by the barcode pr	nt on Roll paper.	
Control Panel			
Colour & Size	2.7" Colour LCD		
Number of Dots	960 x 240 pix.		
Connectivity	-		
Standard	Hi-Speed USB		
Ethernet	1000BASE-T (Recommended) / 100BASE-TX		
Control Code	ESC/P raster		
	LOO/F Tasici		
Memory	100	4.500	
Main	1GB	1.5GB	
Software			
PC Software	User's Guide(EN) Network Guide(EN), LFP RemotePanel 2, EpsonColorCalibrationUtility, EpsonNet Setup,		
	EpsonNet Config, EpsonNet Print (Windows only)		
Printer Web Function	'Remote Manager' HDD utility - Control of HDD functions		
Software from Web Download	LFP Accounting Tool (Job monitoring, consumable cost tracking), HDD Utility software (Web download)		
Electrical Specifications	<u> </u>		
oltage	AC100-240V 50/60Hz		
-			
Rated Current	5A		
Power Consumption	Operating: Approx. 95W; Sleep: Approx. 2.8W *Interface is 1000BASE-T; Power off (Stand-by): Less than 0.5W		
Recommended Operating			
Temperature	Operating: 10°C - 35°C; Storage: -20°C - 40°C		
Humidity	Operating: 20% - 80% (no condensation); Storage: 5% - 85% (no condensation)		
Acoustic Noise Level			
Sound Pressure Level	Approx 50.5dB (A)	Approx 51.1dB (A) less than	
Sound Power Level	Approx 65.3dB (A)	Approx 67dB (A) less than	
	- ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '	_ · · · · · · · · · · · · · · · · · · ·	

Dimensions & Weight SC-P10070 Weight: 126kg 1145 mm (45") 760 mm 1879 mm (29.9")SC-P20070

Weight: 171kg 1145 mm (45")760 mm 2415 mm (29.9")(95.0")

*1 Figures represent print times only for Epson test sample image (A1 size) as shown, produced on Premium Photo paper.



A1:588×735mm

Ink Cartridge Compatibility

700 ml Ink Cartridges

 Photo Black 	C13T809100	
Cyan	C13T809200	
Magenta	C13T809300	
Yellow	C13T809400	
Light Cyan	C13T809500	
 Vivid Light Magenta 	C13T809600	
Dark Grey	C13T809700	
 Matte Black 	C13T809800	
Grev	C13T809900	

C13T809000

Supplies & Optional Accessories

Auto Cutter Spare Blade C13S210040 Cleaning Stick C13S090013 Maintenance Box C13T619300 Auto Take-up Reel Unit C12C932201 Roll Adapter C12C932231 Adobe® PostScript® 3™ Expansion Unit C12C891131 Hard Disk Unit C12C848031

©2023 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Print samples shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct as of April 2023

EPSON INDIA PVT. LTD.

System Requirement

12th Floor, The Millenia, Tower A, No.1 Murphy Road, Ulsoor, Bangalore 560 008 Tel: 080-4566 5000, Fax: 080-4566 5005

Scan the QR code or Click here to contact an Epson representative close to you.

CONTACT EPSON TODAY! EMAIL: pravin@eid.epson.co.in

Windows XP/Vista/7/8/8.1 (32/64bit) or later

Macintosh Mac OS X10.6.8 or later

 ${\it CPU: Core\ 2\ Duo\ 3.05GHz;\ Memory: Memory\ more\ than\ 1GB;\ HDD: Free\ space\ more\ than\ 32GB}$

CPU : Core 2 Duo 3.05GHz; Memory : Memory more than 1GB; HDD : Free space more than 32GB





Epson Helpline: For product info or service - 1800 425 0011 For service: 1800 123 001 600 (9AM - 6PM) (Mon-Sat) Email: Ifp@epsonindia.in

Dealer's Stamp