

EPSON


Real 4K Home Projector

CREATE YOUR OWN IMMERSIVE
BIG-SCREEN EXPERIENCE

EH-QB1000B



EH-LS9000W



SPECIFICATIONS

EH-QB1000B



EH-LS9000W



Projection System				
Specification of Main Parts	LCD	Size		
		Driving Method		
		Aspect Ratio		
	Projection Lens	Type		
		F-Number		
		Zoom Ratio		
		Throw Ratio Range		
		Screen Size		
		Projected Distance		
	Light Source	Type		
		Light Source Life (Normal)	Light Output: 100%	
Resolution on Screen (Max)	Resolution	*Pixel shifting technology achieves		
	Pixel Number			
Color Light Output		Color Mode: Dynamic, Light Output: 100%, Zoom: Wide, Lens shift: V Center / H Center, Scene Adaptive Gamma: OFF, Dynamic Tone Mapping OFF		
Contrast	Dynamic	Color Mode: Dynamic, Light Output: 100%, Zoom: Wide, Lens shift: V -50% or 50% / H Center, Dynamic Contrast: High speed or Normal, Scene Adaptive Gamma: OFF, Dynamic Tone Mapping: OFF		
Color Reproduction				
High Dynamic Range				
Hybrid Log Gamma				
Dynamic Tone Mapping				
Adjustment Function	Image	Color Mode		
		Geometry Correction	H Keystone V Keystone	Zoom: Tele with Standard Zoom Lens Zoom: Tele with Standard Zoom Lens
Control I/O	RS-232C	D-sub 9pin		
USB-I/O	Type A			
	Type B			
Network I/O	Wired LAN	RJ45	RJ45	
Operating Altitude		over 1500 m / 4921 ft: with High altitude mode		
Start-up Period				
Cool-down Period				
Exhaust Direction				
Intake Direction				
Power Supply Voltage				
Power Consumption	220-240V Area	LD On (Power consumption: Normal)	Light Output: 100%	
Dimension	Exclude Feet (W x H x D)			
Weight				
Fan Noise	Power consumption: Normal/ ECO			

RGB liquid crystal shutter projection system	
0.74-inch wide panel	0.74-inch
Poly-silicon TFT active matrix	
16:9	
Power zoom, Power focus	
2.0 - 3.0	
1 - 2.1	
1.35 - 2.84	
50" to 300"	
Standard size: 100" screen 3.00 - 6.30 m	
Laser Diode	
20000 hours	
4K*	
8,294,400 dots (1,920 x 1,080 x 4)	
3300 lm	2200 lm
over 5000000:1	over 2500000:1
Up to 1.07 billion colors	
Yes (HDR10, HDR10+, HLG)	
Yes	
Yes	N/A
Dynamic	
Vivid	
Cinema	
Natural	
-	Bright Cinema
-30 degrees to +30 degrees	
-30 degrees to +30 degrees	
1	
2	
1	
1	
0 m to 3048 m <0 ft to 10000 ft>	
Less than 8 seconds	
Warm-up period: 30 seconds	
Instant off	
Front	
Side	
100 - 240 V AC +/- 10%, 50/60 Hz	
328 W	302W
520 x 169 x 447 mm	520 x 193 x 447 mm
Approx. 28.2 lbs. / 12.8 kg	Approx. 28.0 lbs. / 12.7 kg
32 dB/ 22 dB	30 dB/ 22 dB



Epson Hong Kong Limited
Unit 715-722A, 7/F Trade Square, 681 Cheung Sha Wan Road,
Cheung Sha Wan, Kowloon, H.K.
*Please call our sales hotlines for demonstration at our showroom.

Epson Authorized Customer Service Centre
Wah Fung Computer Services Ltd.
Unit 901, 9/F, Westin Centre, 26 Hung To Road,
Kwun Tong, Kowloon, Hong Kong

HK Sales Hotline : (852) 2827 8711
HK Technical Hotline : (852) 2827 8911
Macau Hotline : (853) 6516 4693
URL: www.epson.com.hk

JUL25-01-PROJECTOR