

SPECIFICATION SHEET

EB-PU1007W WUXGA 3LCD Laser Projector with 4K Enhancement¹



Product shown with lens Lens sold separately.

Premium, compact large-venue laser projector with 4K Enhancement¹.

Best-in-Class Color Brightness² — 7,000 lumens Color/White Brightness³ from a compact large-venue laser projector

Exceptional widescreen display – native WUXGA with 4K Enhancement Technology¹ (1920 x 1200 x 2); accepts 4K content and provides up to 4.6 million pixels onscreen

Worry-free operation — features a virtually maintenance-free 20,000-hour laser light source and air filter⁴

Simplified installation features – 11 optional powered lenses including ultra short throw with 0.35 throw; inputs including HDBaseT[®] and HDMI[®] (HDCP 2.3)

NFC function built-in⁵ — reduce installation time of multiple projectors; read and write setting information using Epson's mobile app

Clip-on optional external camera – access powerful automated tools including auto color calibration⁶, screen matching of multiple projectors⁷, tiling assist⁶ for edge blends and the stacking assist⁹ function

Lifelike images — high native contrast ratio, HDR support and scene adaptive gamma correction for more realistic images and easy-to-read presentations

Optional external air filter — extend the filter maintenance cycle in dusty environments

Dynamic projection capabilities — advanced built-in edge blending, image warping and shape overlay features for a variety of applications; direct content playback from USB storage media

Customized performance — brightness modes to maximize light-source life and provide a consistent brightness level

Powerful remote management — control and monitor projector status via the Epson[®] Projector Management app for Windows[®]







Large Venue



EB-PU1007W WUXGA 3LCD Laser Projector with 4K Enhancement¹

Specifications

Projection System High-Aperture Epson 3LCD, 3-chip technology

Projection Method Front/rear/ceiling mount Driving Method Poly-Silicon TFT Active Matrix Pixel Number 2,304,000 dots (1920 x 1200) x 3 Signal Input Maximum Display Resolution: 4096 x 2160 (resizing display) Display Resolution: 1920 x 1200 pixels Native Resolution WUXGA with 4K Enhancement¹ (1920 x 1200 x2)

Resolution on Screen WUXGA with 4K1 Enhancement/4.6 million pixels

Aspect Ratio Supports 4:3, 16:10, 16:9*, 21:9* * With vertical image shift control within letterbox area.

Pixel Arrangement Cross stripe Color Brightness³ Color Light Output: 7,000 lumens White Brightness³ White Light Output: 7,000 lumens Contrast Ratio 2,500,000:1 (Dynamic Contrast: On) Brightness Uniformity (Typical) 85% Color Reproduction Up to 1.07 billion colors

Keystone Correction Vertical: ±45 degrees; Horizontal: ±30 degrees

Illumination Technology Laser Phosphor

Projection Lens (Standard)

See website for information on optional lenses. Standard Lens ELPLM08 (sold separately) Type Powered shift/focus/zoom F-Number 1.7 - 2.3 Focal Length 24.0 mm - 38.2 mm Zoom Ratio Optical zoom 1.0 - 1.6x Throw Ratio Range 1.45 - 2.32 Lens Shift Vertical: ±67%; horizontal: ±30%

Other

Operating Temperature 32 °F to 113 °F (0 °C to 45 °C) Power Supply Voltage 100 V - 240 V ±10%, 50/60 Hz AC **Power Consumption** 448 W (Normal, Custom)

379 W (Medium, Quiet, Extended)

2.0 W Standby (Communication on)

0.5 W Standby (Communication off)

Fan Noise 33 dB (Normal Mode), 31 dB (Medium Mode),

29 dB (Eco Mode) Security Security cable hole, lens lock, Kensington

lock provision, wireless LAN unit lock

Video I/O

Input Signal Input Video Signal (HDMI, DVI-D and HDBaseT ports) 480i/480p/576i/576p/720p/1080i/1080p/ 3840 x 2160/4096 x 2160 - Max PC graphics: 2560 x 1600 Auto Power On Signal Detection on HDMI/Plug-In Detection (HDMI, VGA 15pin) Sleep Mode Yes (with timer) **HDMI CEC Control** Yes

Interfaces

DVI-D x 1 HDMI (HDCP 2.3) x 1 HDBaseT x 1 RGB D-Sub 15pin Variable Audio Out: Mini Stereo x 1 USB Connector Type A x 2 USB Connector Type B x 1 Serial: RS-232C x 1 Remote Stereo Mini Network: RJ-45



Dimensions (W x D x H)

Excluding Feet, Lens 21.5" x 17.2" x 6.5" Weight 35.9 lb

Remote Control

Features Power, source search selection, lens shift, zoom, focus, test pattern selection, A/V mute, freeze, user ID, auto, aspect, color mode, number, page up and down, E-zoom, volume, help, menu, enter, esc and pointer functions

Operating Angle

Angle Front: Right/Left: 60 to +60 Upper/Lower +30 to 20 degrees Angle Rear: Right/Left 30 to +30 Upper/Lower +50

to +10 degrees **Operating Distance** 98 ft

Eco Features RoHS compliant Recyclable product¹⁰ Epson America, Inc. is a SmartWay® Transport Partner¹¹

Support

Epson Connection^{SN}

Pre-sales support: U.S. and Canada 800-463-7766 Internet website: www.epson.com

Service Programs

The projector has a limited warranty of 3 years. Epson Road Service program with free Next-Business-Day replacement¹ PrivateLine® dedicated toll-free support (U.S. and Canada only)

What's in the Box

EB-PU1007W Projector, power cable, remote control with 2 batteries, cable cover, lens connector cap, user guide and warrantv sheet

Ordering Information

EB-PU1007W V11HA34920 ELPLAF46 V13H134A46 V13H134AD0 External Air Filter (ELPAF63) Ultra Short Throw Lens (ELPLX01S) V12H004X0A Ultra Short Throw Lens - White (ELPLX01WS) V12H004Y0A V12H004UA3 Short Throw #1 Zoom Lens (ELPLU03S) Short Throw #2 Zoom Lens (ELPI LI04) V12H004U04 Wide Throw #1 Zoom Lens (ELPLW05) V12H004W05 Wide Throw #2 Zoom Lens (ELPLW06) V12H004W06 Wide Throw #3 Zoom Lens (ELPLW08) V12H004W08 Middle Throw #1 Zoom Lens (ELPLM08) V12H004M08 Middle Throw #2 Zoom Lens (ELPLM15) V12H004M0F V12H004M0A Middle Throw #3 Zoom Lens (ELPLM10) Middle Throw #4 Zoom Lens (ELPLM11) V12H004M0B Long Throw Zoom Lens (ELPLL08) V12H004L08 External Camera (ELPEC01) V12HA46010 Rigging Frame (ELPMB59) V12H996A01 Wireless LAN Module (ELPAP11) V12H005A02 Projector Ceiling Mount (ELPMB67) V12HA54010 Suspension Adapter (ELPFP15) V12HA55010

1 4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen. | 2 Color brightness measured per IDMS 15.4. Additional colors and picture modes tested. Top-selling Epson 3LCD projectors vs. comparable top-selling 1-chip DLP projectors based on NPD sales data for October 2019 - September 2020. COLOR BRIGHTNESS WILL VARY BASED ON USAGE CONDITIONS. | 3 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 4 No required maintenance for the light source and filter up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 – 0.20 mg/m3 of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. | 5 NFC requires use of a device that includes NFC and may require additional software. | 6 Requires Epson external camera. | 7 Requires an Epson external camera for each projector. | 8 Requires Epson external camera for each projector and the Epson Projector Professional Tool App. | 9 Requires Epson external camera for each projector. | 10 For convenient and reasonable recycling options, visit www.epson.com/recycle | 11 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. I 12 Expedited shipping not available in all areas. Road Service orders must be placed and processed by 3 p.m. Eastern Time for Next-Business-Day delivery.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future" eco.epson.com

Epson America, Inc.

3131 Katella Ave., Los Alamitos, CA 90720



185 Renfrew Drive, Markham, Ontario L3R 6G3

SmartWay Transport Partner

www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PrivateLine is a registered trademark and Epson Connection is a service mark of Epson America, Inc. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and other countries. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2022 Epson America, Inc. Com-SS-Oct-13 CPD-61029R2 12/22 Contact: