

## PowerLite® L895E

8,000-Lumen 3LCD Laser Projector with 4K Enhancement



Experience an ultra bright and compact projector with pro-level features.







**Ultra bright, true-to-life images** — 3-chip 3LCD technology and 8,000 lumens of equal color and white brightness<sup>2</sup>

**WUXGA with 4K Enhancement Technology¹** — accepts 4K content and displays double HD resolution on-screen; enjoy a visibly sharper, more detailed picture even at close viewing distances

**Large, versatile display options** — easily create a display up to 500" diagonal in 16:10, plus ultra wide 16:6 and 21:9 aspect ratios for enhanced content display and visibility

**Simplified installation** — compact and lightweight design featuring a wide vertical and horizontal lens shift, 1.6x optical zoom, 360-degree mounting, built-in geometric correction tools and a universal VESA mounting pattern

 ${\bf Low\ maintenance}$  — up to 30,000-hour laser light source and air filter  $^{3}$  in Extended Mode

**Wireless networking and content sharing**<sup>4</sup> — reliable wireless connectivity for screen casting<sup>4</sup>, along with direct connection to the cloud-based service, Epson Projector Management Connected and WPA3-Enterprise security

**Built-in NFC** $^5$  — reduces installation time of multiple projectors; read and write setting information using the Epson Projector Config Tool App

**Optional attachable PixAlign™ camera** — adds powerful multi-projector tools including screen matching<sup>6</sup>, auto color calibration<sup>6</sup>, blending assist<sup>7</sup> for super wide displays and simple stacking<sup>7</sup> without an external PC

**Over-the-air updates**<sup>8</sup> — allows user to optionally be alerted when a Firmware update is available

 $\bf Enhanced\ connectivity\ -\ HDBaseT^{\it @}\ and\ HDMI^{\it @}\ two\ in\ and\ one\ out\ for\ daisy-chaining\ and\ signal\ monitoring$ 

# **EPSON**®

#### **Specifications**

Projection System RGB liquid crystal shutter projection system Projection Method Front/rear/ceiling mount LCD Size 0.67" (C<sup>2</sup>Fine)

Driving Method Poly-Silicon TFT Active Matrix Pixel Number 2,304,000 dots (1920 x 1200) x 3 Native Resolution WUXGA with 4K Enhancement<sup>1</sup> (1920 x 1200 x 2)

Resolution On-Screen WUXGA with 4K Enhancement<sup>1</sup>/ 4.6 million pixels

Resize  $640 \times 480$ ,  $800 \times 600$ ,  $1280 \times 1024$ ,  $1400 \times 1050$ Aspect Ratio Supports 4:3, 16:10,  $16:9^*$ ,  $16:6^*$ ,  $21:9^*$ \* With vertical image shift control within letterbox area.

Pixel Arrangement Cross stripe

Color Brightness<sup>2</sup> Color light output: 8,000 lumens White Brightness<sup>2</sup> White light output: 8,000 lumens

Contrast Ratio Over 5,000,000:1
Brightness Uniformity (Typical) 88%
Color Reproduction Up to 1.07 billion colors
Size (Projected Distance) 50" – 500"
Projected Distance 80" screen 2.33 m – 3.78 m
Lens Shift (Manual) Vertical: ±50%; Horizontal: ±20%

**Keystone Correction** Vertical: ±30 degrees; Horizontal: ±30 degrees

**Light Source** Laser Diode

Laser Light Source Life<sup>3</sup> Normal: 20,000 hours; Quiet: 20,000 hours; Extended: 30,000 hours

#### **Projection Lens (Standard)**

Type Optical Zoom (manual)/Focus (manual)

**F-Number** 1.5 - 1.7

Focal Length 20.0 mm – 31.8 mm Zoom Ratio 1.0 – 1.6x (optical) Throw Rate Range 1.35 – 2.20 (optical) Lens Cover Lens cap (without string)

#### Wireless Specifications

Frequency Type (Modulations) 802.11 b/g/n/ac/ax (2.4 GHz) Supported Security Type Quick Mode: Open, WPA2/WPA3-PSK, WPA2/WPA3-EAP; Advanced Mode: WPA/WPA2-PSK, WPA/WPA2-EAP

#### Other Features

Operating Temperature 32 °F to 113 °F (0 °C to 45 °C)
Power Supply Voltage  $100 \text{ V} - 240 \text{ V} \pm 10\%$ , 50/60 Hz AC
Auto Power On Signal Detection on HDMI/Plug-In Detection
Sleep Mode Yes (with timer)

**HDMI CEC Control** Yes **Power Consumption** 

470 W (Normal Mode) 341 W (Quiet and extended) 2.4 W (Standby comm on)

0.3 W (Standby comm off)

Fan Noise 36 dB (Normal Mode); max. 26 dB (ECO Mode)

Security Security cable hole, Kensington® lock provision

Miracast® Yes Epson iProjection™ Yes (V4) Split Screen<sup>9</sup> Yes (Up to 2 screens)

#### Interfaces

HDMI (HDCP 2.3) x 2 HDMI Out x 1 HDBaseT x 1 Variable Audio Out: Mini Stereo x 1 USB Connector Type-A x 1 USB Connector Type-B x 1 Serial: RS-232c x 1 Wired LAN RJ45 x 1 Wireless I AN: Built-in

#### **Other Features (Continued)**

A/V Mute Yes Camera Yes Speaker(s) 10 W (mono) Content Playback Yes Quick Corner Yes Corner Wall Yes Curved Surface Yes Edge Blending Yes

Screen Sharing Yes

#### **Effective Scanning Frequency Range (Digital)**

Pixel Clock 25.1 MHz – 594 MHz Horizontal 26 kHz – 135 kHz

Vertical 23.98/24/25/29.97/30/50/59.94/60 Hz

#### **Dimensions (W x D x H)**

Excluding Feet 17.32" x 11.97" x 4.80" Including Feet 17.32" x 13.39" x 5.43" Weight 18.7 lb

#### **Network and Remote Control**

Features Power, source search selection, A/V Mute, number input, menu, esc, select, Freeze, ID, Customize, E-Zoom, mute, volume, playback control and pointer functions

Operating Angle Rear: Right/Left: -55 to +55 degrees; Upper/ Lower: +75 to +15 degrees; Front: Right/Left: -30 to +30 degrees; Upper/Lower: 0 to +60 degrees

Operating Distance 26 ft (8 m)

Network Control PJLink, Creston Integrated partner, Crestron Connected V2 with XiO Cloud, Extron IP link, Extron XTP, AMX, Control4

### Eco Features

RoHS compliant

End-of-life options available 10

Epson America, Inc. is a SmartWay® Transport Partner<sup>11</sup>
Design and Manufacturing centers utilize 100% renewable electricity
Dynamic Contrast (ECO) Mode reduces power consumption by 36%

#### **Limited Warranty and Service**

Warranty Three-year limited in the U.S. and Canada
Service Whole unit exchange, usually Next-Business-Day
Toll-free telephone support, Monday through Friday
Epson Connection™

Pre-Sales Support (U.S. and Canada): 800-463-7766

Website: www.epson.com



#### Epson Preferred Plus™ Extended Service Plan12

1-Year Next-Business-Day Whole Unit Exchange<sup>13</sup> EPPEXPE1 2-Year Next-Business-Day Whole Unit Exchange<sup>13</sup> EPPEXPE2 (available for up to a total of 5 years of continuous coverage)

#### What's Included

PowerLite® L895E laser projector, power cable, projector remote control with batteries, Quick Reference card, cable cover

#### **Ordering Information & Accessories**

PowerLite® L895E	V11HB24120
Replacement Air Filter (ELPAF65)	V13H134AF0
Custom Micro-Adjustable Projector Mount (ELPMBPRH)	V12H809001
Universal Projector Mount (ELPMBPJG)	V12H808001
PowerLite Pilot™ 3 (ELPCB03)	V12H927020
PixiePlus	ELPSP10
PixAlign Camera (ELPEC01)	V12HA46010
External Speaker (ELPSP02)	V12H467020
DC-07 Document Camera	V12H759020
DC-13 Document Camera	V12H757020
DC-21 Document Camera	V12H758020

1 4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen. | 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with ISO 21181. | 3 No required maintenance for the light source and filter for up to 30,000 hours (Normal Mode). Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. |5 NFC requires use of a device that includes NFC and may require additional software. |4 The projector supports direct peer-to-peer wireless casting of local content from Miracast-enabled devices or via the Epson iProjection app. For best performance when using Epson iProjection, it is recommended that the projector and connecting devices be configured on a network, either through the Ethernet port on the projector or via a wireless connection. The Epson iProjection App does not support all files and formats. See epson.com/iprojection for details. |6 Using separate camera for each projector. |7 Requires Epson external camera for each projector and may require Epson Projector Professional Tool app. |8 Requires an active Internet connection for alerts and Firmware download. |9 Split Screen feature requires remote control. Consult your user manual for input combinations. | 10 For convenient and reasonable recycling options, visit epson.com/recycle | 11 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. | 12 Product comes with a 3-year limited warranty with the option to purchase Extended Service Plans up to a total of 5 years of continuous coverage. Extended Service Plan can be purchased at any time that you are covered under an Epson limited war

See the latest innovations from Epson Business Solutions at epson.com/forbusiness



Epson America, Inc.

3131 Katella Ave., Los Alamitos, CA 90720

**Epson Canada Limited** 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com

Specifications and terms are subject to change without notice. EPSON, the 3LCD logo and PowerLite are registered trademarks and Epson iProjection is a trademark of Seiko Epson Corporation. Epson Connection, Epson Preferred Plus, Pilot and PixAlign are trademarks of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. Miracast<sup>®</sup> and Wi-Fi<sup>®</sup> are registered trademarks of Wi-Fi Alliance<sup>®</sup>. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2025 Epson America, Inc. CPD-65492 3/25