

ON-DEMAND COLOUR LABELS FOR COST SAVINGS AND INCREASED EFFICIENCY.



Epson's TM-C3510 deliver high quality colour labels on-demand to improve efficiencies and reduce labeling costs. With a high printing speed of up to 103mm per second, excellent resolution and reliability, they are the perfect choice for industrial, chemical, warehousing, medical and other labeling applications. Now you can do away with expensive preprinted labels and simply print them whenever you need.



High Speed Printing High Capacity Inks USB 2.0 Ethernet



TM-C3510

ENGINEERED FOR BUSINESS

Colour Labels On-Demand

Designed to meet the needs of high mix, low-volume applications that require multiple label variations.

Better Inventory Management

Save up to 50% on labeling costs by reducing the need to stock up on different types of preprinted labels.

BS5609 Certified

Printers used together with pigment inks and approved media, are BS5609 certified to print GHS compliant labels.

MODEL NUMBER	TM-C3510			
Print Technology	Technology	MicroPiezo® inkjet technology, serial inkjet dot matrix		
	Colour	Four-colour printing, individual ink cartridge (DURABrite Ultra pigment ink: C, M, Y, K)		
Ink Cartridge	Colour (Pigment Ink)	Cyan, Magenta, Yellow, Black		
	Model	SJC23P(C), SJC23P(M), SJC23P(Y), SJC23P(K)		
Print Resolution	Up to 720 × 360 dpi			
Printing Width	Max. 104mm (Max. 1,474 dot positions / 360dpi)			
Print Speed	Max. 103mm/sec. (Printing Width: 56mm, 360 × 360 dpi, Bi-directional Printing)			
Interfaces	Hi-Speed USB 2.0 and Ethernet (100BASE-TX / 10BASE-T)			
Print Font	Not equipped with print fonts; prints all data as the graphic data			
Barcode Font (Printer Driver Built-in)	Barcode: UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded Two-dimensional symbols: PDF417, QR Code, Maxi Code, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, DataMatrix, Aztec Code			
Media Source	Roll-fed, Fanfold			
Media Types	Plain, Matte, Glossy, Synthetic			
Paper Specifications	Width	Thickness		
	Media Form			
Roll	Continuous Paper	30 - 108 mm		0.084 - 0.124 mm
	Black Mark Continuous Paper			
Fanfold	Full-page Label	Label Width: 25.4 - 108 mm		Plain Label, Matte Label,
	Transparent Full-page Label	Backing Paper Width:		Synthetic Label:
	Die-cut Label (gap)	30 - 112 mm		0.128 - 0.195 mm
	Transparent Die-cut Label	Glossy Label: 0.184mm		
Black Mark Die-cut Label	Label width: 25.4 - 108 mm		Plain Label, Matte Label,	
	Backing paper Width: 30 - 112 mm		Synthetic Label: 0.129 - 0.143 mm Glossy Label: 0.184mm	
Wristband	30mm		0.190 - 0.225 mm	
Black Mark Continuous Paper	50 - 108 mm		0.124 - 0.128 mm	
Black Mark Die-cut Label	Label Width: 46 - 108 mm,		0.161 - 0.164 mm	
	Backing Paper Width: 50 - 112 mm			
External Roll Diameter	Max. 101.6mm			
Paper Core External Diameter	Plain Label, Matte Label, Synthetic Label: min. 44.1mm Glossy Label, Wristband: min. 56.8mm			
Number Of Folds	Fanfold Paper: 500 or Less			
Winding Direction	Face Out			
Autocutter Life	Paper	Die-cut Label	Full Page Label	Wristband
	Plain: 1,500,000 cuts	Plain, Matte, Glossy: 1,500,000 cuts	Synthetic: 100,000 cuts	200,000 cuts
	Matte: 750,000 cuts	Synthetic: 500,000 cuts	Glossy: 300,000 cuts	
			Matte: 500,000 cuts Plain: 750,000 cuts	
Temperature / Humidity	Printing	Printing: 10 - 35°C / 20 - 80% RH; Barcode Printing: 15 - 35°C / 20 - 80% RH		
	Storage	-20 - 60°C / 5 - 85% RH (Without Ink)		
Overall Dimensions (D x W x H) *	283 x 310 x 261 mm			
Mass	Approx. 12.0kg			
Power Supply	Dedicated AC Adapter			
Power Consumption	Printing	Approx. 30W (mean)		
	Standby	Approx. 2.5W (mean)		
Rated Voltage	100 - 240 V			
Rated Frequency	50 - 60 Hz			
Reliability	MTBF	88,000 hours		
	MCBF	9,800,000 passes		
EMC Standards	VCCI Class B, FCC / ICES-003 Class B, CE Marking, C-Tick Class B, CCC, BSMI, MIC, Ukraine EMC			
Safety Standards	UL, CSA, TÜV (EN60950-1), GOST, CCC, BSMI			
Operating System	Windows® XP SP2 (64bit) / SP3 (32bit), Windows Vista® SP2 (32bit / 64bit), Windows® 7 SP1 (32bit / 64bit), Windows Server® 2003 R2 SP2 (32bit / 64bit), Windows Server® 2008 R2 SP2 (32bit / 64bit) Windows Server® 2012, Windows® 8 (32bit / 64bit), Windows Server® 2008 R2 SP1			

Dimensions & Weight

TM-C3510

Weight: Approx. 12kg (26.45lbs)



Option

C32C811281 OT-WA34 Wristband Attachment

Consumables for TM-C3510

C33S020580 SJMB3500 Maintenance Box
C33S020584 SJC23P(C) Ink Cartridge Cyan
C33S020585 SJC23P(M) Ink Cartridge Magenta
C33S020586 SJC23P(Y) Ink Cartridge Yellow
C33S020578 SJC23P(K) Ink Cartridge Black

© 2016 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Print samples shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct at time of printing
Printed December 2017

Usage Restrictions:

When this product is used for applications requiring high reliability/safety such as transportation devices related to aviation, rail, marine, automotive etc.; disaster prevention devices; various safety devices etc.; or functional/precision device etc., you should use this product only after giving consideration by inclusion of fail-safes and redundancies into your design to maintain safety and total system reliability. Because this product was not intended for use in applications requiring extremely high reliability/safety such as aerospace equipment, main communication equipment, nuclear power control equipment, or medical equipment related to direct medical care etc., please make your own judgement on this product's suitability after full evaluation. Epson ColorWorks ink is not intended for direct food contact printing.

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008.

Tel: 080-30515000 Fax: 080-30515005

Regional Offices:

Ahmedabad - 33148500/01, Chennai - 3967 7500, Cochin - 4012 315, Coimbatore - 98942 19200,

Kolkata - 6500 9370/77, Mumbai - 3079 8200, New Delhi - 3312 0300/01, Pune - 3028 6000/05,

Hyderabad - 6463 9640/41



Epson Helpline: For product info or service - 1800 425 0011

For service - 1860 3000 1600 (9AM - 6PM) (Mon - Sat)

Email: pos@eid.epson.in

www.epson.co.in