LARGE FORMAT PRINTERS SURECOLOR[™] SC-S60670L/S80670L





TRUE PERFORMANCE AND RELIABILITY FOR HIGH-VOLUME SIGNAGE PRINTING

The SureColor™ SC-S60670L and SC-S80670L are high-performance eco-solvent signage printers from Epson. These printers feature an array of advanced technologies to get the best of performance, reliability and speed. Complete with Epson's cutting-edge PrecisionCore™ printhead, these printers ensure the highest quality for awe-inspiring prints.



GS3

SC-S60670L ULTRACHROME GS3 INK



MAXIMUM MEDIA WIDTH

163 CM (64")

MAX. INK CAPACITY PER COLOUR

1.5 L





SC-S606701



SC-S806701



PRECISIONCORE

TFP[®] PRINTHEAD

SINGLE





Epson UltraChrome™ GS3 ink is Greenguard Gold certified and meets the French-VOC A+ Class criteria for low chemical emissions

Next-gen Printing Technology

10 COLOURS

Epson's PrecisionCore™ printhead technology and UltraChrome™ GS3 inks for printing in the highest quality with rich colours.

PC-free Convenience

A 6.9 cm (2.7") LCD screen enables hassle-free operation at the push of a button.

PRINT SPEEDS SQM/HR

HIGH QUALITY PRODUCTION

29.4

12.4

12.5

Safe-to-Use, Eco-friendly Inks Epson's UltraChrome™ GS3 inks are

Greenguard certified and have been tested to ensure low chemical emissions.

*Based on 8-pass and 4-pass high-quality printing for production, on banner media

SPECIFICATIONS SURECOLOR™ SC-S60670L/S80670L

EPSON

MODEL NUMBER	SC-S60670L	SC-S80670L	Dimensions and Weight	
Printer Width	163 cm (64")		SC-S60670L Weight: 336 kg (740.75 lbs) (without	ut ink)
Printing Technology			····· g ·······························	
Printhead	PrecisionCore™ TFP [®] Printhead			Î
Nozzle Configuration	360 x 2 nozzles each colour (x4)	360 x 1 x 2 nozzles each colour (x10)		
Maximum Resolution	1440 x 1440 dpi			1,338 m
Minimum Ink Droplet Volume	4.2 pl			(52.67")
Print Speed				
1-pass	95.3 m²/h (360 x 720 dpi)	95.1 m²/h (360 x 720 dpi)		
2-pass	52.3 m²/h (720 x 720 dpi)	52.3 m²/h (720 x 720 dpi)	8	
4-pass	31.6 m²/h (720 x 720 dpi)	26.8 m²/h (720 x 720 dpi)	2,620 mm (103.14")	(34.64")
4-pass (High-quality)	29.4 m²/h (720 x 720 dpi)	31.6 m²/h (720 x 720 dpi)	SC-S80670L	
6-pass	20.7 m²/h (720 x 1440 dpi)	22.8 m²/h (720 x 1440 dpi)	Weight: 328 kg (without ink)	
6-pass (High-quality)	19.5 m²/h (720 x 1440 dpi)	18.2 m²/h (720 x 1440 dpi)	(723.11 lbs)	*
8-pass	14.6 m²/h (720 x 1440 dpi)	13.2 m²/h (720 x 1440 dpi)		
8-pass (High-quality)	12.4 m²/h (720 x 1440 dpi)	12.5 m²/h (720 x 1440 dpi)		
12-pass	8.7 m²/h (1440 x 1440 dpi)	8.8 m²/h (1440 x 1440 dpi)		1,338 m
16-pass	6.8 m²/h (1440 x 1440 dpi)	6.8 m²/h (1440 x 1440 dpi)		(52.67"
Ink System				
Ink Type	Epson UltraChrome™ GS3 ink	Epson UltraChrome™ GS3 ink with Red		
Colours	Cyan, Magenta, Yellow, Black	Cyan, Magenta, Yellow, Black, Light Cyan,	A 10	
000013		Light Magenta, Light Black, Orange, Red, White, Metallic Silver	2,620 mm (103.14")	972 mm (38.26")
Ink Capacity	1.5 L	1.5 L, 500 mL (Metallic Silver)	Ink Cartridge Compatibility	
Paper Handling			1500 mL Ink Cartridges	
Roll Diameter / Weight	Rear roll feed (2" / 3" core with max 250 mm dian	neter and up to 45 kg), Auto take-up reel	 Black 	C13C45P100
Printable Area	Max printing width: 1616 mm, Side Margin: 5 mm both sides, 10 mm with media holding plates		 Cyan 	C13C45P200
Media Width	300 to 1626 mm		Magenta	C13C45P300
Media Thickness	Up to 1 mm		 Yellow Light Cyan 	C13C45P400 C13C45P500
Heaters	Pre- and Platen-heater (30 to 50°C), After-heater (30 to 55°C)		 Light Magenta 	C13C45P600
Control Panel	6.9 cm (2.7") Colour LCD		 Light Black 	C13C45P700
Connectivity			Orange	C13C45P800
Printer Interfaces	Hi-speed USB, 100BASE-TX /1000BASE-T		Red	C13C45P900
Printer Languages	Standard: ESC/P raster		○ White	C13C45PA00
Printer Drivers	NA		 Metallic Silver (500 mL) 	C13C45PB00
Memory	Printer: 512 MB + 128 MB network	Printer: 2 GB, Network : 128 MB	Supplies and Optional Accessories	
Software	Windows - CD Installer - Communication Driver - EPSON Manuals Launcher - Operators Guides - General Information - Epson Edge Dashboard - EpsonNet Config - EpsonNet Setup - EpsonNet Print - Epson Software Updater - Epson Edge Print		Cleaning ink (700 mL)	C13C44A500
			Maintenance Parts Kit	C13S210044
			Ink Cleaner	C13T699300
Other Features	Auto Head Alignment Technology (Media feed and Bi-directional), Auto Nozzle Check System, Mail Report System, Custom Paper Backup		Cleaning Stick	C13S090013
			Clean Room Wiper	C13S090016
Power and Operating Requirements			Waste Ink Bottle	C13T724000
Power Requirements	AC 100-120 V or 200-240 V, 50/60 Hz		Additional Print Drying System Media Holding Guide	C12C932381 C12C932411
Power Consumption	Operating: 865 W, Ready: 525 W	Operating: 640 W, Ready: 400 W,	Media Holding Guide	0120932411
	Sleep: 23 W, Standby: 1.8 W	Sleep: 24 W, Standby: 1.5 W		
Recommended Operating			© 2023 Epson India Pvt. Ltd. All Rights F Reproduction in part or in whole, without	
Temperature and Humidity	15 - 35°C, 20 - 80 % RH (non-condensing)		permission from Epson, is strictly prohibi	ted. EPSON and
Printer Dimensions			EXCEED YOUR VISION are registered tra Epson Corporation. All other products na	
B: .	2,620 x 880 x 1,338 mm (W x D x H) (storage)	2,620 x 972 x 1,338 mm (W x D x H) (storage)	company names used herein are for ider	itification purposes
Dimensions	eee los (other sticl)	328 kg (without ink)	only and are the trademarks or registered respective owners. Epson disclaims any	
Dimensions Weight	336 kg (without ink)			
	Substrate Support System (C12C932361)	Substrate Support System (C12C932361), Optional Additional Print Drying System (C12C932381)	in those marks. Print samples shown are Specifications and product availability are without notice and may vary between co	simulations only. subject to change

Note: RIP Software required to print

Information correct as of April 2023

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1 Murphy Road, Ulsoor, Bangalore 560 008 Tel: 080-4566 5000, Fax: 080-4566 5005

Scan the QR code or Click here to contact an Epson representative close to you.



Dealer's Stamp

CONTACT EPSON TODAY! EMAIL: pravin@eid.epson.co.in



Epson Helpline: For product info or service - 1800 425 0011 For service: 1800 123 001 600 (9AM - 6PM) (Mon-Sat) **Email:** Ifp@epsonindia.in