

PowerLite® L265F 1080p 3LCD Lamp-Free Laser Display with Built-In Wireless



The ultra bright display for impactful presentations and digital signage.

Best-in-Class Color Brightness¹ with 3-chip 3LCD technology — 4,600 lumens of color and white brightness²

Incredible image quality — High Definition 1080p resolution at an exceptional value

High dynamic contrast ratio — up to 2,500,000:1

No lamps to replace ever — solid-state, 20,000-hour, virtually maintenance-free laser light source³

Create amazing effects and experiences — built-in media player with Epson® Projector Content Manager software⁴ includes templates, effects, color filters and customizable options; playlist and playback functions allow for seamless content management for single or multiple PowerLite projectors

Epson Creative Projection App⁴ for iOS® devices — lets you easily create custom content and upload and playback content directly from the projector

Easily project wall-sized images up to 310" diagonal — built-in edge blending and split screen⁵ features for easy, scalable projection

Built-in enterprise-level wireless connectivity with casting capability — supports Miracast® and Epson iProjection™⁶ screen sharing software

360-degree placement capabilities — easily mount or place the projector in any position, from landscape to portrait

Easily manage your fleet — configure, monitor and control up to 2,000 networked projectors at once with the free Epson Projector Management software⁴



Specifications

Projection System RGB liquid crystal shutter projection system
Driving Method Poly-Silicon TFT Active Matrix
Pixel Number 2,073,600 dots (1920 x 1080) x 3
Color Brightness² Color Light Output: 4,600 lumens
White Brightness² White Light Output: 4,600 lumens
Aspect Ratio Supports 4:3, 16:10, 16:9*, 16:6*, 21:9*
 * With vertical image shift control within letterbox area.
Light Source Laser Diode
Laser Light Source Life³
 Normal Mode: Up to 20,000 hours
 Extended Mode: Up to 30,000 hours
Throw Ratio Range 1.32 – 2.12
Size (Projected Distance)
 31" - 310" (0.88 m - 9.06 m)
Keystone Correction (Manual) Vertical: ±30 degrees;
 Horizontal: ±30 degrees
Dynamic Contrast Ratio Over 2,500,000:1
Color Reproduction Up to 1.07 billion colors

Projection Lens

Type Optical zoom (Manual), Focus
F-Number 1.51 – 1.77
Focal Length 18.2 mm - 29.1 mm
Zoom Ratio 1.0 – 1.62

Other

Operating Temperature 32 °F to 104 °F (0 °C to 40 °C) (low altitude: 0 ft – 7,500 ft), 32 °F to 95 °F (0 °C to 35 °C) (high altitude: 7,500 ft – 10,000 ft)
Power Supply Voltage 100 V – 240 V AC ±10%, 50/60 Hz
Auto Power On Signal Detection on HDMI[®]/Plug-In Detection (HDMI, USB, VGA 15-pin)
Sleep Mode Yes (with timer)
Power Consumption
 Normal Mode: 272 W
 Quiet Mode: 208 W
 Standby Mode: 2.0 W
 Energy-Saving Mode: 0.5 W
Fan Noise
 Normal Mode: 37 dB
 Quiet Mode: 27 dB
Security Enterprise Level Security Encryption

Dimensions (W x D x H)

Projector (Including Feet) 12.8" x 4.1" x 11.7"
Weight 9.5 lb

Interfaces

1x D-Sub 15-Pin VGA Input
 1x D-Sub 15-Pin VGA Input/Monitor Out
 1x RCA Composite
 2x HDMI (with CEC Control)
 2x Audio In (3.5 mm stereo mini)
 1x Audio In (Red/White RCA)
 1x Audio Out (3.5 mm stereo mini)
 1x D-Sub 9-Pin RS-232C
 1x USB Type A (with 5 V/2 A power supply)
 1x USB Type B (for copying setting)
 1x Wired LAN RJ-45

Built-in wireless: 802.11 b/g/n (2.4 GHz) (DSSS/CCK, OFDM) 802.11 a/n/ac (5 GHz)* (OFDM)



* Maximum speed and range are achievable when used with same enhanced mode technology. Actual features and performance may vary depending on your computer system, the environment and other factors.

Software

In addition to compatibility with Epson's standard suite of software, this product has a direct playback function via USB. Works with:
 - Epson Projector Content Manager Software⁴ (visit our support pages for the latest version)
 - Epson Creative Projection application⁴

Remote Control

Features Color Mode, A/V Mute, Focus, Zoom, Volume, Spotlight, HDMI, LAN, Keystone, Pattern, Menu, Effect, USB, Split, Computer, Freeze, Aspect, Home

Operating Angle

Front and Rear Remote Sensors
 Up/down: -30 to +30 degrees
 Right/left: -30 to +30 degrees

Operating Distance 20 ft (6 m)

Eco Features

RoHS compliant
 Recyclable product⁷
 Epson America, Inc. is a SmartWay[®] Transport Partner[®]

Support

Epson ConnectionSM

Pre-sales support: U.S. and Canada (800) 463-7766
 Website: www.epson.com

Service Programs 3-year projector limited warranty

Epson Road Service program, dedicated toll-free support (U.S. and Canada only)

What's Included

PowerLite L265F standard-throw laser projector, projector remote control, two (2) AA batteries (for remote), HDMI cable, power cable, cable cover

Ordering Information

PowerLite L265F	V11HA72120
Replacement Air Filter (ELPAF60)	V13H134A60
Soft Carrying Case (ELPKS71)	V12H001K71
Ceiling Mount (ELPMB60W)	V12H963210
Wireless LAN Module (ELPAP11)	V12H005A02
DC-07 Document Camera	V12H759020
DC-13 Document Camera	V12H757020
DC-21 Document Camera	V12H758020

1 Color brightness measured per IDMS 15.4. Additional colors and picture modes tested. Top-selling Epson 3LCD projectors vs. comparable top-selling 1-chip DLP projectors based on NPD sales data for October 2019 – September 2020. COLOR BRIGHTNESS WILL VARY BASED ON USAGE CONDITIONS. | 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 3 No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. | 4 Internet connection required for download. Data usage fee may apply. | 5 Consult your user manual for Split Screen input combinations. | 6 For wireless functionality, including via the Epson iProjection App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection App does not support all files and formats. See www.epson.com for details. | 7 For convenient and reasonable recycling options, visit www.epson.com/recycle | 8 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

Learn more about how our products can empower your institution. Visit us at www.epson.com/foreducation

Better Products for a Better Future[™]
eco.epson.com



Epson America, Inc.
 3131 Katella Ave., Los Alamitos, CA 90720

Epson Canada Limited
 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. EPSON and PowerLite are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and Epson iProjection are trademarks of Seiko Epson Corporation. Epson Connection is a service mark of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. Miracast[®] is a registered trademark of Wi-Fi Alliance[®]. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2023 Epson America, Inc. Com-SS-Oct-13 CPD-62988 1/23

