



Impeccable Photo Quality, Unparalleled Colour Accuracy.

Add a touch of extraordinary to your photo printing with the Epson SureColor™ SC-P7530 (61 cm (24")) and SC-P9530 (112 cm (44")) large format photo printers. Epson's UltraChrome™ PRO12 ink is perfectly paired with the revolutionary PrecisionCore™ MicroTFP® printhead for high-quality prints at outstanding speeds. Expect nothing short of brilliance in every print.



SC-P7530



SC-P9530

SPECIFICATIONS
SURECOLOR™ SC-P7530/P9530



MODEL NUMBER	SC-P7530	SC-P9530
Printer Width	61 cm (24")	112 cm (44")
Printing Technology	PrecisionCore™ Inkjet Technology, Variable-sized Droplet Technology	
Printing Method	MicroTFP® Printhead	
Nozzle Configuration	9,600 nozzles (800 nozzles x 12 channels x 1 head)	
Maximum Resolution	2,400 x 1,200 dpi	
Minimum Ink Droplet Volume	3.5 pl	
Print Speed	97 sec (Level 1) 122 sec (Default) Premium Glossy Photo Paper 170 g/m² A1 size / ISO Bike	219 sec (Level 1) 285 sec (Default) Premium Glossy Photo Paper 170 g/m² B0 size / ISO Bike
Ink System	UltraChrome™ PRO12 Pigment Ink	
Ink Type	Cyan, Vivid Magenta, Yellow, Light Cyan, Vivid Light Magenta, Orange, Green, Violet, Photo Black,	
Colours	Matte Black, Gray, Light Gray	
Ink Capacity	700 mL	
Paper Handling	Friction Feed	
Paper Path	2" roll core media: Max. 103 mm/6 kg, 3" roll core media: Max. 150 mm/6 kg	
Maximum Roll Diameter / Weight	Roll Paper: 254 mm to 620 mm, Cutsheet: 210 mm to 620 mm	
Paper Width (Roll)	Roll Paper: 254 mm to 1118 mm, Cutsheet: 210 mm to 1118 mm	
Paper Thickness	Roll : 0.08 mm to 0.5 mm, Cutsheet : 0.08 mm to 1.5 mm	
Control Panel	10.9 cm (4.3") touch screen	
Connectivity	Super-Speed USB, 100BASE-TX /1000BASE-T	
Printer Interface	USB Interface (Hi-Speed USB/USB), 1000BASE-T/100BASE-TX	
Printer Language	ESC/P raster	
Memory	2 GB	
Power and Operating Requirements	AC 100 to 240 V, 50/60 Hz	
Power Requirements	3.4 - 1.6 A	
Rated Current	Operating: Approx. 85 W	Operating: Approx. 110 W
	Ready: Approx. 32 W	Ready: Approx. 32 W
	Sleep: Approx. 3.4 W	Sleep: Approx. 3.4 W
	Power Off (Standby): Approx. 0.3 W	Power Off (Standby): Approx. 0.3 W
Power Consumption	Operating: 10°C to 35°C, Storage / Packing: -20°C to 60°C, Unpacking: -20°C to 40°C	
Temperature	Operating: 20 - 80% (no condensation), Storage: 5 - 85% (no condensation)	
Humidity	Operating: Approx. 49.5 dB(A), Sleep: Approx. 31.5 dB(A)	
Acoustic Noise Level	Operating: Approx. 7.5 B(A)	
Sound Pressure Level (dB(A))		
Sound Power Level (B(A))		
Utility Software	Windows Install Navi - Printer driver - EpsonNet Setup - EpsonNet Print - EpsonNet Config SE - Epson Software Updater - EPSON manuals - Manual Launcher - Epson Control Dashboard	
Utility Software (Bundled in CD)	Mac Setup Navi - EpsonNet Config SE - Epson Software Updater	
	Windows Install Navi, Web Installer, Firmware Updater, PS Driver, HDI Driver, XPS Driver, Epson	
	Media Installer, EpsonNet Setup Manager, Epson Device Admin, Epson Edge Dashboard, Epson	
	Edge Print, Epson Print Layout, LFP Accounting Tool, Adobe ICC Profiles, Mac Web Installer,	
	Install Navi - Printer driver - EpsonNet Config - Epson Software Updater - Uninstaller - Epson Manuals,	
	Epson Media Installer, Firmware Updater, Linux, Printer driver	
Printer Dimensions		
Storage Dimensions (W x H x D)	1,401 mm x 1,218 mm x 667 mm	1,909 mm x 1,218 mm x 667 mm
Printing Dimensions (W x H x D)	1,401 mm x 1,218 mm x 2,211 mm	1,909 mm x 1,218 mm x 2,211 mm
Weight	121.7 kg	153.8 kg
What's in the box	Printer, Printer Stand, Initial Ink Cartridge, AC Power Cable, Setup Guide, Software CD-ROM, Maintenance Box	
Options	SpectroProofer, SpectroPhotoMeter, iLS30EP, Auto Take Up Reel Unit, Hard Disk Unit, Adobe PostScript 3 Expansion Unit, Roll Media Adapter	
Consumables	Ink Cartridge, Maintenance Box, Auto Cutter Spare Blade, Borderless Replacement Pad Kit	

SC-P7530
Dimensions & Weight
Weight: 121.7 kg



SC-P9530
Dimensions & Weight
Weight: 153.8 kg



Supplies & Optional Accessories

SC-P7530	C11CH12402
SC-P9530	C11CH13402
SC-P7530/9530 PK IC (700 mL)	C13T44N100
SC-P7530/9530 CY IC (700 mL)	C13T44N200
SC-P7530/9530 VM IC (700 mL)	C13T44N300
SC-P7530/9530 YL IC (700 mL)	C13T44N400
SC-P7530/9530 LC IC (700 mL)	C13T44N500
SC-P7530/9530 VL IC (700 mL)	C13T44N600
SC-P7530/9530 LB IC (700 mL)	C13T44N700
SC-P7530/P9530 MK IC (700 mL)	C13T44N800
SC-P7530/9530 LI IC (700 mL)	C13T44N900
SC-P7530/9530 OR IC (700 mL)	C13T44NA00
SC-P7530/9530 GR IC (700 mL)	C13T44NB00
SC-P7530/9530 VI IC (700 mL)	C13T44ND00

© 2025 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is registered trademark of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Information correct as of May 2025.

EPSON INDIA PVT. LTD.
11th Floor, Godrej Centre, Hebbal, Survey No. 26, Bellary Road,
Sahakar Nagar, Byatarayanapura, Bangalore 560 092, Karnataka.
Tel: 080 6939 5000. Fax: 080 6939 5005

Regional Offices:
Ahmedabad 4037 0075, Chennai 4905 5177, Coimbatore 98942 19200, Ernakulam 4012 315,
Hyderabad 4857 0032, Jaipur 4923 119, Kolkata 4603 4714/15/29/30, Mumbai 3079 8200,
New Delhi 4107 3101, 4752 2414, Pune 2998 0641



Epson Helpline: For product info or service - 1800 425 0011
For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon - Sat)
Email: lif@epson-india.in

www.epson.co.in

Dealer's Stamp