


# C12XLB 6-Axis Robot



## Innovative Features. Remarkable Flexibility.

**Ultra high performance and flexibility** — high throughput with heavy payloads and multiple arm configurations to accomplish many of the most demanding tasks with leading-edge precision

**SlimLine design** — compact wrist pitch enables access to hard-to-reach areas in confined spaces; tabletop mounting and 1,400 mm reach available

**Fast cycle times** — high acceleration, smooth motion and fast settling times help maximize throughput with proprietary GYROPLUS® vibration reduction system, plus no ringing or overshoot<sup>1</sup>

**Ultimate ease of use** — intuitive and feature-packed Epson RC+® development software helps create powerful solutions with a simple user interface, integrated debugger and advanced 3D simulator

**Low total cost of ownership** — includes battery-less encoders and Epson RC+ software with no recurring license fee; rich suite of safety features included with RC700E controller; robots are TUV-certified to meet ISO 10218-1 and UL1740 safety standards

**SafeSense™ technology** — standard and advanced safety features allow for increased productivity and worker protection while potentially minimizing machine footprint due to the reduction of physical barriers with a proper risk assessment

**Industrial collaborative workcell tools** — combine SafeSense technology and no-code Epson RC+ Express software to easily develop industrial collaborative solutions with remarkable speed and repeatability

**Built for demanding environments** — Standard and Cleanroom (ISO 4<sup>2</sup>)/ESD models available

**Advanced integrated options** — Vision Guidance, Parts Feeding, Force Guidance, Conveyor Tracking and Fieldbus

**Industry 4.0 ready** — advanced OPC UA for robotics connectivity provides next-level integration and monitoring

Model Name		C12XLB 6-Axis Robot
Mounting Type		Tabletop
Arm Length	P Point: Joints #1 - 5 Center	1,400 mm
	P Point: Joints #1 - 6 Flange Surface	1,480 mm
Repeatability		Joints #1 - 6 ± 0.05 mm
Payload	Rated	3 kg
	Max.	12 kg
Standard Cycle Time <sup>3</sup>		0.50 sec
Max. Motion Range	Joint #1	± 240 deg
	Joint #2	-135 deg ~ +55 deg
	Joint #3	-61 deg ~ +202 deg
	Joint #4	± 200 deg
	Joint #5	± 135 deg
	Joint #6	± 360 deg
Allowable Moment of Inertia	Joint #4	0.70 kg-m <sup>2</sup>
	Joint #5	0.70 kg-m <sup>2</sup>
	Joint #6	0.20 kg-m <sup>2</sup>
User Electric Lines		15-Pin (D-Sub), 8-Pin (RJ45 Cat5e), 6-Pin (Force Sensor)
User Pneumatic Lines		ø6 mm x 2
Brakes		All Axes
Power		AC 200 V - 240 V Single Phase
Power Consumption		2.5 kVA
Power Cable Length		3 m/5 m/10 m
Weight (Cables Not Included)		63 kg
Applicable Controller		RC700E
Installation Environment		Standard/Cleanroom (ISO 4) <sup>2</sup> ESD
Safety Standards		TUV-certified to meet ISO 10218-1, UL 1740, CSA Z434, ISO 13849
What's Included		C12XLB robot and RC700E controller with safety board. Robot power and signal cables. Connector set (I/O, hand I/O and safety circuit connectors).
<b>Options</b>		
Vision Guide CV2		Available
IntelliFlex™ Feeders		Available
Force Guidance		Available
Conveyor Tracking		R12NZ900AA
Epson RC+ 7.0 API		R12NZ920AE
GUI Builder 7.0		R12NZ920AH
Add-On Instructions		Available
Fieldbus Master		Available
Fieldbus Slave (EtherNet/IP, EtherCat®, PROFINET, PROFIBUS, CC-Link, DeviceNet®)		Available
External Control Point (ECP) Option		R12NZ920AF
Teach Pendant		Available
Epson OPC UA for Robots		R19NZ901CE
Vision Guide Camera Mount		R12NZ9003F
Tool Mounting Plate		R12NZ900LQ

### Support

Customer Service  
(562) 290-5920  
service@robots.epson.com

Applications Support  
(562) 290-5930  
applications@robots.epson.com

Sales Inquiries  
(562) 290-5997  
info@robots.epson.com

<sup>1</sup> When operated within specifications. | <sup>2</sup> Complies with ISO Class 4 (ISO 14644-1) cleanroom standards. | <sup>3</sup> Cycle time based on round-trip arch motion (300 mm horizontal, 25 mm vertical) at rated payload setting of tabletop model boost mode (path coordinates optimized for maximum speed).

See the latest innovations from Epson Business Solutions at [www.epson.com/forbusiness](http://www.epson.com/forbusiness)

**Epson America, Inc.**  
3131 Katella Ave., Los Alamitos, CA 90720

**Epson Canada Limited**  
185 Renfrew Drive, Markham, Ontario L3R 6G3

[www.epson.com](http://www.epson.com)  
[www.epson.ca](http://www.epson.ca)

Specifications and terms are subject to change without notice. EPSON, Epson RC+ and GYROPLUS are registered trademarks of Seiko Epson Corporation. IntelliFlex and SafeSense are trademarks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2024 Epson America, Inc. CPD-64528 3/24

### Contact: