

EPSON®

Projectors, Displays & Document Cameras

2025 Line Guide



Optional camera sold separately.

	Budget-Friendly Classroom Projectors		
Note: Highlighted boxes indicate step-ups between models within a series.			
Epson Model	PowerLite® E24	PowerLite X49	PowerLite W49
Product Code	V11HB51020	V11H982020	V11H983020
Replacement Lamp Code	V13H010L97	V13H010L97	V13H010L97
Previous Epson Model	PowerLite E20	PowerLite X39	PowerLite W39
Limited Warranty	2-year	2-year	2-year
Basics			
Color Brightness (Color Lumens)*	3,600	3,600	3,800
White Brightness (White Lumens)*	3,600	3,600	3,800
Light Source	Lamp	Lamp	Lamp
Light Source Life Cycle up to (Normal/Medium/Eco [Hours])†	6,000/-/12,000	6,000/-/12,000	8,000/10,000/17,000
Native Resolution**	XGA	XGA	WXGA
Resolution on Screen	XGA	XGA	WXGA
Ultra Wide Aspect Ratios	–	–	–
Weight	6.0 lb	5.9 lb	5.9 lb
Dimensions (Inches)††	11.8 x 9.8 x 3.6	11.8 x 9.8 x 3.6	11.8 x 9.8 x 3.6
Dynamic Contrast Ratio (up to)	15,000:1	16,000:1	16,000:1
Throw Ratio	1.44 Wide, 2.88 Tele	1.48 Wide, 1.77 Tele	1.30 Wide, 1.56 Tele
Zoom Lens (Ratio)	2.0x Digital	1.2x Optical	1.2x Optical
Power Consumption	349 W	345 W	345 W
Value-Added Features			
Built-In Speaker	5 W	5 W	5 W
Closed Captioning	YES	YES	YES
A/V Mute	Digital/Manual	Digital/Manual	Digital/Manual
Split Screen***	YES	YES	YES
Edge Blending	–	–	–
Scheduling Function	–	–	–
Easy Connectivity and Setup			
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)****	–	YES	YES
Signage Content Playback and Management Software*****	–	–	–
Miracast®	–	–	–
Quick Corner Adjustments	YES	YES	YES
Screen Fit	–	–	–
Keystone (Horizontal/Vertical)	Easy-Slide/Manual	Easy-Slide/Auto	Easy-Slide/Auto
LAN Networking and Control			
Wired	–	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless*****	–	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Compatible Control Systems*****	–	Crestron®, AMX®, Extron®, Control4®, Epson Projector Management Connected (EPM-C)	Crestron, AMX, Extron, Control4, EPM-C
Connections			
HDMI®	HDMI x 1	HDMI x 1	HDMI x 2
Analog Connections	VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 2, Composite x 1
Audio In	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2
Variable Audio Out	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
USB 2.0 Connectors	Type-B x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1
HDBaseT®	–	–	–
Monitor Out	D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1
Serial Control	RS-232c x 1	RS-232c x 1	RS-232c x 1
Recommended Accessory 1	Universal Mount (ELPMBPJG)	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)
Recommended Accessory 2	DC-13 Document Camera	DC-13 Document Camera	DC-13 Document Camera

*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. **WXGA (1920 x 1200), WGA (1280 x 800), XGA (1024 x 768). ***Split Screen feature requires remote control. Consult your user manual for input combinations. ****For wireless functionality, including via the Epson iProjection app, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection app does not support all files and formats. See www.epson.com for details. *****Internet connection required for download. Data usage fee may apply. *****Wi-Fi CERTIFIED™, level of performance subject to the range of the router being used. *****Select projectors require one on-site PC with Epson Projector Connected Agent installed. See individual product specifications.

Basic Projectors for Small and Medium Rooms	Advanced Networking Classroom Projectors – Standard Throw		
			
PowerLite 1290	PowerLite 118	PowerLite 119W	PowerLite 982W
V11HB59220	V11HA03020	V11H985020	V11H987020
V13H010L97	V13H010L97	V13H010L97	V13H010L97
PowerLite 1288	PowerLite 108	PowerLite 109W	PowerLite 980W
2-year	2-year	2-year	2-year
4,100	3,800	4,000	4,200
4,100	3,800	4,000	4,200
Lamp	Lamp	Lamp	Lamp
5,500/-/12,000	8,000/10,000/17,000	8,000/10,000/17,000	6,500/10,000/17,000
1080p	XGA	WXGA	WXGA
1080p	XGA	WXGA	WXGA
–	–	–	–
6.8 lb	6.2 lb	6.2 lb	6.8 lb
12.2 x 11.5 x 4.1	11.8 x 10.2 x 3.6	11.8 x 10.2 x 3.6	12.2 x 11.5 x 4.1
16,000:1	16,000:1	16,000:1	16,000:1
1.30 Wide, 2.09 Tele	1.48 Wide, 1.77 Tele	1.30 Wide, 1.56 Tele	1.38 Wide, 2.24 Tele
1.6x Optical	1.2x Optical	1.2x Optical	1.6x Optical
349 W	345 W	345 W	345 W
16 W	16 W	16 W	16 W
YES	YES	YES	YES
Digital/Manual	Digital/Manual	Digital/Manual	Digital/Manual
YES	YES	YES	YES
–	–	–	–
–	–	–	–
YES	YES	YES	YES
–	–	–	–
YES	YES	YES	YES
–	–	–	–
Easy-Slide/Auto	Easy-Slide/Auto	Easy-Slide/Auto	Easy-Slide/Auto
–	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Included Wi-Fi® 6 (802.11 b/g/n/ac/ax)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
–	Crestron, AMX, Extron, Control4, EPM-C	Crestron, AMX, Extron, Control4, EPM-C	Crestron, AMX, Extron, Control4, EPM-C
HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2
–	VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 2, Composite x 1
–	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1
–	–	–	–
–	D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1
–	RS-232c x 1	RS-232c x 1	RS-232c x 1
Universal Mount (ELPMBPJG)	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)
Soft Carrying Case (ELPKS70)	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera

†Lamp light source life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. Lamps come with a 90-day limited warranty.

††Dimensions including feet and standard lens.

	Advanced Networking Classroom Laser Projectors – Short Throw		Advanced Networking Projectors – Ultra Short Throw
			
PowerLite 994F	PowerLite L210SF	PowerLite L210SW	PowerLite 685W
V11HB60020	V11HA75020	V11HA76020	V11H744520
V13H010L97	–	–	V13H010L91
PowerLite 992F	–	PowerLite L200W	PowerLite 585W
2-year	3-year [‡]	3-year [‡]	2-year
4,100	4,000	4,000	3,500
4,100	4,000	4,000	3,500
Lamp	Laser	Laser	Lamp
6,500/10,000/17,000	20,000/-/30,000 [‡]	20,000/-/30,000 [‡]	5,000/-/10,000
1080p	1080p	WXGA	WXGA
1080p	1080p	WXGA	WXGA
–	21:9, 16:6	–	–
6.8 lb	10.4 lb	10.4 lb	12.6 lb
12.2 x 11.5 x 4.1	12.8 x 3.6 x 13.3	12.8 x 3.6 x 13.3	14.5 x 15.8 x 7.4
16,000:1	5,000,000:1	5,000,000:1	14,000:1
1.30 Wide, 2.09 Tele	0.45 Wide, 0.61 Tele	0.48 Wide, 0.65 Tele	0.28 Wide, 0.37 Tele
1.6x Optical	1.35x Digital	1.35x Digital	1.35x Digital
349 W	272 W	272 W	373 W
16 W	16 W	16 W	16 W
YES	YES	YES	YES
Digital/Manual	Digital	Digital	Digital
YES	YES	YES	YES
–	–	–	–
–	–	–	–
YES	YES	YES	YES
–	YES	YES	–
YES	YES	YES	–
YES	YES	YES	YES
–	–	–	–
Easy-Slide/Auto	Manual/Manual	Manual/Manual	Manual/Manual
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Included Wi-Fi 6 (802.11 b/g/n/ac/ax)	Included (802.11 a/b/g/n/ac); 2.4 GHz/5 GHz	Included (802.11 a/b/g/n/ac); 2.4 GHz/5 GHz	Optional (802.11 b/g/n)
Crestron, AMX, Extron, Control4, EPM-C	Crestron, AMX, Extron, Art-Net, PJLink, EPM-C	Crestron, AMX, Extron, Art-Net, PJLink, EPM-C	Crestron, AMX, Extron, PJLink, Art-Net, Control4, EPM-C
HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 3 (Includes MHL® x 1)
VGA x 2, Composite x 1	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video
RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2, Mic In	RCA (L & R) x 1, Mini Stereo x 2, Mic In	Mini Stereo x 3
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-B x 1, Type-A x 1	Type-B x 1, Type-A with 2-Ampere Power x 1	Type-B x 1, Type-A with 2-Ampere Power x 1	Type-B x 1, Type-A x 1
–	–	–	–
D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Universal Mount (ELPMBPJG)	Short Throw Wall Mount (ELPMB64)	Short Throw Wall Mount (ELPMB64)	Ultra Short Throw Wall Mount (ELPMB62)
DC-21 Document Camera	PowerLite Pilot™ 3R (ELPCB03N)	PowerLite Pilot 3R (ELPCB03N)	PowerLite Pilot 3R (ELPCB03N)

[‡]20,000 hours is the estimated life when the projector is used in Normal Mode in an ordinary environment, 30,000 hours in Eco Mode. Actual hours may vary depending on mode and usage environment.
The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first.
Δ5-year with product registration.

Advanced Networking Laser Projectors for Classrooms and Digital Signage – Ultra Short Throw			Ultra Mobile Projectors – 1700 Series, Extra Thin and Light	
				
PowerLite 760W	PowerLite 770F / PowerLite 775F	PowerLite 800F / PowerLite 805F	PowerLite 1785W	PowerLite 1795F
V11HA81020	V11HA79020 / V11HA83120	V11H923520 / V11H923620	V11H793020	V11H796020
Laser	Laser	Laser	V13H010L94	V13H010L94
PowerLite 725W	PowerLite 750F / PowerLite 755F	PowerLite 700U	PowerLite 1776W	–
3-year ^Δ	3-year ^Δ	3-year ^Δ	2-year	2-year
4,100	4,100	5,000	3,200	3,200
4,100	4,100	5,000	3,200	3,200
Laser	Laser	Laser	Lamp	Lamp
20,000/-/30,000 [†]	20,000/-/30,000 [†]	20,000/-/30,000 [†]	4,000/-/7,000	4,000/-/7,000
WXGA	1080p	1366 x 768 with Panel Shift	WXGA	1080p
WXGA	1080p	1080p	WXGA	1080p
–	21:9, 16:6	21:9, 16:6	–	–
13 lb	13 lb	21.4 lb	4.0 lb	4.0 lb
14.1 x 15.6 x 5.25	14.1 x 15.6 x 5.25	18.1 x 17.7 x 9.0	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1
5,000,000:1	Dynamic 5,000,000:1	Dynamic 5,000,000:1	10,000:1	10,000:1
0.27 Wide, 0.37 Tele	0.25 Wide, 0.35 Tele	0.27 Wide, 0.37 Tele	1.04 Wide, 1.26 Tele	1.02 Wide, 1.23 Tele
1.35x Digital	1.35x Digital	1.35x Digital	1.2x Optical	1.2x Optical
277 W	277 W	381 W	309 W	309 W
16 W	16 W	8 W x 2	1 W	1 W
YES	YES	YES	YES	YES
Digital	Digital	Digital	Digital/Manual	Digital/Manual
YES	YES	YES	YES	YES
–	YES	YES	–	–
–	YES	YES	–	–
YES	YES	YES	YES	YES
–	YES	YES	YES	YES
YES	YES	YES	YES	YES
–	–	–	YES	YES
Manual/Manual	Manual/Manual	Manual/Manual	Auto/Auto	Auto/Auto
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	–	–
Included (802.11 a/b/g/n/ac); 5 GHz	Included (802.11 a/b/g/n), 2.4 GHz; (802.11 a/n/ac), 5 GHz	Optional (802.11 b/g/n), 2.4 GHz; (802.11 a/n/ac), 5 GHz	Included (802.11 b/g/n)	Included (802.11 b/g/n)
Crestron, AMX, Extron, Control4, PJLink, EPM-C	Crestron, AMX, Extron, PJLink, Art-Net, Control4, EPM-C	Crestron, AMX, Extron, PJLink, Art-Net, Control4, EPM-C	–	–
HDMI x 3	HDMI x 3	HDMI x 3	HDMI x 1	HDMI x 1
VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 1, Composite Video	VGA x 1, Composite Video
Mini Stereo x 3, Mic In	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 1	Mini Stereo x 1
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	–	–
Type-B x 1, Type-A with 2-Ampere Power x 1	Type-B x 1, Type-A with 2-Ampere Power x 1	Type-B x 1, Type-A x 2	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1
–	–	YES	–	–
Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1, HDMI Out	–	–
RS-232c x 1	RS-232c x 1	RS-232c x 1	–	–
Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)	ES3000 Screen	ES3000 Screen
DC-21 Document Camera	DC-21 Document Camera	Wireless LAN Module (ELPAP11)	DC-21 Document Camera	DC-21 Document Camera

Δ5-year with product registration.

	PowerLite Standard Throw Laser Projectors		PowerLite L Series Lasers				
Note: Highlighted boxes indicate step-ups between models within a series.							
	Epson Model	PowerLite L210W	PowerLite L260F / PowerLite L265F	PowerLite L530U	PowerLite L690U	PowerLite L790U	PowerLite L890U
	Product Code	V11HA70020	V11HA69020 / V11HA72120	V11HA27020	V11HB29020	V11HB28020	V11HB27020
	Previous Epson Model	PowerLite L200W	PowerLite L250F	PowerLite L510U	PowerLite L630U	PowerLite L730U	-
	Limited Warranty	3-year ^Δ	3-year ^Δ	3-year	3-year	3-year	3-year
Basics							
Color Brightness (Color Lumens)*	4,500	4,600	5,200	6,500	7,300	8,000	
White Brightness (White Lumens)*	4,500	4,600	5,200	6,500	7,300	8,000	
Light Source	Laser	Laser	Laser	Laser	Laser	Laser	
Light Source Life up to (Normal/Extended [Hours])	20,000/30,000 ^{***}	20,000/30,000 ^{***}	20,000/30,000 ^{***}	20,000/30,000 ^{***}	20,000/30,000 ^{***}	20,000/30,000 ^{***}	
Native Resolution**	WXGA	1080p	WUXGA	WUXGA	WUXGA	WUXGA	
Resolution on Screen	WXGA	1080p	WUXGA	WUXGA	WUXGA	WUXGA	
Ultra Wide Aspect Ratios	–	21:9, 16:6	21:9, 16:6	21:9, 16:6	21:9, 16:6	21:9, 16:6	
Weight	9.5 lb	9.5 lb	18.1 lb	19.8 lb	19.8 lb	21.0 lb	
Dimensions (Inches) [†]	19.1 x 14.4 x 6.9	19.1 x 14.4 x 6.9	17.32 x 11.97 x 4.80	17.32 x 5.43 x 13.35	17.32 x 5.43 x 13.35	17.32 x 5.43 x 13.35	
Dynamic Contrast Ratio (up to)	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	
Throw Ratio	1.41 Wide, 2.26 Tele	1.32 Wide, 2.12 Tele	1.35 Wide, 2.20 Tele	1.35 Wide, 2.20 Tele	1.35 Wide, 2.20 Tele	1.35 Wide, 2.20 Tele	
Zoom Lens (Ratio)	1.0x – 1.6x Optical	1.0x – 1.6x Optical	1.00x – 1.6x Optical	1.0x – 1.6x Optical	1.0x – 1.6x Optical	1.0x – 1.6x Optical	
Power Consumption	272 W	272 W	301 W	415 W	415 W	470 W	
Value-Added Features							
Built-In Speaker	16 W	16 W	10 W	10 W	10 W	10 W	
Closed Captioning	YES	YES	YES	–	–	–	
A/V Mute	Digital/Manual	Digital/Manual	Digital	Digital	Digital	Digital	
Split Screen***	YES	YES	YES	YES	YES	YES	
Edge Blending	–	YES	YES	YES	YES	YES	
Camera	–	–	–	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	
Scheduling Function	YES	YES	YES	YES	YES	YES	
Easy Connectivity and Setup							
Epson iProjection Suite (Moderator, Multi-PC, Device Management)****	YES	YES	YES	YES	YES	YES	
Signage Content Playback and Management Software*****	–	YES	YES	YES	YES	YES	
Miracast	YES	YES	YES	YES	YES	YES	
Quick Corner Adjustments	YES	YES	YES	YES	YES	YES	
Keystone (Horizontal/Vertical)	Easy-Slide/Auto	Easy-Slide/Auto	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	
Lens Shift (Vertical and Horizontal)	–	–	YES	YES	YES	YES	
LAN Networking and Control							
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	
Wireless*****	Included (802.11 a/b/g/n/ac); 2.4 GHz and 5 GHz	Included (802.11 a/b/g/n/ac); 2.4 GHz and 5 GHz	Included (802.11 a/b/g/n/ac), 2.4 GHz and 5 GHz	Included (802.11 a/b/g/n/ac/ax), 2.4 GHz, 5 GHz and 6 GHz	Included (802.11 a/b/g/n/ac/ax), 2.4 GHz, 5 GHz and 6 GHz	Included (802.11 a/b/g/n/ac/ax), 2.4 GHz, 5 GHz and 6 GHz	
Compatible Control Systems*****	Crestron, AMX, Extron, PJLink, Control4, EPM-C	Crestron, AMX, Extron, PJLink, Art-Net, Control4, EPM-C	Crestron, AMX, PJLink, Control4, EPM-C	Crestron, AMX, PJLink, Control4, EPM-C	Crestron, AMX, PJLink, Control4, EPM-C	Crestron, AMX, PJLink, Control4, EPM-C	
Connections							
HDMI	HDMI x 2	HDMI x 2	HDMI x 2, HDMI Out x 1	HDMI x 2, HDMI Out x 1	HDMI x 2, HDMI Out x 1	HDMI x 2, HDMI Out x 1	
Analog Connections	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2	–	–	–	
Audio In	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	Mini Stereo x 2	–	–	–	
Variable Audio Out	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	
USB 2.0 Connectors	Type-A with 5V / 2A Power Supply, Type-B	Type-A with 5V / 2A Power Supply, Type-B	Type-B x 1, Type-A x 1	2 x Type-A (5V/2A, 5V/0.9A), Type-B	2 x Type-A (5V/2A, 5V/0.9A), Type-B	2 x Type-A (5V/2A, 5V/0.9A), Type-B	
DVI-D	–	–	–	–	–	–	
HDBaseT	–	–	YES	YES	YES	YES	
SDI	–	–	–	–	–	–	
Monitor Out	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	–	–	–	
Serial Control	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	
Recommended Accessory 1	Ceiling Mount (ELPMB60W)	Ceiling Mount (ELPMB60W)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	
Recommended Accessory 2	DC-21 Document Camera	DC-21 Document Camera	Wireless LAN Module (ELPAP11)	PixAlign™ Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	

*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. **WUXGA (1920 x 1200), WXGA (1280 x 800), XGA (1024 x 768). ***Split Screen feature requires remote control. Consult your user manual for input combinations. ****For wireless functionality, including via the Epson iProjection app, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection app does not support all files and formats. See www.epson.com for details. *****Internet connection required for download. Data usage fee may apply. *****Wi-Fi CERTIFIED; level of performance subject to the range of the router being used. *****Select projectors require one on-site PC with Epson Projector Connected Agent installed. See individual product specifications.

Epson Projectors for Meeting Rooms and Large Rooms						
						
PowerLite L690E	PowerLite L890E / PowerLite L895E	PowerLite L690SU / PowerLite L695SU	PowerLite L790SE / PowerLite L795SE	PowerLite L690SE / PowerLite L695SE	EB-PU1006W	EB-PU1007W / EB-PU1007B
V11HB25020	V11HB24020 / V11HB24120	V11HB31020 / V11HB31120	V11HB26020 / V11HB26120	V11HB36020 / V11HB36120	V11HA35920	V11HA34920 / V11HA34820
PowerLite L570U	PowerLite L770U / L775U	PowerLite L630SU / L635SU	–	–	Pro L1060UNL	Pro L1070UNL
3-year	3-year	3-year	3-year	3-year	3-year	3-year
6,500	8,000	6,200	7,000	6,000	6,000	7,000
6,500	8,000	6,200	7,000	6,000	6,000	7,000
Laser	Laser	Laser	Laser	Laser	Laser	Laser
20,000/30,000 ^{††}	20,000/30,000 ^{††}	20,000/30,000 ^{††}	20,000/30,000 ^{††}	20,000/30,000 ^{††}	20,000/30,000 [†]	20,000/30,000 [†]
WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}
1920 x 1200 x 2	1920 x 1200 x 2	WUXGA	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2
21:9, 16:6	21:9, 16:6	21:9, 16:6	21:9, 16:6	21:9, 16:6	21:9 ^a	21:9 ^a
19.8 lb	21.0 lb	21.0 lb	19.8 lb	22.0 lb	34.2 lb	36.2 lb
17.32 x 5.43 x 13.35	17.32 x 5.43 x 13.35	17.32 x 5.94 x 14.25	17.32 x 5.94 x 14.25	17.32 x 5.94 x 14.49	21.5 x 17.2 x 6.5	21.5 x 17.2 x 6.5
5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1
1.35 Wide, 2.20 Tele	1.35 Wide, 2.20 Tele	0.79 Wide, 1.36 Tele	0.79 Wide, 1.36 Tele	0.5 Wide, 0.7 Tele	See Page 10 for Optional Lenses	
1.0x – 1.6x Optical	1.0x – 1.6x Optical	1.0x – 1.7x Optical	1.0x – 1.7x Optical	1.0x – 1.4x Optical		
415 W	470 W	415 W	470 W	432 W	384 W	448 W
10 W	10 W	10 W	10 W	10 W	–	–
–	–	–	–	–	–	–
Digital	Digital	Digital	Digital	Digital	Digital	Digital
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	–	–
YES	YES	YES	YES	YES	–	–
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
YES	YES	YES	YES	YES	Powered with Lens Memory	Powered with Lens Memory
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Included (802.11a/b/g/n/ac/ax), 2.4 GHz, 5 GHz and 6 GHz	Included (802.11a/b/g/n/ac/ax), 2.4 GHz, 5 GHz and 6 GHz	Included (802.11a/b/g/n/ac/ax), 2.4 GHz, 5 GHz and 6 GHz	Included (802.11a/b/g/n/ac/ax), 2.4 GHz, 5 GHz and 6 GHz	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Crestron, AMX, PJLink, Art-Net, Control4, EPM-C	Crestron, AMX, PJLink, Art-Net, Control4, EPM-C	Crestron, AMX, PJLink, Art-Net, Control4, EPM-C	Crestron, AMX, PJLink, Art-Net, Control4, EPM-C	Crestron, AMX, PJLink, Art-Net, Control4, EPM-C	Crestron, AMX, Extron, Art-Net, EPM-C	Crestron, AMX, Extron, Art-Net, EPM-C
HDMI x 1	HDMI x 2, HDMI Out x 1	HDMI x 2, HDMI Out x 1	HDMI x 2, HDMI Out x 1	HDMI x 2, HDMI Out x 1	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)
–	–	–	–	–	VGA x 1	VGA x 1
–	–	–	–	–	–	–
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
2 x Type-A (5V/2A, 5V/0.9A), Type-B	2 x Type-A (5V/2A, 5V/0.9A), Type-B	2 x Type-A (5V/2A, 5V/0.9A), Type-B	2 x Type-A (5V/2A, 5V/0.9A), Type-B	2 x Type-A (5V/2A, 5V/0.9A), Type-B	Type-B x 1 (For Service, Clone), Type-A x 1 (For Wireless)	
–	–	–	–	–	DVI-D x 1	DVI-D x 1
YES	YES	YES	YES	YES	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)
–	–	–	–	–	–	–
–	–	–	–	–	–	–
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG / ELPMBPRH)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)
PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	Wireless LAN Module (ELPAP11)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)

†Dimensions including feet and standard lens.
Δ5-year with product registration.
^aFirmware update may be required on some models to get 21:9 functionality.

Large Venue Installation – Pro Series Laser Projectors with Optional Lenses

						
EB-PU1008W / EB-PU1008B	EB-PU2010W / EB-PU2010B	EB-PU2113W	EB-PU2213B	EB-PU2116W	EB-PU2216B	EB-PU2120W
V11HA33920 / V11HA33820	V11HA52920 / V11HA52820	V11HA65920	V11HA68820	V11HA64920	V11HA67820	V11HA63920
Pro L1490UNL	—	Pro L1500UH	Pro L1505UH	Pro L1750U	Pro L1755U	Pro L20002U
3-year	3-year	3-year	3-year	3-year	3-year	3-year
8,500	10,000	13,000	13,000	16,000	16,000	20,000
8,500	10,000	13,000	13,000	16,000	16,000	20,000
Laser	Laser	Laser	Laser	Laser	Laser	Laser
20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]	20,000/30,000 [‡]
WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}
1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2	1920 x 1200 x 2
21:9 ^a	21:9 ^a	21:9	21:9	21:9	21:9	21:9
36.2 lb	37.5 lb	52.4 lb	52.2 lb	53.5 lb	53.5 lb	53.7 lb
21.5 x 17.2 x 6.5	21.5 x 17.2 x 6.5	23.1 x 19.4 x 7.3	23.1 x 19.4 x 7.3	23.1 x 19.4 x 7.3	23.1 x 19.4 x 7.3	23.1 x 19.4 x 7.3
5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1
See Page 10 for Optional Lenses						
559 W	559 W	886 W	886 W	1,118 W	1,118 W	1,301 W at 200 V – 240 V
—	—	—	—	—	—	—
—	—	—	—	—	—	—
Digital	Digital	Digital	Mechanical Shutter	Digital	Mechanical Shutter	Digital
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
—	—	—	—	—	—	—
—	—	—	—	—	—	—
YES	YES	YES	YES	YES	YES	YES
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Crestron, AMX, Extron, Art-Net, Control4, EPM-C	Crestron, AMX, Extron, Art-Net, Control4, EPM-C	Crestron, AMX, Extron, Art-Net, Control4, EPM-C	Crestron, AMX, Extron, Art-Net, Control4, EPM-C	Crestron, AMX, Extron, Art-Net, Control4, EPM-C	Crestron, AMX, Extron, Art-Net, Control4, EPM-C	Crestron, AMX, Extron, Art-Net, Control4, EPM-C
HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)
VGA x 1	VGA x 1	VGA x 1	VGA x 1	VGA x 1	VGA x 1	VGA x 1
—	—	—	—	—	—	—
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
FW Update, Clone)	Type-B x 1 (For Service, Clone), Type-A x 3 (For Wireless, FW Update, Clone, Camera)					
DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1
HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)
—	3G-SDI In/Out	—	3G-SDI In/Out	—	3G-SDI In/Out	—
—	—	—	—	—	—	—
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)
PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)

[‡]20,000 hours is the estimated laser light source life when used in Normal Mode, 30,000 hours in Eco Mode. Actual hours may vary depending on mode and usage environment. The projector has a standard limited warranty of 3 years.

^{††}4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen.

^aFirmware update may be required on some models to get 21:9 functionality.

		Large Venue Installation – Pro Series 4K Laser Projectors			
					
EB-PU2220B	Pro L30002UNL / Pro L30000UNL	EB-PQ2008W / EB-PQ2008B	EB-PQ2010W / EB-PQ2010B	EB-PQ2213B	EB-PQ2216W / EB-PQ2216B
V11HA66820	V11H944920 / V11H944820	V11HB01920 / V11HB01820	V11HB02920 / V11HB02820	V11HB03820	V11HB04920 / V11HB04820
Pro L20000U	–	–	–	–	–
3-year	3-years or 20,000 hours	3-year	3-year	3-year	3-year
20,000	30,000	8,000	10,000	13,000	16,000
20,000	30,000	8,000	10,000	13,000	16,000
Laser	Laser	Laser	Laser	Laser	Laser
20,000/30,000 [†]	20,000/30,000 ^{††}	20,000/30,000 [†]	20,000/30,000 [†]	20,000/30,000 [†]	20,000/30,000 [†]
WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	1080p with 4K Crystal Motion	1080p with 4K Crystal Motion	1080p with 4K Crystal Motion	1080p with 4K Crystal Motion
1920 x 1200 x 2	1920 x 1200 x 2	4K UHD (3840 x 2160)	4K UHD (3840 x 2160)	4K UHD (3840 x 2160)	4K UHD (3840 x 2160)
21:9	–	21:9	21:9	21:9	21:9
53.7 lb	140.7 lb	41.0 lb	41.4 lb	63.4 lb	64.3 lb
23.1 x 19.4 x 7.3	31.1 x 28 x 11.4	21.5 x 17.2 x 6.5	21.5 x 17.2 x 6.5	23.1 x 19.4 x 7.3	23.1 x 19.4 x 7.3
5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1
Optional Lenses		See Page 10 for Optional Lenses			
1,301 W at 200 V – 240 V	2,325 W at 200 V – 240 V	522 W	640 W	951 W	1,114 W at 200 V – 240 V
–	–	–	–	–	–
–	–	–	–	–	–
Mechanical Shutter	Mechanical Shutter	Digital	Digital	Mechanical Shutter	Mechanical Shutter
YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES
Optional (ELPEC01)	Built-In	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)
YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES
–	–	–	–	–	–
–	–	–	–	–	–
YES	YES	YES	YES	YES	YES
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Crestron, AMX, Extron, Art-Net, EPM-C	Crestron, AMX, Extron, Art-Net, EPM-C	Crestron, AMX, Extron, Art-Net, EPM-C	Crestron, AMX, Extron, Art-Net, EPM-C	Crestron, AMX, Extron, Art-Net, EPM-C	Crestron, AMX, Extron, Art-Net, EPM-C
HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI 2 In/1 Out (HDCP 2.3)	HDMI 2 In/1 Out (HDCP 2.3)	HDMI 2 In/1 Out (HDCP 2.3)	HDMI 2 In/1 Out (HDCP 2.3)
VGA x 1	VGA x 1, 5-BNC x 1	–	–	–	–
–	–	–	–	–	–
Mini Stereo x 1	–	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
DVI-D x 1	DVI-D x 1	–	–	–	–
HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.3)	HDBaseT x 1 (HDCP 2.3)	HDBaseT x 1 (HDCP 2.3)	HDBaseT x 1 (HDCP 2.3)
3G-SDI In/Out	3G-SDI	–	12G-SDI In/Out	12G-SDI In/Out	12G-SDI In/Out
–	Mini D-Sub (15-Pin) x 1	–	–	–	–
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Ceiling Mount (ELPMB67)	Stacking Frame (ELPMB52)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)
PixAlign Camera (ELPEC01)	Handling Frame (ELPMB56)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)

††20,000 hours is the estimated life when the projector is used in Normal Mode in an ordinary environment, 30,000 hours in Eco Mode. Actual hours may vary depending on mode and usage environment.
The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first.

	Interactive Laser Displays – BrightLink® Series					Extreme Short Throw
						
EB-PQ2220B	BrightLink 760Wi	BrightLink 770Fi	BrightLink 1480Fi	BrightLink 1485Fi	PowerLite 810E / PowerLite 815E	
V11HB05820	V11HA80020	V11HA78020	V11H921520	V11H919520	V11HA99020 / V11HA99120	
–	BrightLink 725Wi	BrightLink 735Fi	BrightLink Pro 1460Ui	BrightLink Pro 1470Ui	–	
3-year	3-year ^Δ	3-year ^Δ	3-year ^Δ	3-year ^Δ	3-year ^Δ	
20,000	4,100	4,100	5,000	5,000	5,000	
20,000	4,100	4,100	5,000	5,000	5,000	
Laser	Laser	Laser	Laser	Laser	Laser	
20,000/30,000*	20,000/30,000 ⁺⁺	20,000/30,000 ⁺⁺	20,000/30,000 ⁺⁺	20,000/30,000 ⁺⁺	20,000/30,000 ⁺⁺	
1080p with 4K Crystal Motion	WXGA	1080p	1366 x 768 with Panel Shift	1366 x 768 with Panel Shift	1080p with 4K Enhancement ⁺⁺	
4K UHD (3840 x 2160)	WXGA	1080p	1080p	1080p	1920 x 1080 x 2	
21:9	–	21:9, 16:6	–	21:9, 16:6	21:9, 16:6	
64.3 lb	12.7 lb	12.7 lb	21.4 lb	21.4 lb	27.6 lb	
23.1 x 19.4 x 7.3	14.1 x 15.6 x 5.25	14.1 x 15.6 x 5.25	18.1 x 14.3 x 8.3	18.1 x 14.3 x 8.3	27.4 x 13.5 x 5.7	
5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	
	0.28 Wide, 0.37 Tele	0.26 Wide, 0.36 Tele	0.27 Wide, 0.37 Tele	0.27 Wide, 0.37 Tele	0.16 Wide, 0.22 Tele	
	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	
1,431 W at 200 V – 240 V	267 W	267 W	381 W	381 W	398 W	
–	16 W	16 W	8 W x 2	8 W x 2	8 W x 2	
–	YES	YES	YES	YES	YES	
Mechanical Shutter	Digital	Digital	Digital	Digital	Digital	
YES	YES	YES	YES	YES	YES	
YES	–	–	–	YES	YES	
Optional (ELPEC01)	–	–	–	–	–	
YES	YES	YES	YES	YES	YES	
YES	YES	YES	YES	YES	YES	
–	–	–	–	–	–	
–	YES	YES	YES	YES	YES	
YES	YES	YES	YES	YES	YES	
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	
Powered with Lens Memory	–	–	–	–	–	
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	
Optional (802.11 b/g/n)	Included (802.11 a/b/g/n/ac); 5 GHz	Included (802.11 a/b/g/n/ac); 5 GHz	Included (802.11 a/b/g/n/ac); 5 GHz	Included (802.11 a/b/g/n/ac); 5 GHz	Included (802.11 a/b/g/n/ac); 2.4 GHz	
Crestron, AMX, Extron, PJLink, Art-Net, Control4, EPM-C	Crestron, AMX, Extron, PJLink, Control4, EPM-C	Crestron, AMX, Extron, PJLink, Control4, EPM-C	Crestron, AMX, Extron, PJLink, Control4, EPM-C	Crestron, AMX, Extron, PJLink, Control4, EPM-C	Crestron, AMX, Extron, PJLink, Art-Net, Control4, EPM-C	
HDMI 2 In/1 Out (HDCP 2.3)	HDMI x 3	HDMI x 3	HDMI x 3	HDMI x 3	HDMI x 2	
–	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	–	
–	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	–	
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	–	
Update, Clone, Camera)	Type-B x 2, Powered Type-A x 1	Type-B x 2, Powered Type-A x 1	Type-B x 2, Type-A x 2 (Memory Stick & Doc Camera)		USB-A x 2, Powered Type-A x 1, USB-B x 1	
–	–	–	–	–	–	
HDBaseT x 1 (HDCP 2.3)	–	–	–	–	YES	
12G-SDI In/Out	–	–	HDMI Out	HDMI Out	HDMI Out	
–	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	HDMI x 1	
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	
Ceiling Mount (ELPMB67)	Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)	Extreme Short Throw Wall Mount - White (ELPMB75)	
PixAlign Camera (ELPEC01)	100" Whiteboard (16:10) (V12H831000)	100" Whiteboard (16:9) (V12H006A02)	100" Whiteboard (16:9) (V12H006A02)	100" Whiteboard (16:9) (V12H006A02)	Mobile Projector Cart (ELPCS01)	

Δ5-year with product registration.

Note: Highlighted boxes indicate step-ups between models within a series.	Interactive Projectors – BrightLink Series			
	BrightLink 760Wi	BrightLink 770Fi	BrightLink 1480Fi	BrightLink 1485Fi
Interactive Features				
Pens	2 Pens Included, Dual-User Support	2 Pens Included, Dual-User Support	2 Pens Included, Dual-User Support	2 Pens Included, Dual-User Support
Pen Technology	IR, 850 nm			
Finger Touch	Optional, up to 6 Fingers	Optional, up to 6 Fingers	Optional, up to 6 Fingers	Included, up to 6 Fingers
Interactive Pen Functions	Mouse Function (Left/Right Click), Digital Pen, LED Battery Status Indicator			
PC-Free Whiteboard Sharing	YES	YES	YES	YES
DuoLink Extended Whiteboard [‡]	–	–	–	YES, with Edge Blending
Calibration	Automatic or Manual			
Interactive Image Size	16:10 up to 100"	16:9 up to 100", 16:6 up to 110"	16:9 up to 100"	16:9 up to 100", 16:6 up to 120"
Interactive Connectivity	USB, Miracast, LAN	USB, Miracast, LAN	USB, Miracast, LAN	USB, Miracast, LAN
PC-Free Annotation	YES	YES	YES	YES
PC-Free Digital Whiteboard	Up to 20 Pages	Up to 20 Pages	Up to 20 Pages	Up to 20 Pages
Wall-Mounted Control Panel	–	–	–	YES
PC-Free Save, Email, Print	YES	YES	YES	YES
Android® OS	–	–	–	–
Gesture Support	YES, computers require Windows® 8/10/11 or Mac® OS 10 or later			
Included Software	Easy Interactive Tools for PC/Mac, Built-In Annotation Toolbar			

[‡]Requires Easy Interactive Driver. Certain functionality is only available through Epson Interactive Tools (EIT) software. For a list of supported operating systems, visit www.epson.com

Lens Data for EB-PU Projectors up to 8,500 Lumens										
Epson Model	Ultra Short Throw Lens	Short Lens #1	Short Lens #2	Wide Lens #1	Wide Lens #2	Middle Lens #1	Middle Lens #2	Middle Lens #3	Middle Lens #4	Long Lens
Lens Model	ELPLX01S	ELPLU03S	ELPLU04	ELPLW05	ELPLW06	ELPLM08	ELPLM15	ELPLM10	ELPLM11	ELPLL08
Product Code	V12H004X0A	V12H004UA3	V12H004U04	V12H004W05	V12H004W06	V12H004M08	V12H004M0F	V12H004M0A	V12H004M0B	V12H004L08
Zoom Ratio	1.0x	1.0x – 1.2x	1.0x – 1.2x	1.0x – 1.4x	1.0x – 1.4x	1.0x – 1.6x	1.0x – 1.6x	1.0x – 1.5x	1.0x – 1.5x	1.0x – 1.4x
Throw Ratio (16:10)	0.35	0.65 – 0.78	0.87 – 1.05	1.04 – 1.46	1.62 – 2.22	1.44 – 2.32	2.16 – 3.48	3.32 – 5.06	4.85 – 7.38	7.21 – 10.11
White Version	V12H004Y0A	–	–	–	–	–	–	–	–	–

Lens Data for EB-PU Projectors (10,000 to 20,000 Lumens) / Lens Data for EB-PQ Projectors										
Epson Model	Ultra Short Throw Lens	Short Lens #1	Short Lens #2	Wide Lens #1*	Wide Lens #2	Wide Lens #3	Middle Lens #2	Middle Lens #3	Middle Lens #4	Long Lens
Lens Model	ELPLX02S	ELPLU03S	ELPLU04	ELPLW05*	ELPLW06	ELPLW08	ELPLM15	ELPLM10	ELPLM11	ELPLL08
Product Code	V12H004X0B	V12H004UA3	V12H004U04	V12H004W05	V12H004W06	V12H004W08	V12H004M0F	V12H004M0A	V12H004M0B	V12H004L08
Zoom Ratio	1.0x	1.0x – 1.2x	1.0x – 1.2x	1.0x – 1.4x	1.0x – 1.4x	1.0x – 1.4x	1.0x – 1.6x	1.0x – 1.5x	1.0x – 1.5x	1.0x – 1.4x
Throw Ratio (EB-PU)	0.35	0.48 – 0.57	0.64 – 0.77	0.77 – 1.07	1.19 – 1.62	0.86 – 1.21	1.57 – 2.56	2.42 – 3.71	3.54 – 5.41	5.27 – 7.41
Throw Ratio (EB-PQ)	0.34	0.46 – 0.56	0.62 – 0.75	0.74 – 1.04	1.19 – 1.62	0.83 – 1.17	1.52 – 2.47	2.34 – 3.59	3.42 – 5.23	5.09 – 7.16
White Version	V12H004Y0B	–	–	–	–	–	–	–	–	–

*ELPLW05 lens has limited compatibility with projectors above 13,000 lumens. Visit lens product pages for more information.

Essential Teaching Tools for the Modern Classroom

Share books, 3D objects and detailed demonstrations or experiments with your entire class using Epson's easy-to-use document cameras. Record lessons for viewing at a later time and give your students a more interactive learning experience.

In addition, Epson laser displays are easy to install and easy to maintain, offering free software tools and simple, seamless integration into your tech stack.

Epson iProjection[®] App – wirelessly project from Chromebook[®], iOS[®] or Android mobile devices with the free Epson iProjection app

Epson Projector Management Connected[®] – monitor and control your networked projector fleet from any device with a Web browser tool

[‡]For wireless functionality, including via the Epson iProjection app, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection app does not support all files and formats. See www.epson.com for details.

[‡]Requires one on-site PC with Epson Projector Connected Agent installed.

Document Cameras				
				
Epson Model	DC-07	DC-13	DC-21	DC-30
Product Code	V12H759020	V12H757020	V12H758020	V12HB09020
Limited Warranty	2-year			
Zoom	8x Digital	16x Digital	12x Optical, 10x Digital	10x Optical, 23x Digital
Pixel Count	2MP	2MP	2MP	13MP
Output Resolution (Max.)	1080p	1080p	1080p	4K
Frame Rate	15 fps	30 fps	30 fps	60 fps
Connectivity (Output)	USB	USB, VGA, HDMI	USB, VGA, HDMI	USB, HDMI
Capture Area	10.7" x 14.3"	11.7" x 20.7"	11.7" x 20.7"	13.6" x 18.9"
A/V Recording	YES	YES	YES	YES
Built-In Microphone	YES	YES	YES	YES
Microscope Adapter	–	YES	YES	YES
SD Card Slot [‡]	–	YES	YES	USB Drive Slot
Software Included	YES	YES	YES	YES

[‡]SD card sold separately.

Note: Highlighted boxes indicate step-ups between models within a series.

Epson Model

Product Code

Replacement Lamp Code

Previous Epson Model

Limited Warranty

Basics

Color Brightness (Color Lumens)*

White Brightness (White Lumens)*

Light Source

Light Source Life Cycle up to
(Normal/Medium/Eco [Hours])†

Native Resolution**

Resolution on Screen

Ultra Wide Aspect Ratios

Weight

Dimensions (Inches)††

Dynamic Contrast Ratio (up to)

Throw Ratio

Zoom Lens (Ratio)

Power Consumption

Value-Added Features

Built-In Speaker

Closed Captioning

A/V Mute

Split Screen***

Edge Blending

Scheduling Function

Easy Connectivity and Setup

Epson iProjection™ Suite
(Moderator, Multi-PC, Device Management)****

Signage Content Playback and Management Software*****

Miracast®

Quick Corner Adjustments

Screen Fit

Keystone (Horizontal/Vertical)

LAN Networking and Control

Wired

Wireless*****

Compatible Control Systems*****

Connections

HDMI®

Analog Connections

Audio In

Variable Audio Out

USB 2.0 Connectors

HDBaseT®

Monitor Out

Serial Control

Recommended Accessory 1

Recommended Accessory 2



LightScene® Accent Lighting Laser Projectors

LightScene laser projectors elevate ordinary spaces into stunning visual environments, unleashing dynamic, experiential content for digital art, spatial design, signage and wayfinding applications.

LightScene Projectors		
Epson Model	EV-110	EV-115
Product Code	V11HA22020	V11HA22120
Product Color	White	Black
Limited Warranty	3 Years or 20,000 Hours, Whichever Comes First	
Color Brightness (Color Lumens)*	2,200	
White Brightness (White Lumens)*	2,200	
Native Resolution	WXGA (1280 x 800)	
Contrast Ratio (Dynamic)	Up to 5,000,000:1	
Light Source Life	Up to 20,000 hours**	
Left/Right, Up/Down Movement	180 Degrees	
Ball-Joint Axis Rotation	360 Degrees	
Zoom (Powered)	1.58x	
Edge Blending Capable	YES	
HDMI/SD Card Slot***	1 x HDMI, 1 x SD Card Slot	
Variable Audio Out	1 x Stereo, Mini Out	
GPI Motion Sensor Compatible	YES	
Bluetooth® Audio	YES	
Epson Creative Content Projection App for Signage****	YES	
Epson Projector Content Manager Software****	YES	

*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.

**No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period.

***SD card sold separately.

****Internet connection required for download. Data usage fee may apply.



Epson Laser Projection Technology

As a world leader in digital 3LCD projection solutions, Epson continues to drive the future of projection technology with its full suite of laser projectors and displays. Featuring lamp-free, long-life laser light engines, Epson laser solutions achieve new levels of performance and reliability¹.

Why Choose Laser?

Breakthrough laser technology — long-life laser light engine provides up to 20,000 hours of light source life¹

Outstanding color performance and contrast — get exceptional, true-to-life color reproduction and deep, dark blacks for stunning visuals you can count on for an array of applications

Instant Off™ — displays and projectors reach maximum brightness and turn off almost instantly, without having to warm up or cool down

Reliable operation — ideal for applications requiring extended projection

Explore Epson's Suite of Laser Projectors and Displays

				
Laser Large Venue Projectors	Interactive Laser Displays	Portable Laser Projectors	Ultra Short Throw Laser Displays	Lighting Laser Displays
High-lumen laser projectors designed for exceptional performance in large venues	Full HD, ultra short throw interactive laser displays for collaborative meetings and learning	High-performance laser projectors offering a variety of brightnesses, connectivities and resolutions	Bold, rich, Full HD laser displays for virtually any application, including those in small spaces, without any shadows	Project dynamic, experiential content for digital art, commercial signage and décor applications

Epson Preferred Plus™ Extended Service Plans[◇]

We've got you covered.

Epson Preferred Plus Extended Service Plans offer you peace of mind with a variety of flexible plan options to best fit your needs and budget, helping you maximize uptime and protect your investment.

For more information, go to epson.com/esp

For Brighter Futures® Extended Service Plans see, epson.com/brighterfutures



epson.com/projectors



Extended Service Plans[◇]

PowerLite E, X, W, 100, 900, 1200, 1700 Series, PowerLite 685W, 1-Year Next-Business-Day Whole Unit Exchange (Years 3-5)^{◇◇}
PowerLite E, X, W, 100, 900, 1200, 1700 Series, PowerLite 685W, 2-Year Next-Business-Day Whole Unit Exchange (Years 3-5)^{◇◇}
PowerLite E, X, W, 100, 900, 1200, 1700 Series, PowerLite 685W, 3-Year Next-Business-Day Whole Unit Exchange (Years 3-5)^{◇◇}
EB-PU1000/2000 Series, 1-Year Next-Business-Day Whole Unit Exchange (Year 4 or 5)
EB-PU1000/2000 Series, 2-Year Next-Business-Day Whole Unit Exchange (Years 4-5)
Pro L30000 Series, 1-Year Return for Repair Extension (Year 4 or 5)
Pro L30000 Series, 2-Year Return for Repair Extension (Years 4-5)
PowerLite L Series, LightScene Series, 1-Year Next-Business-Day Whole Unit Exchange (Year 4 or 5)
PowerLite L Series, LightScene Series, 2-Year Next-Business-Day Whole Unit Exchange (Years 4-5)
BrightLink Series, PowerLite 700 and 800 Series, 1-Year Next-Business-Day Whole Unit Exchange (Year 4 or 5)
BrightLink Series, PowerLite 700 and 800 Series, 2-Year Next-Business-Day Whole Unit Exchange (Years 4-5)
DC-07, 1-Year Next-Business-Day Whole Unit Exchange
DC-07, 3-Year Next-Business-Day Whole Unit Exchange
DC-13, DC-21, 1-Year Next-Business-Day Whole Unit Exchange
DC-13, DC-21, 3-Year Next-Business-Day Whole Unit Exchange
DC-30, 1-Year Next-Business-Day Whole Unit Exchange
DC-30, 3-Year Next-Business-Day Whole Unit Exchange
EB-PU2100/2200 Series, 3-Year Shipping Upgrade to Next-Business-Day (Years 1-3)
EB-PU2113W, EB-PU2116W, EB-PU2213B, EB-PU2216B, 5-Year Next-Business-Day Upgrade (Years 1-3) and Extension (Years 4-5)
EB-PU2120W, EB-PU2220B, 5-Year Next-Business-Day Upgrade (Years 1-3) and Extension (Years 4-5)
EB-PQ Series, 3-Year Shipping Upgrade to Next-Business-Day (Years 1-3)
EB-PQ Series (Except EB-PQ2220B), 5-Year Next-Business-Day Upgrade (Years 1-3) and Extension (Years 4-5)
EB-PQ2220B, 5-Year Next-Business-Day Upgrade (Years 1-3) and Extension (Years 4-5)

EPPEXPA1
EPPEXPA2
EPPEXPA3
EPPEXPC1
EPPEXPC2
EPPEXPD1
EPPEXPD2
EPPEXPE1
EPPEXPE2
EPPEXPF1
EPPEXPF2
EPDCAE1
EPDCAE3
EPDCEB1
EPDCEB3
EPDCEC1
EPDCEC3
EPPRJPU3
EPPRJPU5
EPPRJPU20E5
EPPRJPUQ3
EPPRJPUQ5
EPPRJPUQ20E5

[◇]Check individual extended service plans for Terms and Conditions. Eligibility and coverage vary by plan. Expedited shipping not available in all areas. Orders must be placed and processed by 1 p.m. Pacific Time, Monday through Friday, excluding holidays. See limited warranty or service plan for details. Pro L30000 Series not eligible for Next-Business-Day replacement. ¹ ^{◇◇}Lamp-based models only.

Epson America, Inc.
3131 Katella Ave., Los Alamitos, CA 90720

Epson Canada Limited
185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
epson.com/projectors

www.epson.ca

¹ No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. Large Venue Series: 20,000 hours is the estimated life when the projector is used in Normal Mode in an ordinary environment. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first. The EB-PU Series and EB-PQ Series of projectors have a standard limited warranty of 3 years. Interactive, Digital Signage and Accent Lighting Projectors: 20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. Interactive and Digital Signage Projectors come with a 3-year limited warranty; Accent Lighting Projectors have a limited warranty of 3 years or 20,000 hours, whichever comes first. Corporate Series: 20,000 hours is the estimated laser light source life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a standard limited warranty of 3 years.

Specifications and terms are subject to change without notice. EPSON, LightScene and PowerLite are registered trademarks and Epson iProjection and Instant Off are trademarks of Seiko Epson Corporation. BrightLink and Brighter Futures are registered trademarks and Epson Preferred Plus, the Epson Preferred Plus logo, Pilot and PivAlign are trademarks of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. Android and Chromebook are registered trademarks of Google LLC. Windows is a trademark of the Microsoft group of companies. Miracast® and Wi-Fi® are registered trademarks and Wi-Fi CERTIFIED™ is a trademark of Wi-Fi Alliance®. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2025 Epson America, Inc. CPD-63281R2 3/25