



Efficiency meets economy with the EcoTank monochrome M1100, M1120, and the multi-functional M2140 printers. Look forward to lower business costs with bottles that provide an ultra-high page yield of up to 6,000 pages² each. Simplify processes with integrated ink tanks that enable spill- and error-free ink refilling, and enjoy laser-quality text that is smudge-proof and water-resistant with the pigment ink. What's more, the M1120 brings convenient printing with wireless connectivity. Whatever the printing need, there's an Epson printer that meets the requirements.





M1120



M2140



















Each printer comes bundled with a starter kit of 1 high-capacity bottle of Epson genuine ink.

IT'S IN THE DETAILS.







Designed to support the Sustainable Development Goals (SDGs) set by the UN

# **Better Savings and Page Yield**

Print cost-effectively with affordable ink bottles and an ultra-high page yield of up to 6,000 pages<sup>2</sup>, and save on paper costs with auto-duplex<sup>4</sup> printing.

### **Better for the Environment**

Each printer is designed to reduce running costs and impact to the environment, using up to 30X less power<sup>6</sup> than laser printers.

# **Epson Warranty for Peace of Mind**

Enjoy warranty coverage of 3 years or 100,000 prints<sup>7</sup>, whichever comes first, printhead included.

## **EcoTank PRINTER M1100/M1120/M2140**



| MODEL NUMBER   | M1100   | M1120  | M2140   |
|--|---|--|---|
| Printer Type   | Print   |  | Print, Scan, Copy   |
| Printing   |   |  |   |
| Printing Technology  | Epson's Heat-Free Technological   | ogy  | Epson's Heat-Free Technology  |
| Nozzle Configuration   | 180 x 2 nozzles Black   | -97  | 400 x 2 nozzles Black   |
| Print Direction  | Bi-directional printing   |  |   |
| Maximum Resolution   |   | le-Sized Droplet Technology)   | 1200 x 2400 dpi (with Variable-Sized                                |
| Victoria i i i i i i i i i i i i i i i i i i   | THO X 120 apr (Wall Vallace   | o dizad Bropiet reermology)  | Droplet Technology)   |
| Minimum Ink Droplet Volume   | 3 pl  |  | 2.8 pl  |
| Print Speed <sup>1</sup>   | ·   |  | 1   |
| Draft Text - Memo, A4 (Black *1)   | Up to 32 ppm  |  | Up to 39 ppm  |
| ISO 24734, A4 (Black)  | Up to 15 ipm  |  | Simplex: Up to 20 ipm, Duplex: 9.0 ipm                              |
| First Page Out Time (Black)  | Approx. 8 sec   |  | Approx. 6 sec (simplex) / 13 sec (duplex)                           |
| Printer Language   | ESC / P-R   |  | Approxit a see (employ). To see (deploy)                            |
| Automatic 2-sided printing   | No  |  | Yes   |
| , ,  |   |  | 165   |
| Copying  |   |  |   |
| Copy Speed   |   |  |   |
| ISO 29183, A4, Simplex (Black)   | <u>-</u>  |  | Up to 17 ipm  |
| Copy Quality   | -   |  | Standard / Best   |
| Maximum Copies from Standalone   | -   |  | 99 copies   |
| Reduction/Enlargement  | -   |  | 25 – 400 % Auto Fit Function  |
| Maximum Copy Resolution  |   |  | 600 x 600 dpi   |
| Maximum Copy Size  | <u> </u>  |  | A4, Letter  |
| Scanning   |   |  |   |
| Scanner Type   | -   |  | Flatbed colour image scanner  |
| Sensor Type  | -   |  | CIS   |
| Optical Resolution   | -   |  | 1200 x 2400 dpi   |
| Maximum Scan Area  | -   |  | 216 x 297 mm (8.5 x 11.7")  |
| Scanner Bit Depth  |   |  | 1   |
| Colour   | -   |  | 48-bit input, 24-bit output   |
| Grayscale  | -   |  | 16-bit input, 8-bit output  |
| Black & White  |   |  | 16-bit input, 1-bit output  |
| Scan Speed (Flatbed)   |   |  | - Strapsi, Strouput   |
| Monochrome 200 dpi   |   |  | 12 sec  |
| · ·  |   |  | 27 sec  |
|  |   |  | 121 300   |
| Paper Handling   |   |  |   |
| Paper Feed Method  | Friction feed   |  |   |
| Number of Paper Trays  | 1   |  | 2   |
| Paper Hold Capacity  |   |  |   |
| Input Capacity   | Up to 150 sheets-A4 / Lette   | er Plain Paper (80 g/m²); 10-sheets-Envelope   | Cassette 1: 250 Sheets-A4 / Letter Plain Pape                       |
|  | •   |  | (80 g/m²); 10-sheets-Envelope;<br>Rear Slot: 1 Sheet-A4 Plain Paper |
| Output Conneits  | Up to 30 sheets   |  |   |
| Output Capacity  | <u>'</u>  | 245 mm) 9.5 v 12" Lottor A4 16K (105 v 270   | Up to 100 sheets  |
| Paper Size   | Envelopes: #10, DL, C6  | ossomini, o.o.x. ro., Letter, A4, 16K (195 X 270   | mm), B5, A5, B6, A6, Hagaki (100 x 148 mm),                         |
| Mavimum Banar Siza   | 215.9 x 1200 mm (8.5 x 47   | 24"\   |   |
| Maximum Paper Size   |   | *  |   |
| Print Margin   | o mini top, ieit, right, botton   | n via custom settings in printer driver  |   |
| nterface   |   |  |   |
| JSB  | USB 2.0   |  |   |
| Network  | <u>-</u>  | Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct   | -   |
| Network Protocol   | -   | TCP/IPv4, TCP/IPv6   |   |
| Network Management Protocols   |   |  |   |
| ACTIVOTIC IVICATING CITTOTIC TO TOTO COLO  | -   | SNMP, HTTP, DHCP, APIPA, PING,   | -   |
| vetwork management i rotocolo  | -   |  | -   |
|  |   | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD  | -   |
| Mobile and Cloud Printing  |   | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD  Epson iPrint, Epson Email Print,  | -<br> -   |
| Mobile and Cloud Printing Epson Connect  | -<br>-<br>-   | SNMP, HTTP, DHCP, APIPA, PING,<br>DDNS, mDNS, SLP, WSD, LLTD  Epson iPrint, Epson Email Print,<br>Remote Print Driver  |   |
| Mobile and Cloud Printing Epson Connect  |   | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD  Epson iPrint, Epson Email Print,  | -   |
| Mobile and Cloud Printing Epson Connect Other Mobile Solutions   | -<br>-<br>-   | SNMP, HTTP, DHCP, APIPA, PING,<br>DDNS, mDNS, SLP, WSD, LLTD  Epson iPrint, Epson Email Print,<br>Remote Print Driver  |   |
| Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel   | ·<br>·<br>·   | SNMP, HTTP, DHCP, APIPA, PING,<br>DDNS, mDNS, SLP, WSD, LLTD  Epson iPrint, Epson Email Print,<br>Remote Print Driver  |   |
| Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel .CD Screen  | -<br>-<br>-<br>-  | SNMP, HTTP, DHCP, APIPA, PING,<br>DDNS, mDNS, SLP, WSD, LLTD  Epson iPrint, Epson Email Print,<br>Remote Print Driver  | -<br>-<br>-<br>1.44" LCD Screen                                     |
| Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software   |   | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD  Epson iPrint, Epson Email Print, Remote Print Driver  Google Cloud Print  |   |
| Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software   |   | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD  Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print   | -<br>-<br>-<br>-<br>1.44* LCD Screen                                |
| Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel .CD Screen Printer Software   | Windows Server 2003 / 200   | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD  Epson iPrint, Epson Email Print, Remote Print Driver  Google Cloud Print  |   |
| Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel .CD Screen Printer Software   | Windows Server 2003 / 200   | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print   |   |
| Mobile and Cloud Printing Epson Connect Dther Mobile Solutions Control Panel .CD Screen Printer Software Operating System Compatibility  | Windows Server 2003 / 200<br>Only printing and scanning   | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print   |   |
| Mobile and Cloud Printing Epson Connect Dther Mobile Solutions Control Panel .CD Screen Printer Software Departing System Compatibility  | Windows Server 2003 / 200<br>Only printing and scanning t<br>Mac OS X 10.6.8 or later   | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print   |   |
| Abbile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage   | Windows Server 2003 / 200 Only printing and scanning to Mac OS X 10.6.8 or later  AC 220 - 240 V  | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print   |   |
| Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency   | Windows Server 2003 / 200<br>Only printing and scanning t<br>Mac OS X 10.6.8 or later   | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print   |   |
| Mobile and Cloud Printing Epson Connect Dither Mobile Solutions Control Panel .CD Screen Printer Software Diperating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption   | Windows Server 2003 / 200<br>Only printing and scanning I<br>Mac OS X 10.6.8 or later<br>AC 220 – 240 V<br>50 – 60 Hz   | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver     Google Cloud Print     78.1 / 10     33 x64 / 2008 / 2012 / 2016     functions are supported for Windows Server On the power of the property of the prop | S   |
| Mobile and Cloud Printing Epson Connect Dither Mobile Solutions Control Panel .CD Screen Printer Software Diperating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating   | Windows Server 2003 / 200<br>Only printing and scanning I<br>Mac OS X 10.6.8 or later  AC 220 – 240 V 50 – 60 Hz  | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print    8.1 / 10   |   |
| Abbile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby   | Windows Server 2003 / 200<br>Only printing and scanning I<br>Mac OS X 10.6.8 or later  AC 220 – 240 V 50 – 60 Hz  13 W 2.4 W  | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print    8.1 / 10   | S   |
| Mobile and Cloud Printing Epson Connect Dither Mobile Solutions Control Panel LCD Screen Printer Software Departing System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep  | Windows Server 2003 / 200 Only printing and scanning I Mac OS X 10.6.8 or later  AC 220 – 240 V 50 – 60 Hz  13 W 2.4 W 0.4 W  | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print    8.1 / 10   |   |
| Mobile and Cloud Printing Epson Connect Dither Mobile Solutions Control Panel LCD Screen Printer Software Departing System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off  | Windows Server 2003 / 200<br>Only printing and scanning I<br>Mac OS X 10.6.8 or later  AC 220 – 240 V 50 – 60 Hz  13 W 2.4 W  | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print    8.1 / 10   |   |
| Mobile and Cloud Printing Epson Connect  Other Mobile Solutions  Control PanelCD Screen  Printer Software  Operating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off  Noise Level (PC Printing)  | Windows Server 2003 / 200 Only printing and scanning I Mac OS X 10.6.8 or later  AC 220 – 240 V 50 – 60 Hz  13 W 2.4 W 0.4 W  | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print    8.1 / 10   |   |
| Mobile and Cloud Printing Epson Connect  Other Mobile Solutions  Control PanelCD Screen  Printer Software  Operating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off  Noise Level (PC Printing)  | Windows Server 2003 / 200 Only printing and scanning I Mac OS X 10.6.8 or later  AC 220 – 240 V 50 – 60 Hz  13 W 2.4 W 0.4 W  | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print    8.1 / 10   |   |
| Mobile and Cloud Printing Epson Connect Dther Mobile Solutions Control Panel LCD Screen Printer Software Departing System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off Noise Level (PC Printing) Plain Paper Default *2  | Windows Server 2003 / 200 Only printing and scanning I Mac OS X 10.6.8 or later  AC 220 – 240 V 50 – 60 Hz  13 W 2.4 W 0.4 W 0.3 W  | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver Google Cloud Print    8.1 / 10   | 13 W<br>5.1 W   |
| Mobile and Cloud Printing Epson Connect  Other Mobile Solutions  Control PanelCD Screen  Printer Software  Operating System Compatibility  Electrical Specifications Rated Voltage Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off  Noise Level (PC Printing) Plain Paper Default *2  Consumables  | Windows Server 2003 / 200 Only printing and scanning I Mac OS X 10.6.8 or later  AC 220 – 240 V 50 – 60 Hz  13 W 2.4 W 0.4 W 0.3 W  6.6 B(A), 53 dB (A)  Page Yield' <sup>3</sup> | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver     Google Cloud Print     78.1 / 10     33 x64 / 2008 / 2012 / 2016     functions are supported for Windows Server Office     14 W     3.0 W     0.7 W     Order Code   | 13 W<br>5.1 W   |
| Mobile and Cloud Printing Epson Connect  Other Mobile Solutions  Control Panel  CD Screen  Printer Software  Operating System Compatibility  Electrical Specifications  Rated Voltage  Rated Voltage  Rated Frequency  Power Consumption  Operating  Standby  Sleep  Power off  Noise Level (PC Printing)  Plain Paper Default *2  Consumables  Standard Black Ink Bottles | Windows Server 2003 / 200 Only printing and scanning I Mac OS X 10.6.8 or later  AC 220 – 240 V 50 – 60 Hz  13 W 2.4 W 0.4 W 0.3 W  6.6 B(A), 53 dB (A)  Page Yield*3 2,000       | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver     Google Cloud Print     8.1 / 10     33 x64 / 2008 / 2012 / 2016     functions are supported for Windows Server On the control of | 13 W<br>5.1 W   |
| Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep   | Windows Server 2003 / 200 Only printing and scanning I Mac OS X 10.6.8 or later  AC 220 – 240 V 50 – 60 Hz  13 W 2.4 W 0.4 W 0.3 W  6.6 B(A), 53 dB (A)  Page Yield' <sup>3</sup> | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD    Epson iPrint, Epson Email Print, Remote Print Driver     Google Cloud Print     78.1 / 10     33 x64 / 2008 / 2012 / 2016     functions are supported for Windows Server Office     14 W     3.0 W     0.7 W     Order Code   | 13 W<br>5.1 W   |

Dimensions & Weight

M1100 / M1120 Weight: 3.5 kg / 7.7 lbs



M2140 Weight: 6.2 kg / 13.7 lbs



\*1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.



#1 Black Text and graphics

- \*2 Default mode in accordance with ISO7779 for MFPs
- 2 Outstand the the theoretic with the Control of the Control of

© 2020 Epson India Pvt. Ltd. All Rights Reserved.
Reproduction in part or in whole, without the written
permission from Epson, is strictly prohibited. EPSON and
EXCEED YOUR VISION are registered trademarks of Seiko
Epson Corporation. All other products names and other
company names used herein are for identification purposes
only and are the trademarks or registered trademarks of
their respective owners. Epson disclaims any and all rights
in those marks. Print samples shown are simulations only.
Specifications and product availability are subject to change
without notice and may vary between countries. Please
check with local Epson offices for more information.

Dealer's Stamp

### EPSON INDIA PVT. LTD.

Zlean

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-3051 5000 Fax: 080-3051 5005

### **Regional Offices:**

Ahmedabad - 3314 8500/01, Chennai - 3967 7500, Cochin - 4012 315, Coimbatore - 98942 19200, Kolkata - 4603 4729, Mumbai - 3079 8200, New Delhi - 3312 0300, Pune - 3028 6000/05, Hyderabad - 4857 0032, Jaipur - 78699 11699



Information correct at time of printing Printed January 2020

