

EXPERIENCE RUGGED RELIABILITY AND POWERFUL PERFORMANCE.



Discover a new way to print all business documents with Epson's FX-2190II, FX-2190IIN, FX-2175II and FX-2175IIN dot matrix printers. Designed to deliver absolute performance and reliability, these powerful printers offer blazing print speeds of up to 615cps and an MTBF (Mean Time Before Failure) of up to 25,000 POH (Power On Hours). With the built-in network connectivity* function, printing efficiently is achieved in the most convenient way.



- 
Print
- 
High Speed Printing
- 
Cost Effective
- 
Power Savings
- 
Ethernet



Epson genuine ribbons ensure greater yield, better quality and longer lifespan.

<p>Unparalleled Productivity Boost productivity with fast print speeds of up to 615 cps (10 cpi) and 128 kb memory buffer.</p>	<p>Rugged Reliability Enjoy cost savings, superior print quality and minimal downtime with a MTBF of up to 25,000 POH.</p>	<p>Superior Connectivity Stay connected and experience fuss-free printing with built-in network connectivity* via Ethernet cable.</p>
--	--	---

*FX-2190IIN and FX-2175IIN only.

SPECIFICATIONS

FX-2175II/2175IIN/2190II/2190IIN

MODEL NUMBER	FX-2175II	FX-2175IIN	FX-2190II	FX-2190IIN			
Printer Technology							
Printing Method	Impact dot matrix						
Number of Pins in Head	9 pins						
Print Direction	Bi-direction with logic seeking						
Control Code	ESC/P2, IBM PPDS						
Printer Speed							
Ultra Speed Draft	10cpi	496cpi	615 cps				
High Speed Draft	10cpi	496cpi	612 cps				
Draft	10cpi	372dpi	463 cps				
NLQ	10cpi	93cpi	115 cps				
Print Characteristics							
Character Table	1 Italic and 12 graphical character tables: Italic table, PC437 (US, Standard/Europe), PC850 (Multilingual), PC860 (Portuguese), PC861 (Icelandic), PC865 (Nordic), PC863 (Canadian-French), Abicomp, BRASCil, Roman 8, ISO Latin 1, PC858, ISO 8859-15						
Bitmap Fonts							
Epson Draft	10, 12, 15 cpi						
Epson Roman / Epson Sans Serif	10, 12, 15 cpi, Proportional		N/A				
Scalable Fonts	Epson Roman / Epson Sans Serif						
Barcode Fonts	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET						
Printable Columns							
Pitch	10cpi	136 cpl					
Paper Handling							
Paper Path	Manual Insertion (front or rear in, top out), Push Factor (front or rear in, top out), Pull Tractor (front, rear or bottom in, top out)						
Paper / Media							
Cut Sheet (Single Sheet)							
Entry: Front	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.065 - 0.14 mm (0.0025 - 0.0055")	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.065 - 0.14 mm (0.0025 - 0.0055")	
Entry: Rear	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.065 - 0.14 mm (0.0025 - 0.0055")	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.065 - 0.14 mm (0.0025 - 0.0055")	
Cut Sheet (Multi-part Sheet)							
Entry: Front	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.12 - 0.39 mm (0.0047 - 0.015")	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.12 - 0.46 mm (0.0047 - 0.018")	
Entry: Rear	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.12 - 0.39 mm (0.0047 - 0.015")	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.12 - 0.46 mm (0.0047 - 0.018")	
Continuous Paper (Single Sheet / Multi-part)							
Entry: Front / Rear / Bottom	101.6 - 558.8 mm (4.0 - 22.0")	101.6 - 406.4 mm (4.0 - 16.0")	0.065 - 0.39 mm (0.0025 - 0.015")	101.6 - 558.8 mm (4.0 - 22.0")	101.6 - 406.4 mm (4.0 - 16.0")	0.065 - 0.46 mm (0.0025 - 0.018")	
Copies Original + 4 copies							
Envelope (No.6)	Entry: Rear	92 mm (3.6")	165 mm (6.5")	0.16 - 0.52 mm (0.0063 - 0.0205")	92 mm (3.6")	165 mm (6.5")	0.16 - 0.52 mm (0.0063 - 0.0205")
Envelope (No.10)	Entry: Rear	105 mm (4.1")	241 mm (9.5")	0.16 - 0.52 mm (0.0063 - 0.0205")	105 mm (4.1")	241 mm (9.5")	0.16 - 0.52 mm (0.0063 - 0.0205")
Label (Base Sheet)	Entry: Bottom	101.6 - 558.8 mm (4.0 - 22.0")	101.6 - 406.4 mm (4.0 - 16.0")	0.16 - 0.19 mm (0.0063 - 0.0075")	101.6 - 558.8 mm (4.0 - 22.0")	101.6 - 406.4 mm (4.0 - 16.0")	0.16 - 0.19 mm (0.0063 - 0.0075")
Card	Entry: Front / Rear	100 - 148 mm (3.9 - 5.8")	100 - 148 mm (3.9 - 5.8")	0.22 mm (0.0087")	100 - 148 mm (3.9 - 5.8")	100 - 148 mm (3.9 - 5.8")	0.22 mm (0.0087")
Roll Paper							
Entry: Rear	Diameter	127mm (5")	Width	216 mm (8.5")	Thickness	0.07 - 0.09 mm (0.0028 - 0.035")	
Line Spacing							
4.23mm (1/6") or programmable in increments of 0.059mm (1/432")							
Acoustic Noise							
Input Data Buffer			56 dB				
128KB							
Interface							
USB 2.0, Bi-directional parallel (IEEE-1284 nibble mode supported)		USB 2.0, Bi-directional parallel (IEEE-1284 nibble mode supported) Serial, 100base-Tx wired LAN		USB 2.0, Bi-directional parallel (IEEE-1284 nibble mode supported)		USB 2.0, Bi-directional parallel (IEEE-1284 nibble mode supported) Serial, 100base-Tx wired LAN	
Ribbon Cartridge							
Standard	Fabric Ribbon Cartridge (Black)						
Ribbon Life	Approx. 12 million Characters ¹						
Reliability							
Mean Print Volume Between Failure (MVBF)		30 million lines (except print head)		52 million lines (except print head)			
Mean Time Between Failure (MTBF)		15,000 Power On Hours (POH) (25% Duty)		25,000 Power On Hours (POH) (25% Duty)			
Print Head Life		200 million strokes/wire		400 million strokes / wire			
Control Panel							
6 switches and 10 LEDs							
Environmental Conditions (Operating)							
Temperature ²		5 - 35 °C					
Humidity ²		10 - 80% RH					
Electrical Specification							
Rated Voltage		AC 220 - 240 V					
Rated Frequency		50 Hz - 60 Hz					
Power Consumption		54W					
Operating		0.5W					
Sleep Mode		0.8W					
Power Off		0.1W in power off mode					
Supported Operating System							
Printer Driver							
Microsoft Windows XP / Vista / 7 / 8 / 10							
Utility							
Epson Status Monitor 3: Microsoft Windows XP / Vista / 7 / 8 / 10							
Epson Setting Utility: Microsoft Windows XP / Vista / 7 / 8 / 10							

Dimensions & Weight

Weight: Approx. 9.4kg (20.8lbs)



Options and Consumables

Pull Tractor Unit	C12C933761
Ribbon Cartridge	C13S015584
Single Bin Cut Sheet Feeder	C12C806392

Legend

- cpi Characters per inch (Characters per 25.4mm)
- cps Characters per second
- cpl Character per line

¹ Actual print yield may vary depending on usage purpose and environment
² Without condensation



© 2018 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct as at July 2018

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-30515000 Fax: 080-30515005

Regional Offices:

Ahmedabad - 2640 7176/77, Chennai - 3027 7500/11, Cochin - 4012 315, Coimbatore - 98942 19200, Hyderabad - 6463 9640/41, Jaipur - 96808 52132, Kolkata - 6500 9370/77, Mumbai - 2826 1515/17, New Delhi - 4658 5444, Pune - 3028 6000,



Epson Helpline:

For product info, service or to order a ribbon cartridge - 1800 425 0011
 For service - 1860 3000 1600 (9AM - 6PM) (Mon - Sat)

www.epson.co.in

Dealer's Stamp