

# EB-770F



Drive engagement and communication with an affordable display, up to 150", that will improve productivity in any environment.

Whatever the size of class or meeting room, unrestricted and immersive presentations are possible with this bright, clear, compact and affordable display solution.

The EB-770F's bright, 1080p image, scalable up to 150", is clearly visible from every angle and at a distance, and content can easily be shared or streamed directly from multiple devices for the ultimate collaborative experience.

The EB-770F's ultra short throw lens allows safe, discreet positioning close to the display, enabling presenters free access to perform without casting shadows.

With 4,100 lumens CLO and 3LCD technology, the display is bright and vibrant up to 150", clearly visible from all angles and at a distance. The experience is immersive and user-friendly.

Scalable from 49-150", display sizes can be optimised for each room with one product and a fixed cost, and the EB-770F supports multi-projection edge-blending for a low cost, large, seamless, energy efficient 3780x1080p image.

Versatile wired and wireless connectivity options, including Miracast™ screen mirroring, ensures effortless, multi-device content sharing, and with a connected optional Epson visualiser, documents, presentations or 3D objects can be projected in incredible detail to the whole room.

Unlike a flat-panel display, there is no heavy, breakable, glass panel to create disruptive, reflected blind spots at certain angles, and teachers are not subjected to LCD panel direct blue light radiation, believed to damage eyes. Paired with a hygienic, antibacterial whiteboard, teachers can annotate presentations with dry-wipe pens, or to save energy, simply use the whiteboard with the display turned off.

## DATASHEET / BROCHURE



## KEY FEATURES

- **Scalable FHD display for any room**  
49-150" UST display for unrestricted viewing (no shadows/reflections)
- **Bright and energy efficient laser**  
4,100lm CLO with 3LCD technology for brighter colours at only 205W
- **Effortless connectivity options**  
Auto-on, wired / wireless display with USB 2A output for smart sticks
- **Simple to use and built to last**  
Virtually maintenance free with 5-year, 12,000hr warranty
- **Document camera compatibility**  
Create and record a live, totally immersive lesson or presentation

# EPSON

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0.62 inch with C2 Fine
IMAGE	
Color Light Output	4,100 Lumen- 2,800 Lumen (economy) In accordance with IDMS15.4
White Light Output	4,100 Lumen - 2,800 Lumen (economy) In accordance with ISO 21118:2020
Resolution	1080p
High Definition	Full HD
Aspect Ratio	16:9
Contrast Ratio	Over 2,500,000 : 1
Light source	Laser
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco
Keystone Correction	Manual vertical: ± 3 °, Manual horizontal ± 3 °
Colour Video Processing	10 Bits
2D Vertical Refresh Rate	192 Hz - 240 Hz
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.25 - 0.35:1
Zoom	Digital, Factor: 1 - 1.35
Lens	Optical
Screen Size	60 inches - 150 inches
Projection Lens F Number	1.6
Projection Lens Focal Length	3.7 mm
Projection Lens Focus	Manual
Offset	5 : 1
CONNECTIVITY	
Interfaces	USB 2.0-A (2x), RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, VGA in (2x), VGA out, HDMI in (3x), Composite in, Miracast, Jack plug out, Jack plug in (3x), USB 2.0 Type B (Service Only), Wi-Fi Direct, Microphone input
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink
ADVANCED FEATURES	
Security	Kensington lock, Control panel lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection
Other features	21:9 aspect ratio support, A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Customizable user logo, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Email notification, Home Screen, Horizontal and vertical keystone correction, Image Shift, JPEG Viewer, Long light source life, Network projection, OSD copy function, PC Free, Point correction, Power on button, Quick Corner, Schedule Function, Screen Mirroring, Split-Screen-Function, Ultra-wide display (16:6), Web Control, Web Remote, Wireless LAN capable, iProjection App
Video Color Modes	Blackboard, Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection
Projector control	via: Crestron Integrated Partner, Crestron RoomView, Extron IP Link, AMX Device Discovery, Control4 Simple Device Discovery Protocol

EB-770F

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries



## PRODUCT SPECIFICATIONS

EB-770F

### GENERAL

Power consumption	197 Watt - On mode power consumption (Normal) 263 Watt (Peak), 199 Watt (Eco), 0.5 Watt (Energy saving standby)
Heat Dissipation	895 BTU/hour (max)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	356 x 395 x 133 mm (Width x Depth x Height)
Product weight	5.9 kg
Noise Level	Normal: 37 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10° C - 60° C
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%  If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could break and cause the projector to drop from the ceiling.  If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance.
Included Software	Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Content Manager, Epson Projector Management
Options	Air filter, Visualiser camera, WP System - ELPWP10, Wall mount, Wireless LAN unit, Wireless transmitter - ELPWT01
Loudspeaker	16 Watt
Room Type / Application	Boardroom, Home Office, Meeting room / Classroom, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop, Table Mounted, Wall Mounted
Colour	White

### OTHER

Warranty	3 years or 20,000 hours whichever is earlier
----------	--

EPSON

## OPTIONAL ACCESSORIES

EB-770F

- Wall Mount - ELPMB62 - EB-7xx / EB-8xx  
V12HA06A06
- Adapter - ELPAP11 Wireless LAN (5GHz)  
V12H005A01
- Air Filter - ELPAF60 - EB-7XX / EB-L2xx Series  
V13H134A60

## LOGISTICS INFORMATION

SKU	V11HA79056
Country of Origin	Philippines

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.  
Product information is subject to change without prior notice.

### EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1,  
Murphy Road, Ulsoor, Bangalore – 560 008.  
Tel: 080–4566 5000 Fax: 080–4566 5005

### Regional Offices:

Ahmedabad 3314 8500/01, Chennai 3967 7500, Cochin 4012 315, Coimbatore 98942 19200  
Hyderabad 4857 0032, Jaipur 78699 11699, Kolkata 4603 4729, Mumbai 3079 8200  
New Delhi 3312 0300, Pune 3028 6000/05,



**Epson Helpline:** For product info or service– 1800 425 0011  
For service – 1800 123 001 600 (9AM – 6PM) (Mon – Sat)  
**Email:** emp@eid.epson.co.in

[www.epson.co.in](http://www.epson.co.in)

**EPSON**