

3LCD PROJECTOR



No. 1 PROJECTOR BRAND
WORLDWIDE
2001-2024
SOURCE: FUTURESOURCE CONSULTING



3LCD PROJECTOR

SOLUSI SOFTWARE



iProjection

Epson iProjection adalah aplikasi nirkabel yang memungkinkan pengguna menampilkan konten dari laptop atau perangkat mobile ke proyektor Epson melalui Wi-Fi. Mendukung berbagai format file dan fitur anotasi, iProjection mempermudah presentasi interaktif dan kolaboratif tanpa kabel, ideal untuk lingkungan kerja maupun pendidikan modern.

Multi-screen

menampilkan hasil proyeksi dari 4 perangkat sekaligus.

Moderator mode

Moderator dapat mengontrol dan mengelola konten yang ditampilkan di layar proyektor saat beberapa perangkat terhubung secara bersamaan

Multi-platform

Support Android, iOS, Windows, macOS.

Format File

Menampilkan file (PDF, gambar, dokumen) secara nirkabel dari smartphone/laptop ke proyektor

Kompatibilitas

Semua proyektor Epson yang memiliki jaringan network



Projector Distance Calculator

Projector Distance Calculator adalah alat bantu untuk menghitung jarak ideal antara proyektor dan layar guna mendapatkan ukuran gambar (image size) yang sesuai dan tajam. Dengan memasukkan jenis proyektor, ukuran layar yang diinginkan, dan rasio zoom lensa, alat ini membantu menentukan jarak proyeksi optimal dan penempatan proyektor yang tepat di ruangan.

Menentukan Jarak Proyektor yang Ideal

Meng Hitung jarak ideal antara proyektor dan layar (throw distance) sesuai dengan kebutuhan pengguna

Memastikan Kualitas Gambar Optimal

Menentukan ukuran layar sesuai jarak ruangan yang tersedia.

Edge Blending & Mendukung Perencanaan Instalasi

Membantu menghitung dan merancang instalasi dengan penggunaan 2 atau lebih proyektor agar menghasilkan gambar yang lebih lebar panoramatic.

Membantu Pemilihan Tipe Lensa

Jika menggunakan proyektor dengan lensa yang bisa diganti (interchangeable lens), kalkulator ini membantu menentukan jenis lensa yang sesuai (misalnya short-throw atau long-throw).



Professional Tools for Projector Config Tools

Professional Tools for Projector Configuration adalah sekumpulan alat bantu digital yang disediakan oleh Epson untuk membantu teknisi, desainer ruangan, atau tim presales dalam merencanakan dan memasang proyektor secara tepat.

Perencanaan Instalasi yang Akurat

Membantu menentukan posisi ideal proyektor, ukuran layar, dan jenis lensa yang dibutuhkan, sehingga instalasi lebih presisi dan efisien. Sudah terdapat fungsi pengaturan Geometry correction, Edge blending dan Color Matching & Color Calibration

Pengaturan yang mudah

Proyektor pada jaringan yang sama akan terdeteksi sehingga teknisi dapat melakukan monitoring dan controlling dari remote area

Kompatible

Dapat digunakan pada sistem operasi Windows 7/8.1/10 and macOS.

3LCD PROJECTOR

Small Sized Rooms



Total Nilai
TKDN + BMP
55.70%

E600 untuk Indonesia



EB-E600

Brightness 3,400 lm	Resolution XGA	Contrast 15,000:1
Light Source Life 6,000/12,000 hrs	Keystone ±30° (V) / ±30° (H)	Connectivity USB Type-B x 1, VGA x 2, RCA x 1, HDMI x 1
Network N/A	Power Consumption 327W / 225W	Weight 2.7 kg



12,000 Hours
Lamp Life in Eco Mode



Split Screen



Total Nilai
TKDN + BMP
55.02%

X600 untuk Indonesia



EB-X600

Brightness 3,600 lm	Resolution XGA	Contrast 16,000:1
Light Source Life 6,000/12,000 hrs	Keystone ±30° (V) / ±30° (H)	Connectivity USB Type-A & B x 1, VGA x 2, RCA x 1, HDMI x 1
Network RJ45 x 1, Optional (ELPAP11)	Power Consumption 327W / 225W	Weight 2.7 kg



12,000 Hours
Lamp Life in Eco Mode



Split Screen



Auto Vertical
Keystone



Horizontal Keystone
Adjuster*



Wireless
iProjection

ENGINEERED FOR good

EPSON

GENUINE TKDN



Epson EB-E/X600



Hingga

55.70%

Rasio TKDN dan BMP tertinggi
dalam kategori proyektor

No.1

Merk proyektor selama 24
tahun berturut-turut di Dunia*

10.000+

Lapangan Kerja untuk
Karyawan Lokal

*2001 - 2024 Source: Futuresource Consulting

Inovasi untuk Negeri

3LCD PROJECTOR

Small Sized Rooms

EB-X52



Brightness 3,800 lm	Resolution XGA	Contrast 16,000:1
Light Source Life 6,000/12,000 hrs	Keystone ±30° (V) / ±30° (H)	Connectivity HDMI in x2 USB Type A USB Type B
Network Optional (ELPAP11)	Power Consumption 332W / 231W	Weight 2.5 kg



12,000 Hours
Lamp Life in Eco Mode



Split Screen



Auto Vertical
Keystone



Horizontal Keystone
Adjuster*



Wireless
iProjection

EB-W55




Brightness 4,000 lm	Resolution WXGA	Contrast 16,000:1
Light Source Life 6,000/12,000 hrs	Keystone ±30° (V) / ±30° (H)	Connectivity HDMI in x2 USB Type A USB Type B
Network Built In Wireless	Power Consumption 332W / 231W	Weight 2.5 kg



12,000 Hours
Lamp Life in Eco Mode



Split Screen



Auto Vertical
Keystone



Horizontal Keystone
Adjuster*



Wireless
iProjection

3LCD PROJECTOR

3LCD PROJECTOR

EB-W53



Brightness 4,000 lm	Resolution WXGA	Contrast 16,000:1
Light Source Life 6,000/12,000 hrs	Keystone ±30° (V) / ±30° (H)	Connectivity HDMI in x2 USB Type B
Network NA	Power Consumption 332W / 231W	Weight 2.5 kg



12,000 Hours
Lamp Life in Eco Mode



Split Screen

EB-FH54



Brightness 4,100 lm	Resolution Full HD	Contrast 16,000:1
Light Source Life 5,500/12,000 hrs	Keystone ±30° (V) / ±30° (H)	Connectivity HDMI in x2, Stereo Mini USB Type A USB Type B
Network Built In, Support Miracast & AirPlay 2	Power Consumption 332W / 231W	Weight 3.1 kg



12,000 Hours
Lamp Life in Eco Mode



Split Screen



Auto Vertical
Keystone



Horizontal Keystone
Slider



Wireless iProjection
/ Screen Mirroring



Full HD
Resolution



Apple
AirPlay 2

3LCD PROJECTOR

Small Sized Rooms

EB-972



Brightness 4,100 lm	Resolution XGA	Contrast 16,000:1
Light Source Life 6,500/17,000 hrs	Keystone $\pm 30^\circ$ (V) / $\pm 30^\circ$ (H)	Connectivity HDMI in x2, VGA in x1, VGA out x1, RCA in x1, 2RCA x1 Stereo Mini Jack in x2 Stereo Mini Jack out x1 USB Type-A & Bx1
Network Optional (ELPAP11)	Power Consumption 327W / 225W	Weight 3.1 kg



17,000 Hours
Lamp Life in Eco Mode



Split Screen



Auto Vertical
Keystone



Horizontal Keystone
Slider



Wireless
iProjection

EB-982W



Brightness 4,200 lm	Resolution WXGA	Contrast 16,000:1
Light Source Life 6,500/17,000 hrs	Keystone $\pm 30^\circ$ (V) / $\pm 30^\circ$ (H)	Connectivity HDMI in x2, VGA in x1, VGA out x1, RCA in x1, 2RCA x1 Stereo Mini Jack in x2 Stereo Mini Jack out x1 USB Type-A & Bx1
Network Optional (ELPAP11)	Power Consumption 327W / 225W	Weight 3.1 kg



17,000 Hours
Lamp Life in Eco Mode



Split Screen



Auto Vertical
Keystone



Horizontal Keystone
Slider



Wireless
iProjection

3LCD PROJECTOR

Ultra Portable Projectors

EB-1785W Gesture Presenter



Brightness 3,200lm	Resolution WXGA	Contrast 10,000:1
Light Source Life 4,000 / 7,000 hrs	Keystone $\pm 45^{\circ}$ (V) / $\pm 30^{\circ}$ (H)	Connectivity VGA in x1, HDMI in x1 (Support MHL) Stereo Mini Jack in x1 USB Type-A & Bx1
Network Built-in Support Screen Mirroring	Power Consumption 295W / 208W	Weight 1.81 kg



Gesture
Presenter



NFC



Wireless
Projection



Real-Time Auto V/H
Keystone Correction



Split Screen



reddot design award



EB-1795F Gesture Presenter

Brightness 3,200lm	Resolution 1080p	Contrast 10,000:1
Light Source Life 4,000 / 7,000 hrs	Keystone $\pm 45^{\circ}$ (V) / $\pm 30^{\circ}$ (H)	Connectivity HDMI in x1 (Support MHL) VGA in x1, RCA x1 Stereo Mini Jack in x1 USB Type-A & Bx1
Network Built-in Support Screen Mirroring	Power Consumption 295W / 208W	Weight 1.83 kg



Gesture
Presenter



NFC



Wireless
Projection



Real-Time Auto V/H
Keystone Correction



Split Screen



Full HD

3LCD PROJECTOR

Mid Size Rooms Projectors

EB-2265U Gesture Presenter



Brightness 5,500lm	Resolution WUXGA	Contrast 15,000:1
Light Source Life 5,000 / 10,000 hrs	Keystone ±30°(V) / ±30°(H)	Connectivity HDBaset x1, HDMI in x2 (1 Support MHL) VGA in x2, VGA out x1 Stereo Mini Jack in x2 Stereo Mini Jack out x1 2RCA x1, RCA x1, RS-232C x1, RJ45 x1 USB Type-A & Bx1
Network Optional [ELPAP10]	Power Consumption 425W / 323W	Weight 4.7 kg



Gesture
Presenter



Multi-PC
Projection



Wireless
Projection



Split Screen

EB-2155W



Brightness 5,000lm	Resolution WXGA	Contrast 15,000:1
Light Source Life 5,000 / 10,000 hrs	Keystone ±30°(V) / ±30°(H)	Connectivity HDMI in x2 (1 Support MHL) VGA in x2, VGA out x1 Stereo Mini Jack in x2 Stereo Mini Jack out x1 2RCA x1, RCA x1, RS-232C x1, RJ45 x1 USB Type-A & Bx1
Network Optional [ELPAP10]	Power Consumption 405W / 323W	Weight 4.3 kg



Gesture
Presenter



Multi-PC
Projection



Wireless
Projection



Split Screen

3LCD PROJECTOR

EB-L690U

Brightness 6,500 lm	Resolution WUXGA [16:10]	Contrast over 5,000,000 : 1
Light Source Life 20,000 hours	Keystone ±50°(V) / ±30°(H)	Connectivity HDMI in x2 D-Sub 9 PIN USB Type A USB Type B HDMI Out Stereo Mini Out Wired LAN
Network Built In, Support Miracast & AirPlay 2	Power Consumption 399W / 295W	Weight Approx 8.2 Kg



EB-L690U/EB-L790U/EB-L890U



Wireless Projection



Flexible 360 degree installation



WUXGA Resolution



Edge Blending Technology



Apple AirPlay 2

EB-L790U

Brightness 7,300 lm	Resolution WUXGA [16:10]	Contrast over 5,000,000 : 1
Light Source Life 20,000 hours	Keystone ±50°(V) / ±30°(H)	Connectivity HDMI in x2 D-Sub 9 PIN USB Type A USB Type B HDMI Out Stereo Mini Out Wired LAN
Network Built In, Support Miracast & AirPlay 2	Power Consumption 399W / 295W	Weight Approx 8.2 Kg

EB-L890U

Brightness 8,000 lm	Resolution WUXGA [16:10]	Contrast over 5,000,000 : 1
Light Source Life 20,000 hours	Keystone ±50°(V) / ±30°(H)	Connectivity HDMI in x2 D-Sub 9 PIN USB Type A USB Type B HDMI Out Stereo Mini Out Wired LAN
Network Built In, Support Miracast & AirPlay 2	Power Consumption 450W / 330W	Weight Approx 8.5 Kg

3LCD PROJECTOR

Mid Size Rooms Projectors



EB-L690E/EB-L890E



Wireless Projection



Flexible 360 degree installation



Edge Blending Technology



Apple AirPlay 2

EB-L690E

Brightness 6,500 lm	Resolution WUXGA (4K Enhancement)	Contrast over 5,000,000 : 1
Light Source Life 20,000 hours	Keystone ±50°(V) / ±30°(H)	Connectivity HDMI in x2 D-Sub 9 PIN USB Type A USB Type B HDMI Out Stereo Mini Out Wired LAN
Network Built In, Support Miracast & AirPlay 2	Power Consumption 399W / 295W	Weight Approx 8.2 Kg

EB-L890E

Brightness 8,000 lm	Resolution WUXGA (4K Enhancement)	Contrast over 5,000,000 : 1
Light Source Life 20,000 hours	Keystone ±50°(V) / ±30°(H)	Connectivity HDMI in x2 D-Sub 9 PIN USB Type A USB Type B HDMI Out Stereo Mini Out Wired LAN
Network Built In, Support Miracast & AirPlay 2	Power Consumption 450W / 330W	Weight Approx 8.5 Kg

3LCD PROJECTOR

Business Projector

EB-L210W



Brightness 4,500lm / 3,100lm	Resolution WXGA (1280 x 800)	Contrast Over 2,500,000 : 1
Light Source Life 20,000 / 30,000 hrs	Keystone ±30° [V] / ±30° [H]	Connectivity -HDMI 2 (HDCP 2.3) -D-Sub 15Pin (1 [Black] lin common with Computer 2) -RCA 2 (White, Red) -Stereo Mini Jack (2) -USB Type A & B
Network -Wired LAN : RJ45 x 1 [100Mbps] -Wireless : Built-in*2 and Optional (Using ELPAP11)	Power Consumption -Lamp On (Normal / Extended) : 260W / 191W - Standby (Network On / Off) : 2.0W / 0.5W	Weight Approx. 4.2kg



30,000 Hours
Lamp Life in Eco Mode



Split Screen



Auto Vertical
Keystone



Horizontal
Keystone Adjuster



Wi-Fi
Connection



EB-L260F



Brightness 4,600lm / 3,200lm	Resolution Full HD (1080p)	Contrast Over 2,500,000 : 1
Light Source Life 20,000 / 30,000 hrs	Keystone ±30° [V] / ±30° [H]	Connectivity -HDMI 2 (HDCP 2.3) -D-Sub 15Pin (1 [Black] lin common with Computer 2) -RCA 2 (White, Red) -Stereo Mini Jack (2) -USB Type A & B
Network -Wired LAN : RJ45 x 1 [100Mbps] -Wireless : Built-in*2 and Optional (Using ELPAP11)	Power Consumption -Lamp On (Normal / Extended) : 260W / 191W - Standby (Network On / Off) : 2.0W / 0.5W	Weight Approx. 4.2kg



30,000 Hours
Lamp Life in Eco Mode



Split Screen



Auto Vertical
Keystone



Horizontal
Keystone Adjuster



Wi-Fi
Connection



3LCD PROJECTOR

Ultra Portable Projectors

EB-2065



Brightness 5,500lm	Resolution XGA	Contrast 15,000:1
Light Source Life 5,000 / 10,000 hrs	Keystone ±30°(V) / ±30°(H)	Connectivity HDMI in x2 (1 Support MHL) VGA in x2, VGA out x1 2RCA x1, RCA x1, RS-232C x1, RJ45 x1 Stereo Mini Jack in x2 Stereo Mini Jack out x1 USB Type-A & Bx1
Network Optional (ELPAP10)	Power Consumption 425W / 323W	Weight 4.4 kg



Gesture
Presenter



Multi-PC
Projection



Wireless
Projection



Split Screen

EB-L520U



Brightness 5,200lm	Resolution WUXGA (1920 x 1200)	Contrast over 2,500,000 : 1
Light Source Life 20,000 hours	Keystone ±30°(V) / ±30°(H)	Connectivity D-Sub 15Pin IN x 2, HDMI In x 2, HDBaseT RJ45 In x 1, D-Sub 15Pin Out x 1, Stereo Mini Jack In x 2, Stereo Mini Jack Out x 1, USB Type A x 1, USB Type B x 1, RS-232C D-Sub 9Pin x 1, Wired Lan RJ45 x 1,
Network Optional (ELPAP11)	Power Consumption 293W/233W	Weight Approx 7.7 Kg



Split Screen



Flexible
360 degree
installation

3LCD PROJECTOR

Extreme Short Throw Laser Projectors

3LCD PROJECTOR

EB-810E



Brightness 5,000lm / 3,500lm	Resolution 1080P (4K Enhancement)	Contrast Over 2,500,000 : 1
Light Source Life 20,000 / 30,000 hrs	Keystone ±30° (V) / ±30° (H)	Connectivity -HDMI 2 (HDCP 2.3) -HDBaseT 1 (HDCP 2.3) -USB Type A & B
Network -Wired LAN : RJ45 x 1 (100Mbps) -Wireless : Built-in and Optional (Using ELPAP11)	Power Consumption -Lamp On (Normal / Extended) : 380W / 286W - Standby (Network On / Off) : 2.0W / 0.4W	Weight Approx. 12.5kg



30,000 Hours
Lamp Life in Eco Mode



Split Screen



Wide Screen Display
(21:9)



Extreme
Short Throw



Wi-Fi
Connection



EB-815E



Brightness 5,000lm / 3,500lm	Resolution 1080P (4K Enhancement)	Contrast Over 2,500,000 : 1
Light Source Life 20,000 / 30,000 hrs	Keystone ±30° (V) / ±30° (H)	Connectivity -HDMI 2 (HDCP 2.3) -HDBaseT 1 (HDCP 2.3) -USB Type A & B
Network -Wired LAN : RJ45 x 1 (100Mbps) -Wireless : Built-in and Optional (Using ELPAP11)	Power Consumption -Lamp On (Normal / Extended) : 380W / 286W - Standby (Network On / Off) : 2.0W / 0.4W	Weight Approx. 12.5kg



30,000 Hours
Lamp Life in Eco Mode



Split Screen



Wide Screen Display
(21:9)



Extreme
Short Throw



Wi-Fi
Connection



3LCD PROJECTOR

Short Throw Projectors



EB-W56S

Brightness 3,700lm	Resolution WXGA	Contrast 16,000 : 1
Light Source Life 6,500/17,000 hrs	Keystone ±30°(V) / ±30°(H)	Connectivity HDMI in x2 USB Type A USB Type B
Network Optional (ELPAP11)	Power Consumption 332W / 231W	Weight Approx 3.1 Kg



Short Throw



17,000
Light Hours



Wi-Fi
Connection



EB-L690SU

Brightness 6,200 lm	Resolution WUXGA	Contrast over 5,000,000 : 1
Light Source Life 20,000 hours	Keystone ±50°(V) / ±30°(H)	Connectivity HDMI in x2 D-Sub 9 PIN USB Type A USB Type B HDMI Out Stereo Mini Out Wired LAN
Network Built In, Support Miracast & AirPlay 2	Power Consumption 339W / 295W	Weight Approx 8.9 Kg



Wireless Projection



Flexible 360 degree
installation



WUXGA Resolution



Edge Blending
Technology



Apple
AirPlay 2



3LCD PROJECTOR

Short Throw Projectors

3LCD PROJECTOR

EB-L210SW



Brightness 4,000lm / 2,800lm	Resolution WXGA (1280 x 800)	Contrast over 2,500,000 : 1
Light Source Life Type : Laser Diode Life (Normal / Quiet / Extended) : 20,000 / 20,000 / 30,000 hrs	Keystone ±15°(V) / ±15°(H)	Connectivity HDMI 2 (HDCP 2.3) D Sub 15 Pin RCA Stereo Mini Jack USB Type A & B
Network Wired LAN : RJ45 x 1 (100Mbps) Wireless : Built-in*2 and Optional wireless (using ELPAP11)	Power Consumption Lamp On (Normal / Extended) 260W / 191W Standby (Network On / Off) 2.0W / 0.5W	Weight Approx 4.6 Kg



Short Throw



30,000
Light Hours



Wi-Fi
Connection



Multi-PC
Projection

EB-L210SF



Brightness 4,000lm / 2,800lm	Resolution Full HD (1080p)	Contrast over 2,500,000 : 1
Light Source Life Type : Laser Diode Life (Normal / Quiet / Extended) : 20,000 / 20,000 / 30,000 hrs	Keystone ±15°(V) / ±15°(H)	Connectivity HDMI 2 (HDCP 2.3) D Sub 15 Pin RCA Stereo Mini Jack USB Type A & B
Network Wired LAN : RJ45 x 1 (100Mbps) Wireless : Built-in*2 and Optional wireless (using ELPAP11)*	Power Consumption Lamp On (Normal / Extended) 260W / 191W Standby (Network On / Off) 2.0W / 0.5W	Weight Approx 4.6 Kg



Short Throw



30,000
Light Hours



Wi-Fi
Connection



Multi-PC
Projection

3LCD PROJECTOR

Short Throw Projectors



EB-L690SE

Brightness 6,000 lm	Resolution WUXGA (4K Enhancement)	Contrast over 5,000,000 : 1
Light Source Life 20,000 hours	Keystone ±50°(V) / ±30°(H)	Connectivity HDMI in x2 D-Sub 9 PIN USB Type A USB Type B HDMI Out Stereo Mini Out Wired LAN
Network Optional (ELPAP11)	Power Consumption 415W / 303W	Weight Approx 9.3 Kg



Wireless Projection

Flexible 360 degree
installation

WUXGA Resolution

Edge Blending
Technology

EB-L790SE

Brightness 7,000 lm	Resolution WUXGA (4K Enhancement)	Contrast over 5,000,000 : 1
Light Source Life 20,000 hours	Keystone ±50°(V) / ±30°(H)	Connectivity HDMI in x2 D-Sub 9 PIN USB Type A USB Type B HDMI Out Stereo Mini Out Wired LAN
Network Built In, Support Miracast & AirPlay 2	Power Consumption 450W / 330W	Weight Approx 9.3 Kg



Wireless Projection

Flexible 360 degree
installation

WUXGA Resolution

Edge Blending
TechnologyApple
AirPlay 2

3LCD PROJECTOR

Lighting Scene

3LCD PROJECTOR

EB-U50



Brightness 3,700 lm	Resolution WUXGA	Contrast 16,000:1
Light Source Life 10,000/17,000 hrs	Keystone ±30° (V) / ±30° (H)	Connectivity HDMI in x2, VGA in x2 VGA out x1, RJ45 x1 Stereo Mini Jack in x2 Stereo Mini Jack out x1 USB Type-A & B x1
Network Built-in	Power Consumption 285W / 218W	Weight 3.1 kg



17,000 Hours
Lamp Life in Eco Mode



Split Screen



Auto Vertical
Keystone



Dust Resistance
Design



USB Direct
Playback

EB-W50



Brightness 3,800 lm	Resolution WXGA (1280 x 800)	Contrast 16,000:1
Light Source Life 10,000 hours (Normal), 17,000 hours (Eco)	Keystone ±30° (V) / ±30° (H)	Connectivity D-Sub 15 Pin In x 2, HDMI In x 2, D-Sub 15Pin Out x 1, Stereo Mini Jack In x 2, Stereo Mini Jack Out x 1, USB Type A x 1, USB Type B x 1, RS-232C D-Sub 9pin x 1, Wired LAN RJ45 x 1
Network Wireless ELPAP10 (Optional)	Power Consumption 285 W / 218 W	Weight 3.1 kg



17,000 Hours
Lamp Life in Eco Mode



Split Screen



Auto Vertical
Keystone



Dust Resistance
Design



USB Direct
Playback

3LCD PROJECTOR

Lighting Scene



EB-800F / 805F

Brightness 5,000 lm	Resolution 1080p	Contrast over 2,500,000 : 1
Light Source Life 20,000 hours (Normal), 30,000 hours (Extended)	Keystone ±3° (V) / ±3° (H)	Connectivity D-Sub 15Pin In x 2, Composite In RCA x 1 (Yellow), HDMI In x 3 (HDCP2.3), HDBaseT x 1 (HDCP2.3), D-Sub 15Pin Out x 1, HDMI Out x 1, Stereo Mini Jack In x 3, Stereo Mini Jack Out x 1, Rs-232C D-Sub 9Pin x 1, USB Type A x 2, USB Type B x 1, Wired Lan RJ45 x 1
Network Wireless Lan x 1 USB Type A	Power Consumption 366 W / 262 W	Weight Approx 9.4 Kg



Full HD
Resolution



Ultra short-throw
130 inch Ø80,3 cm



Multi-PC
Projection



PC free
USB memory



EV-115 (Black)

EV-110 (White)

EV-110/EV-115

Brightness 2,200lm	Resolution WXGA	Contrast >2,500,000:1
Laser Light Source 20,000 hrs	Keystone ±45°(V) / ±40°(H)	Connectivity HDMI in x1 SD Card x1, RJ45 x1 Stereo Mini Jack out x1 USB Type-A & Bx1
Network Built-in	Power Consumption 149W / 112W	Weight 6.9 kg (Exclude Direct Mount)



Flexible
Installation



Sleek Spotlight
Design

3LCD PROJECTOR

Ultra Short Throw Lamp Projectors

3LCD PROJECTOR

EB-685W



Brightness	Resolution	Contrast
3,500 lm	WXGA	14,000:1
Light Source Life	Keystone	Connectivity
5,000/10,000 hrs	±3° [V] / ±3° [H]	HDMI in x3, RCA x1 VGA in x2, VGA out x1 RS-232C x1, RJ45 x1 Stereo Mini Jack out x1 Stereo Mini Jack in x3 USB Type-A & B x1 Microphone x1
Network Optional (ELPAP10)	Power Consumption	Weight
	354W / 309W	5.7 kg



EB-760W



Brightness	Resolution	Contrast
4,100lm / 2,800lm	WXGA (1280 x 800)	over 2,500,000 : 1
Light Source Life	Keystone	Connectivity
Type : Laser Diode Life (Normal / Quiet / Extended) : 20,000 / 20,000 / 30,000 hrs	±3°[V] / ±3°[H]	HDMI Stereo Mini Jack USB Type A & B
Network	Power Consumption	Weight
Wired LAN RJ45 x 1 (100Mbps) Wireless Built-in and Optional (using ELPAP11)	Lamp On (Normal / Extended) 263W / 199W Standby (Network On / Off) 2.0W / 0.5W	Approx 5.9 Kg



3LCD PROJECTOR

Ultra Short Throw Lamp Projectors

EB-770F



Brightness 4,100lm / 2,800lm	Resolution Full HD (1080p)	Contrast over 2,500,000 : 1
Light Source Life Type : Laser Diode Life (Normal / Quiet / Extended) : 20,000 / 20,000 / 30,000 hrs	Keystone ±3°(V) / ±3°(H)	Connectivity HDMI Stereo Mini Jack USB Type A & B
Network Wired LAN RJ45 x 1 (100Mbps) Wireless Built-in and Optional (using ELPAP11)	Power Consumption Lamp On (Normal / Extended) 263W / 199W Standby (Network On / Off) 2.0W / 0.5W	Weight Approx 5.9 Kg



Ultra-Short Throw



20,000 Light Hours



Wireless Connection



Multi-PC Projection



Full HD

EB-760Wi



Brightness 4,100lm / 2,800lm	Resolution WXGA (1280 x 800)	Contrast over 2,500,000 : 1
Light Source Life Type : Laser Diode Life (Normal / Quiet / Extended) : 20,000 / 20,000 / 30,000 hrs	Keystone ±3°(V) / ±3°(H)	Connectivity HDMI Stereo Mini Jack USB Type A & B
Network Wired LAN RJ45 x 1 (100Mbps) Wireless Built-in and Optional (using ELPAP11)	Power Consumption Lamp On (Normal / Extended) 263W / 199W Standby (Network On / Off) 2.0W / 0.5W	Weight Approx 6.0 Kg



Ultra-Short Throw



20,000 Light Hours



Wireless Connection



Multi-PC Projection



Optional Finger Touch Interactive

3LCD PROJECTOR

3LCD PROJECTOR

EB-770Fi



Brightness 4,100lm / 2,800lm	Resolution Full HD (1080p)	Contrast over 2,500,000 : 1
Light Source Life Type : Laser Diode Life (Normal / Quiet / Extended) : 20,000 / 20,000 / 30,000 hrs	Keystone ±3°(V) / ±3°(H)	Connectivity HDMI Stereo Mini Jack USB Type A & B
Network Wired LAN RJ45 x 1 (100Mbps) Wireless Built-in and Optional (using ELPAP11)	Power Consumption Lamp On (Normal / Extended) 263W / 199W Standby (Network On / Off) 2.0W / 0.5W	Weight Approx 6.0 Kg



Ultra-Short Throw



20,000 Light Hours



Wireless Connection



Multi-PC Projection



Full HD



Finger Touch Interactive

EB-695Wi Touch Interactive



Brightness 3,500 lm	Resolution WXGA	Contrast 14,000:1
Light Source Life 5,000/10,000 hrs	Keystone ±3° (V) / ±3° (H)	Connectivity HDMI in x3, RCA x1 VGA in x2, VGA out x1 RS-232C x1, RJ45 x1 Stereo Mini Jack out x1 Stereo Mini Jack in x3 Interactive Sync x1 USB Type-A & B x1 Microphone x1
Network Optional (ELPAP10)	Power Consumption 354W / 309W	Weight 5.8 kg



Ultra-Short Throw



10,000 Hours Lamp Life in Eco Mode



Finger Touch Interactive



Multi-PC Projection

3LCD PROJECTOR

Ultra Short Throw Lamp Projectors

EB-1485Fi Touch Interactive



Brightness 5,000lm	Resolution 1080p	Contrast >2,500,000:1
Laser Light Source 20,000 hrs	Keystone $\pm 3^{\circ}$ (V) / $\pm 3^{\circ}$ (H)	Connectivity HDMI in x3 (HDCP2.3) HDBaseT x1 (HDCP2.3) HDMI out x1, RJ45 x1 VGA in x2, VGA out x1 Stereo Mini Jack in x3 Stereo Mini Jack out x1 RCA x1, RS-232C x1 Interactive Sync x1 Microphone x1, USB Type-A & Bx1
Network Built-in Support Screen Mirroring	Power Consumption 366W / 262W	Weight 9.3 kg



Ultra-Short
Throw



20,000 Light
Hours



Wireless
Connection



Multi-PC
Projection



Finger Touch
Interactive



Full HD

Large Venues

EB-PU1006W/ EB-PU1007W



Brightness 6,000 lm (PU1006W) 7,000 lm (PU1007W)	Resolution WUXGA	Contrast >2,500,000:1
Laser Source Life 20,000 hrs	Keystone $\pm 45^{\circ}$ (V) / $\pm 30^{\circ}$ (H)	Connectivity D-Sub 15Pin in x1, HDMI in x1, DVI-D in x1, HDBaseT, USB Type A x2 USB Type B x1, RS-232C x1, Stereo Mini Out x1, RJ45
Network Wireless Optional (ELPAP11)	Power Consumption 367W (PU1006W) 431W (PU1007W)	Weight 15.4 kg (PU1006W) 16.3 kg (PU1007W)



HDBaseT



Edge
Blending



Flexible
Installation



NFC

3LCD PROJECTOR

Large Venues

EB-PU1008B/ EB-PU2010B



Brightness 8,500 lm (PU1008B) 10,000 lm (PU2010B)	Resolution WUXGA	Contrast >2,500,000:1
Laser Source Life 20,000 hrs	Keystone ±45°(V) / ±30°(H)	Connectivity D-Sub 15Pin in x1, HDMI in x1, DVI-D in x1, HDBaseT, USB Type A x2, USB Type B x1, RS-232C x1, Stereo Mini Out x1, RJ45, SDI x1 (for PU2010B)
Network Wireless Optional (ELPAP11)	Power Consumption 535W	Weight 16.3 kg (PU1008B) 16.8 kg (PU2010B)



EB-PU2213B



Brightness 13,000lm	Resolution WUXGA	Contrast >2,500,000:1
Laser Source Life 20,000 hrs	Keystone ±45°(V) / ±30°(H)	Connectivity HDMI in x1, SDI x1, HDBaseT x1, VGA in x1, VGA out x1, 5BNC x1, DVI-D x1, RS-232C x1, RJ45 x1, Stereo Mini Jack in x3, Stereo Mini Jack out x1, USB Type-A & Bx1
Network Wireless optional (ELPAP10)	Power Consumption 908W / 597W	Weight 21.9 kg



3LCD PROJECTOR

Large Venues

EB-PU2216B



Brightness 16,000lm	Resolution WUXGA	Contrast >2,500,000:1
Laser Source Life 20,000 hrs	Keystone ±45°(V) / ±30°(H)	Connectivity HDMI in x1 HDBaseT x1 VGA in x1, VGA out x1 5BNC x1, DVI-D x1 RS-232C x1, RJ45 x1 Stereo Mini Jack in x3 Stereo Mini Jack out x1 USB Type-A & Bx1
Network Wireless optional (ELPAP10)	Power Consumption 1024W / 647W	Weight 22.3 kg



HDBaseT



Edge
Blending



Flexible
Installation


EB-PU2220B



Brightness 20,000lm	Resolution WUXGA	Contrast >2,500,000:1
Laser Source Life 20,000 hrs	Keystone ±44°(V) / ±30°(H)	Connectivity HDBaseT x1, RS-232C x1 VGA in x1, VGA out x1 BNC in x1, SDI in x1 Expansion Board ELPIF01 (HDMI in x1, DVI-D x1, DC-Out x1) Expansion Board ELPIF03 (Display port in x2) BNC out x1 RJ-45 x1 (etherCON) USB Type-A & B x1
Network Built-in	Power Consumption 1860W / 1123W	Weight 49.6 kg



HDBaseT



Flexible
Installation



Edge
Blending

3LCD PROJECTOR

EB-L30000UNL



Brightness 30,000lm	Resolution WUXGA	Contrast >2,500,000:1
Laser Source Life 20,000 hrs	Keystone ±45°[V] / ±30°[H]	Connectivity HDBaseT x1 (HDCP 2.2) VGA in x1, VGA out x1 SDI in x1, 5BNC x1 DVI-D x1 (Single link, HDCP 1.4) HDMI in x1 (HDCP 2.2) SDI out x1, RS-232C x1 Remote x1, RJ45 x1 USB Type-A & B x1
Network Optional	Power Consumption 2325W / 1511W	Weight 69.9 kg



HDBaseT



Flexible
Installation



Edge
Blending

EB-PQ2010B



Brightness 10,000 lm	Resolution 4K UHD (3840 x 2160)	Contrast >5,000,000:1
Laser Source Life 20,000 hrs	Keystone ±45°[V] / ±30°[H]	Connectivity SDI (BNC) x1, HDMI in x2, HDBaseT x1, USB Type A x2, USB Type B x1, RS-232 C x1, Stereo Mini Jack in x1, SDI out (BNC) x1, HDMI out x1, Stereo Mini Jack Out x1
Network LAN RJ45 x1 Wireless Optional (ELPAP11)	Power Consumption 613W/483W	Weight 18.8 kg



HDBaseT



Edge
Blending



Flexible
Installation



NFC

3LCD PROJECTOR

Large Venues

EB-PQ2008B



Brightness 8,000 lm (PQ2010B)	Resolution 4K UHD (3840 x 2160)	Contrast >5,000,000:1
Laser Source Life 20,000 hrs	Keystone ±45°(V) / ±30°(H)	Connectivity SDI (BNC) x1, HDMI in x2, HDBaseT x1, USB Type A x2, USB Type B x1, RS-232 C x1, Stereo Mini Jack in x1, SDI out (BNC) x1, HDMI out x1, Stereo Mini Jack Out x1
Network LAN RJ45 x1 Wireless Optional (ELPAP11)	Power Consumption 502W/410W	Weight 18.6 kg



HDBaseT



Edge
Blending



Flexible
Installation



NFC

EB-PQ2213B



Brightness 13,000 lm	Resolution 4K UHD (3840 x 2160)	Contrast >5,000,000:1
Laser Source Life 20,000 hrs	Keystone ±45°(V) / ±30°(H)	Connectivity SDI (BNC) x1, HDMI in x2, HDBaseT x1, USB Type A x2, USB Type B x1, RS-232 C x1, Stereo Mini Jack in x1, SDI out (BNC) x1, HDMI out x1, Stereo Mini Jack Out x1
Network LAN RJ45 x1 Wireless Optional (ELPAP11)	Power Consumption 925W/666W	Weight 28.8 kg



HDBaseT



Edge
Blending



Flexible
Installation



NFC

3LCD PROJECTOR

3LCD PROJECTOR

EB-PQ2216B



Brightness 16,000 lm	Resolution 4K UHD (3840 x 2160)	Contrast >5,000,000:1
Laser Source Life 20,000 hrs	Keystone ±45°[V] / ±30°[H]	Connectivity SDI (BNC) x1, HDMI in x2, HDBaseT x1, USB Type A x2, USB Type B x1, RS-232 C x1, Stereo Mini Jack in x1, SDI out (BNC) x1, HDMI out x1, Stereo Mini Jack Out x1
Network LAN RJ45 x1 Wireless Optional (ELPAP11)	Power Consumption 1.114W/784W	Weight 29.2 kg



EB-PQ2220B



Brightness 20,000 lm	Resolution 4K UHD (3840 x 2160)	Contrast >5,000,000:1
Laser Source Life 20,000 hrs	Keystone ±45°[V] / ±30°[H]	Connectivity SDI (BNC) x1, HDMI in x2, HDBaseT x1, USB Type A x2, USB Type B x1, RS-232 C x1, Stereo Mini Jack in x1, SDI out (BNC) x1, HDMI out x1, Stereo Mini Jack Out x1
Network LAN RJ45 x1 Wireless Optional (ELPAP11)	Power Consumption 1.431W/975W	Weight 29.2 kg



3LCD PROJECTOR

Home Entertainment Projectors


EH-QL3000W



Brightness 6,000lm	Resolution 4K	Contrast > 5,000,000:1
Laser Light Source 20,000 hrs	Keystone $\pm 30^\circ$ (V) / $\pm 30^\circ$ (H)	Connectivity HDMI x 2 USB Type-A x 2 USB Type-B x 1 Stereo Mini Jack Out x 1
Network LAN RJ45 x1	Power Consumption 453W/357W	Dimension Approx. 21kg 570 x 560 x 190 mm



4K



Lens Shift



EpiqVision EF-21G/R

Brightness 1,000lm	Resolution Full HD (1080p)	Contrast > 5,000,000: 1
Weight Approx 2.3 kg	Keystone $\pm 20^\circ$ (V) / $\pm 20^\circ$ (H)	Connectivity HDMI x1 (HDCP 2.3) 5 W Stereo Speaker USB Type-A & Type-B x1



Auto Vertical Keystone



Miracast



3LCD PROJECTOR

3LCD PROJECTOR

NEW
PRODUCT



EpiqVision EF-22N

Brightness 1,000lm	Resolution Full HD (1080p)	Contrast > 5,000,000: 1
Weight Approx 2.3 kg	Keystone ±20° (V) / ±20° (H)	Connectivity HDMI x1 (HDCP 2.3) 5 W Stereo Speaker USB Type-A & Type-B x1



Auto Vertical Keystone



Miracast



Google TV

EH-TW6250



Brightness 2,800lm / 1,900lm	Resolution Full HD (1080P)	Contrast 35,000 : 1
Light Source Life Type Lamp: 200W UHE Lamp Life*1 Normal: 4,500 / Eco: 7,500 hours	Keystone ±30°(V) / ±30°(H)	Connectivity HDMI USB Type B
Network -	Power Consumption Lamp On (Normal/Quiet, Extended) 301W /231W Energy Saving 0.3W	Weight Approx 4.1 Kg



Auto Vertical Keystone



AndroidTV

3LCD PROJECTOR

Home Entertainment

EH-LS800B



Brightness 4,000lm / 2,000lm	Resolution 4K	Contrast Over 2,500,000:1
Light Source Life 20,000 hours (Normal / Eco)	Keystone -	Connectivity HDMI USB Type A
Network -	Power Consumption Lamp On (Normal / Quiet, Extended) 335W / 210W Standby (Network On / Off) 2.0W / 0.4 W	Weight Approx 7.2 Kg




4K PRO-UHD



sound by **YAMAHA**

Chromecast built-in

EpiqVision Ultra EH-LS650B



Android TV™ Dongle (ELPAP12)
sudah ada di dalam unit nya



Brightness 3,600lm	Resolution Full HD (1080p)	Contrast > 2,500,000:1
Laser Light Source 20,000 hrs	Keystone 8 point arc correction	Connectivity HDMI x2 (SMF, HDMI2=ARC) Audio Out (Bluetooth & Optical Out) USB Type-A x 1 USB Type-B Mini x1
Wireless Built-in	Power Consumption 278 W	Weight & Dimension Approx. 7.2 kg 400x467x133 mm



sound by **YAMAHA**

Chromecast built-in

3LCD PROJECTOR

3LCD PROJECTOR

EH-LS12000B



Brightness 2,700lm	Resolution 4K	Contrast > 2,500,000:1
Laser Light Source 20,000 hrs	Keystone ±30° (V) / ±30° (H)	Connectivity HDMI x 2 USB Type-A x 2 USB Type-B x 1 Stereo Mini Jack Out x 1
Network N/A	Power Consumption 302W/198W	Dimension Approx. 12.7kg 447 x 520 x 169 mm



4K



Lens Shift

EH-TW7000



Brightness 3,000lm	Resolution Full HD (1080p)	Contrast 40,000:1
Light Source Life 3,500 hrs / 5,000 hrs	Keystone ±30° (V) / ±30° (H)	Connectivity HDMI x 2 (HDCP 2.2) Stereo Mini Jack Out x 1 USB Type-A x 2 Type-B Mini x 1 Wireless ELPAP10 (Optional)
Max Screen Size 500 inch	Power Consumption 368W/280W	Weight & Dimension Approx 6.6 kg 410 x 310 x 157 mm



Vertical & Horizontal
Keystone Adjuster



HDMI



3LCD PROJECTOR

Cross Over



Full HD
1080p

CO-FH01

Brightness 3,000lm / 2,000lm	Resolution Full HD (1080P)	Contrast -
Light Source Life -	Keystone ±30°(V) / ±30°(H)	Connectivity HDMI USB Type A & B
Network Wireless Optional (ELPAP11)	Power Consumption 270W / 214W	Weight Approx 2.4 Kg



CO-FH02

Brightness 3,000lm / 2,000lm	Resolution Full HD (1080P)	Contrast -
Light Source Life Type Lamp (Fixed), 188 W UHE Life (Normal/ Extended) 6,000 / 12,000 hours (Normal / ECO)	Keystone ±30°(V) / ±30°(H)	Connectivity USB Type A & B
Network -	Power Consumption 270W / 214W	Weight Approx 2.6 Kg

Full HD
1080p



Chromecast built-in

3LCD PROJECTOR

Wireless Presenter



ELPWP10

Ideal for small-group presentation, Selected Epson projectors offers an affordable and versatile wireless presentation system for offices.

[Contents: Wireless Dongle x2, ELPAP11 x1, Tray x1]



ELPWP20

- Cable-free collaboration Wireless presentation system for maximum ease of use
- Instant multi-screen sharing Display up to four devices simultaneously
- Display-agnostic Compatible with all displays with a HDMI input
- Compatibility with all major OSs Works with Windows, Mac, Android, iOS and Chromebooks
- Miracast built in For simple sharing on compatible devices

[Contents: Wireless Dongle x2, Base Station x1, Tray x1, IR Remote x1]



ELPWT01

- Power Consumption 5 VDC / 0.5 A
- Operating Temperature 0 to +40°C (Humidity of 20 to 80%, No condensation)
- Storage Temperature -20 to +70°C (Humidity of 0 to 95%, No condensation)
- Operating Altitude 0 to 3,000 m
- Dimensions Width 63.5 x Height 11 x Depth 175 mm (excluding USB conversion adapter)
- Weight Approx. 53 g

[Contents: Wireless Dongle x1]