LARGE FORMAT TECHNICAL PRINTERS SURECOLOR™ SC-T3730E/T3730DE/T3730D/ T5730D/T7730D

CUTTING-EDGE INNOVATION FOR HIGH-VOLUME AND SECURED PRINTING.



SC-T3730D/DE 60.96 cm (24")

> SC-T7730D 111.76 cm (44")

Exceptional performance, spectacular precision and true-to-life colours from your SureColor™ printer.

KPSON

Be ready to amplify your ideas and showcase them in spectacular precision with Epson's new SureColor technical printer series. They come equipped with PrecisionCore[™] MicroTFP[®] printheads for precise printing and vivid colour-accurate prints using the UltraChrome[™] XD3 inks. With versatile printing capabilities, these printers are engineered with user-friendly functions and secure management features for businesses to enjoy a seamless printing process. Get ready to be mesmerised by the exceptional line printing accuracy and top-class efficiency.



SC-T5730D

91.44 cm (36")

EPSON

SPECIFICATIONS

MODEL NUMBER	SC-T3730E/DE/D	SC-T5730D	SC-T7730D	Dimensions and Weight	
SKU Code		SC-T5730D C11CH81402	SC-T7730D C11CH83402	SC-T3730E/DE/D	
	<u>C11CH80402</u>			- Weight: Approx. 118.1 kg	
Printer Width	60.96 cm (24")	91.44 cm (36")	111.76 cm (44")	– weight: Approx. 118.1 kg –	
Printing Technology					
Printhtead	PrecisionCore [™] MicroTFP [®] Prir				
Nozzle Configuration Maximum Resolution	9600 Nozzles (400 nozzles x 24 2400 x 1200 dpi	+ channels x T head)		– 975 m	Im
Minimum Ink Droplet Volume	3.5 pl				
Line Accuracy	±0.1% or ±0.26 mm				
Minimum Line Width	0.08 mm ^{*1} (0.02 mm ^{*2})				
Print Speed	A1 Size		B0 Size	1365 mm 499 mr	า
	Plain Paper: 16 sec (Draft), 21 sec (Speed),	Plain Paper: 25 sec (Draft), 32 sec (Speed),	Plain Paper: 35 sec (Draft), 46 sec (Speed),	1303 11111	
	111 sec (High Quality)	184 sec (High Quality)	258 sec (High Quality)	SC-T5730D	
	Premium Glossy Photo	Premium Glossy Photo	Premium Glossy Photo		
	Paper 170 gsm: 65 sec	Paper 170 gsm: 108 sec	Paper 170 gsm: 152 sec	Weight: Approx. 136.8 kg	
	(Speed), 111 sec (Quality),	(Speed), 184 sec (Quality),	(Speed), 281 sec (Quality),		
CAD	245 sec (Max Quality)	417 sec (Max Quality)	614 sec (Max Quality)		
CAD	A1 Size Plain Paper 300 dpi x 600 dpi	A1 Landscape	dpi Line Draw/Draft: 16 sec,	975 m	m
	Line Draw/Draft: 20 sec,	600 dpi x 600 dpi Line Dra			
	600 dpi x 600 dpiAO SizeLine Draw/Speed: 27 secPlain Paper 300 dpi x 600 dpi Line Draw/Draft: 28 sec,				
		600 dpi x 600 dpi Line Dra	aw/Speed: 43 sec	– 499 mr	า
Poster	A1 Size	AO Size	BO Size	1645 mm	
	Plain Paper 300 dpi x 600 dpi	Plain Paper 300 dpi x 600 dp EPSON Vivid/Speed: 32 sec	bi Plain Paper 300 dpi x 600 dpi EPSON Vivid/Speed: 46 sec		
Ink System	EPSON Vivid/Speed: 21 sec	<u> </u>	TEPSON WWW/Speed: 46 sec	[–] SC-T7730D	
Ink Type	UltraChrome™ XD3 Pigment Inł	<		Weight: Approx. 155 kg	
Colours	Cyan, Magenta, Yellow, Red, M				
Paper Handling					
Paper Path	Roll (Double Roll), Cut-sheet (M	anual Feed), Poster Board (N	lanual Feed)	- 075	
Maximum Roll Diameter Maximum Roll Weight	2/3" Core, Max. 170 mm 6.8 kg	10.5 kg	12.5 kg	_ 975 n	Im
Paper Width Roll	<u>0.0 kg</u> 254 – 610 mm	254 – 914 mm	254 – 1118 mm		
Cut-sheet	203 – 610 mm	$\frac{254 - 914 \text{ mm}}{203 - 914 \text{ mm}}$	203 - 1118 mm		
Margin (Roll Paper)*3	Top, Bottom: Min. 3 mm right, I				
Margin (Cut-sheet) ^{*3}	Top: Min. 3 mm, Bottom: Min. 1	12.7 mm right, left: Min. 0 mr		– 1848 mm 499 mr	า
Media Thickness	Roll: 0.07 mm – 0.8 mm, Cut-s	hoot: 0.07 mm 0.9 mm Do	atox Doord, 0.0 mm 1 E mm	1040 1111	
Borderless Width Sizes (mm) ⁻⁴	1118, 1030, 914, 841, 728, 700,			— —	
Connectivity	1118, 1030, 914, 841, 728, 700	, 610, 594, 515, 508, 500, 432	2, 406, 356, 330, 300, 254	_	
Connectivity Interface	<u>1118, 1030, 914, 841, 728, 700</u> USB 3.0, Ethernet (100BASE-T	, 610, 594, 515, 508, 500, 432 X/1000BASE-T), Wi-Fi (IEEE	2, 406, 356, 330, 300, 254	- - - Options	
Connectivity	1118, 1030, 914, 841, 728, 700 USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes ¹⁵	, 610, 594, 515, 508, 500, 432 X/1000BASE-T), Wi-Fi (IEEE device connections)	2, 406, 356, 330, 300, 254	Roll Feed Spindle (24") C12C937	
Connectivity Interface Wi-Fi Direct	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes ⁵ SC-T3730D / T5730D / T7730	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE device connections) D:	2, 406, 356, 330, 300, 254	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937	671
Connectivity Interface Wi-Fi Direct USB Host	I118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes'5 SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2'8, HF	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE device connections) D:	2, 406, 356, 330, 300, 254	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936	671 171
Connectivity Interface Wi-Fi Direct USB Host	I118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes'5 SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2'8, HF SC-T3730E/T3730DE:	, 610, 594, 515, 508, 500, 432 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ⁻¹⁸	2, 406, 356, 330, 300, 254	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937	671 171
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ^{*6}	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes'5 SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*8, Hf SC-T3730E/T3730E: Epson Scanned PDF, TIFF, JPE	, 610, 594, 515, 508, 500, 432 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ^{*8} G, HP-GL/2 ^{*8} , HP RTL ^{*8}	2, 406, 356, 330, 300, 254	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936	671 171
Connectivity Interface Wi-Fi Direct USB Host	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes'5 SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HI SC-T3730D / T5730DE: Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ¹⁸ , HP RTL ¹⁸ D:	2, 406, 356, 330, 300, 254 302.11b/g/n)	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE C	671 171 671
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ^{*6}	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes'5 SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*8, Hf SC-T3730E/T3730E: Epson Scanned PDF, TIFF, JPE	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ¹⁸ , HP RTL ¹⁸ D:	2, 406, 356, 330, 300, 254 302.11b/g/n)	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 C13S210	671 171 671 115
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes'5 SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2'8, HI SC-T3730E/T3730DE: Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2'8, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2'8, HP R	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ¹⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad	2, 406, 356, 330, 300, 254 302.11b/g/n)	 Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 	671 171 671 115 116
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes'5 SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2'8, HF SC-T3730D / T5730D / T7730 PC-T3730D / T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2'8, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2'8, HP R 10.92 cm (4.3") Touch Screen	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ¹⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸	2, 406, 356, 330, 300, 254 302.11b/g/n)	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 C13S210	671 171 671 115 116 117
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ^{*6} Printer Languages ^{*7} Control Panel Mobile Solutions	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes* SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730D / T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ¹⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸	2, 406, 356, 330, 300, 254 302.11b/g/n)	 Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 	671 171 671 115 116 117
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes ⁵ SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, Hf SC-T3730D/T5730D/TFF, JPE Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R GSC-R raster, HP-GL/2*, HP R 10.92 cm (4.3*) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD)	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ¹⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸	2, 406, 356, 330, 300, 254 302.11b/g/n)	 Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 	671 171 671 115 116 117
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ^{*6} Printer Languages ^{*7} Control Panel Mobile Solutions	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes* SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730D / T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R	, 610, 594, 515, 508, 500, 432 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁹ G, HP-GL/2 ¹⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸ rint	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7	 Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 	671 171 671 115 116 117
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes ⁵ SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2°, HF SC-T3730D / T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2°, HP R 10.92 cm (4.3°) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist	, 610, 594, 515, 508, 500, 432 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁹ G, HP-GL/2 ¹⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸ rint	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7	 Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 	671 171 671 115 116 117
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes* SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730D / T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: SC-T3730E/T3730DE:	, 610, 594, 515, 508, 500, 432 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ⁻⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸ rint a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7	 Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 	671 171 671 115 116 117
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes ⁵ SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2 [®] , HF Sc-T3730D/T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2 [®] , HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2 [®] , HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2 [®] , HP R 10.92 cm (4.3 ^m) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6	, 610, 594, 515, 508, 500, 432 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ⁻⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸ rint a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7	 Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 	671 171 671 115 116 117
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes* SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730D / T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: SC-T3730E/T3730DE:	, 610, 594, 515, 508, 500, 432 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ⁻⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸ rint a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7	 Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Cleaning Stick C13S090 	671 171 671 115 116 117
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage Rated Current	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes ⁵ SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2 ³ , HI SC-T3730E/T3730DE: Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 SC-T3730E/T3730DE: Epson Scanned PDF, TIFF, JPE SC-T3730E/T3730DE: ESC/R raster, HP-GL/2 ³ , HP R 10.92 cm (4.3") Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6 3.4 to 1.6 A 75 W	, 610, 594, 515, 508, 500, 432 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ⁻⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸ rint a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7 019 / 2022	 Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 Cleaning Stick C13S090 9 2025 Epson India Pvt. Ltd. All Rights Reserved 	671 171 671 115 116 117 013
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage Rated Current Power Consumption Operating Ready	1118, 1030, 914, 841, 728, 700. USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes* SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730D / T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R SC-T3730D/T5730D/T7730 ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R 10.92 cm (4.3*) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6 3.4 to 1.6 A 75 W 32 W	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ¹⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸ rint a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2 50 Hz 80 W 32 W	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7 019 / 2022 70 W 32 W	 Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 Cleaning Stick C13S090 Cleaning Stick C13S090 © 2025 Epson India Pvt. Ltd. All Rights Reserved Reproduction in part or in whole, without the writt permission from Epson, is strictly prohibited. EPS6 	671 171 671 115 116 117 013
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage Rated Current Power Consumption Operating Ready Sleep	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes ⁵ SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, Hf SC-T3730D / T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730E/T3730DE: Epson Scanned PDF, TIFF, JPE SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R 10.92 cm (4.3*) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist. Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6 3.4 to 1.6 A 75 W 32 W 2.0 W	(610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE) o device connections) D: P RTL [™] G, HP-GL/2 [™] , HP RTL [™] D: TL [™] , Adobe PostScript 3, Ad TL [™] Adobe PostScript 3, Ad Adobe PostScript 3, A	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7 019 / 2022 70 W 32 W 2.0 W	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Printer Cutter Blade C13S210 Cleaning Stick C13S090 Oleaning Stick C13S090 @ 2025 Epson India Pvt. Ltd. All Rights Reserved Reproduction in part or in whole, without the writt permission from Epson, is strictly prohibited. Epson Corporation.	671 171 671 115 116 117 013 m is All other
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage Rated Current Power Consumption Operating Ready Sleep Standby	1118, 1030, 914, 841, 728, 700. USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes* SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730D / T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R SC-T3730D/T5730D/T7730 ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R 10.92 cm (4.3*) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6 3.4 to 1.6 A 75 W 32 W	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ¹⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸ rint a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2 50 Hz 80 W 32 W	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7 019 / 2022 70 W 32 W	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 Cleaning Stick C13S090 O Cleaning Stick C13S090 Printer Cutter Blade C13S210 Cleaning Stick C13S090 O	671 171 671 115 116 117 013 MI other herein demarks
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage Rated Current Power Consumption Operating Ready Sleep Standby Environmental Conditions	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes ⁵ SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730E/T3730DE: Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R 10.92 cm (4.3*) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6 3.4 to 1.6 A 75 W 32 W 2.0 W 0.3 W	610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE) • device connections) D: P RTL** G, HP-GL/2**, HP RTL** D: TL**, Adobe PostScript 3, Ad TL** a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2 S0 Hz S0 Hz B0 W 32 W 2.0 W 0.3 W	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7 019 / 2022 70 W 32 W 2.0 W	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Printer Cutter Blade C13S210 Cleaning Stick C13S090 Oleaning Stick C13S090 Oleaning Stick C13S090 Oleaning Stick C13S090 production in part or in whole, without the writt permission from Epson, is strictly prohibited. EPS registered trademark of Seike Epson Corporation. products names and other company names used are for identification purposes only and are the tra or registered trademarks of their respective owner	671 171 671 115 116 117 013 whis Notis All other herein temarks s. Epson
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage Rated Current Power Consumption Operating Ready Sleep Standby Environmental Conditions Temperature	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes'5 SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2'8, HF SC-T3730E/T3730DE: Epson Scanned PDF, TIFF, JPE SC-T3730E/T3730DE: ESC/R raster, HP-GL/2'8, HP R 10.92 cm (4.3") Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6 3.4 to 1.6 A 75 W 32 W 2.0 W 0.3 W Operating: 10°C to 35°C, Stora	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE r device connections) D: P RTL [™] G, HP-GL/2 [™] , HP RTL [™] D: TL [™] , Adobe PostScript 3, Ad TL [™] rint a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2 50 Hz 60 Hz 60 Hz 10	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7 019 / 2022 70 W 32 W 2.0 W 0.3 W	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 Cleaning Stick C13S090 Cleaning Stick C13S090 Signed Clean A C13S210 Cleaning Stick C13S090 Cleaning Stick C13S090 Signed Clean A C13S210 Clean A C1	671 171 671 115 116 117 013 All other herein All other herein s. Epson amples s. Epson
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage Rated Current Power Consumption Operating Ready Sleep Standby Environmental Conditions	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes ⁵ SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730E/T3730DE: Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R 10.92 cm (4.3*) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6 3.4 to 1.6 A 75 W 32 W 2.0 W 0.3 W	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE r device connections) D: P RTL [™] G, HP-GL/2 [™] , HP RTL [™] D: TL [™] , Adobe PostScript 3, Ad TL [™] rint a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2 50 Hz 60 Hz 60 Hz 10	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7 019 / 2022 70 W 32 W 2.0 W 0.3 W	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Printer Cutter Blade C13S210 Cleaning Stick C13S090 Oleaning	671 171 671 115 116 117 013 minis all other herein demarks s. Epson amples duct d may
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage Rated Current Power Consumption Operating Ready Sleep Standby Environmental Conditions Temperature Humidity Sound Pressure	1118, 1030, 914, 841, 728, 700. USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes's SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730D / T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R 10.92 cm (4.3*) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6 3.4 to 1.6 A 75 W 32 W 2.0 W 0.3 W Operating: 10°C to 35°C, Stora Operating: 20% to 80% (no cor	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE r device connections) D: P RTL ¹⁸ G, HP-GL/2 ⁻⁸ , HP RTL ¹⁸ D: TL ⁻⁸ , Adobe PostScript 3, Ad TL ⁻⁸ rint a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2 50 Hz <u>80 W</u> <u>32 W</u> 2.0 W 0.3 W uge: -20°C to 40°C ndensation), Storage: 5% to 8	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7 019 / 2022 70 W 32 W 2.0 W 0.3 W 35% (no condensation)	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 Cleaning Stick C13S090 Cleaning Stick C13S090 Signed Clean A C13S210 Cleaning Stick C13S090 Cleaning Stick C13S090 Signed Clean A C13S210 Clean A C1	671 171 671 115 116 117 013 minis all other herein demarks s. Epson amples duct d may
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage Rated Current Power Consumption Operating Ready Sleep Standby Environmental Conditions Temperature Humidity Sound Pressure Sound Power Dimensions & Weight	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes ⁵ SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730D / T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R 10.92 cm (4.3*) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6 3.4 to 1.6 A 75 W 32 W 2.0 W 0.3 W Operating: 10°C to 35°C, Stora	, 610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE ¹ device connections) D: P RTL ¹⁹ G, HP-GL/2 ¹⁸ , HP RTL ¹⁸ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸ rint a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2 S0 Hz 80 W 32 W 2.0 W 0.3 W ge: -20°C to 40°C rdensation), Storage: 5% to 8 46 dB(A) 6.4 B(A)	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7 019 / 2022 70 W 32 W 2.0 W 0.3 W 2.0 W 0.3 W 35% (no condensation) 50 dB(A) 6.6 B(A))	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 Cleaning Stick C13S090 Oleaning Stick C13S090 Solution of the second structure of the se	671 171 671 115 116 117 013 All other herein Jemarks & Epson amples duct d may pson
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage Rated Current Power Consumption Operating Ready Sleep Standby Environmental Conditions Temperature Humidity Sound Pressure Sound Power Dimensions & Weight Dimension (W x D x H), Stowed	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes*5 SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730E/T3730DE: Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R 10.92 cm (4.3*) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6 3.4 to 1.6 A 75 W 32 W 2.0 W 0.3 W Operating: 10°C to 35°C, Stora Operating: 20% to 80% (no cor 46 dB(A) 6.3 B(A) 1365 x 499 x 975 mm	610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE device connections) D: P RTL ¹⁸ G, HP-GL/2 ¹⁸ , HP RTL ¹⁶ D: TL ¹⁸ , Adobe PostScript 3, Ad TL ¹⁸ a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2 50 Hz 80 W 32 W 2.0 W 0.3 W 2.0 W 0.3 W ge: -20°C to 40°C indensation), Storage: 5% to 8 46 dB(A) 6.4 B(A) 1645 x 499 x 975 mm	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7 019 / 2022 70 W 32 W 2.0 W 0.3 W 35% (no condensation) 50 dB(A) 6.6 B(A)) 1848 x 499 x 975 mm	Boll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 Cleaning Stick C13S090 Cleaning Stick C13S090 O2025 Epson India Pvt. Ltd. All Rights Reserved Reproduction in part or in whole, without the writt permission from Epson, is strictly prohibited. EPS registered trademark of Seiko Epson Corporation. products names and other company names used are for identification purposes only and are the tra or registered trademarks of their respective owner disclaims any and all rights in those marks. Print s shown are simulations only. Specifications and pr availability are subject to change without notice ar vary between countries. Please check with local E offices for more information.	671 171 671 115 116 117 013 All other herein s. Epson amples s. Epson amples aduct d may osson
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage Rated Current Power Consumption Operating Ready Sleep Standby Environmental Conditions Temperature Humidity Sound Pressure Sound Power Dimension & Weight Dimension (W x D x H), Stowed Weight	1118, 1030, 914, 841, 728, 700. USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes* SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730D / T5730D / T7730 Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R SC-T3730D/T5730D/T7730 ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R SC-T3730E/T3730DE: ESC/R raster, HP-GL/2*, HP R 10.92 cm (4.3*) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6 3.4 to 1.6 A 75 W 32 W 2.0 W 0.3 W Operating: 10°C to 35°C, Stora Operating: 20% to 80% (no cor 46 dB(A) 6.3 B(A) 1365 x 499 x 975 mm 118.1 kg	610, 594, 515, 508, 500, 433 ×/1000BASE-T), Wi-Fi (IEEE) • device connections) D: P RTL*8 G, HP-GL/2*8, HP RTL*8 D: TL*8, Adobe PostScript 3, Ad TL*8 a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2 50 Hz 50 Hz 60 Hz 90 W 32 W 2.0 W 0.3 W ge: -20°C to 40°C >> odensation), Storage: 5% to 8 46 dB(A) 6.4 B(A) 1645 x 499 x 975 mm 136.8 kg	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7 019 / 2022 70 W 32 W 2.0 W 0.3 W 2.0 W 0.3 W 35% (no condensation) 50 dB(A) 6.6 B(A))	Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Borderless Maintenance Box C13S210 Printer Cutter Blade C13S210 Cleaning Stick C13S090 Oleaning Stick C13S090 Solution of the second structure of the se	671 171 671 115 116 117 013 All other herein s. Epson amples s. Epson amples aduct d may osson
Connectivity Interface Wi-Fi Direct USB Host USB Direct Print ¹⁶ Printer Languages ¹⁷ Control Panel Mobile Solutions Memory Operating System Electrical Specifications Voltage Rated Current Power Consumption Operating Ready Sleep Standby Environmental Conditions Temperature Humidity Sound Pressure Sound Power Dimensions & Weight	1118, 1030, 914, 841, 728, 700, USB 3.0, Ethernet (100BASE-T Wi-Fi Direct (Simple AP, up to 8 Yes*5 SC-T3730D / T5730D / T7730 PDF, TIFF, JPEG, HP-GL/2*, HF SC-T3730E/T3730DE: Epson Scanned PDF, TIFF, JPE SC-T3730D / T5730D / T7730 ESC/R raster, HP-GL/2*, HP R 10.92 cm (4.3*) Touch Screen Epson Smart Panel, Apple AirP 4GB + 960GB (Option SSD) Windows XP (32bit/64bit) / Vist Windows Server 2003 SP2 or la Mac OS X 10.6.8 or later AC 100-240 V; Frequency: 50/6 3.4 to 1.6 A 75 W 32 W 2.0 W 0.3 W Operating: 10°C to 35°C, Stora Operating: 20% to 80% (no cor 46 dB(A) 6.3 B(A) 1365 x 499 x 975 mm	610, 594, 515, 508, 500, 433 X/1000BASE-T), Wi-Fi (IEEE) • device connections) D: P RTL*8 G, HP-GL/2*8, HP RTL*8 D: TL*8, Adobe PostScript 3, Ad TL*8 a / 7 / 8 / 8.1 / 10 / 11 ater / 2008 / 2012 / 2016 / 2 60 Hz 60 Hz 60 Hz 60 Hz 610 - 20°C to 40°C 0 - 3 W ige: -20°C to 40°C 0 - 46 dB(A) 6.4 B(A) 1645 x 499 x 975 mm 136.8 kg ver cable, Setup guide,	2, 406, 356, 330, 300, 254 302.11b/g/n) obe PDF 1.7 019 / 2022 70 W 32 W 2.0 W 0.3 W 35% (no condensation) 50 dB(A) 6.6 B(A)) 1848 x 499 x 975 mm	 Roll Feed Spindle (24") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (36") C12C937 Roll Feed Spindle (44") C12C936 SSD Unit (960 GB) C12C936 CONSUMABLE Maintenance Box C13S210 Printer Cutter Blade C13S210 Cleaning Stick C13S090 Cleaning Stick C13S090 Cleaning Stick C13S090 Settered trademark of Seiko Epson Corporation. products names and other company names used are for identification purposes only and are the trademarks of Seiko Epson Corporation. products names and all rights in those marks. Print s shown are simulations only. Specifications and pri availability are subject to change without notice ar vary between countries. Please check with local E offices for more information. Apple, iPad and iPhone are trademarks of Apple 1 	671 171 671 115 116 117 013 All other herein s. Epson amples duct d may oson

1 ISO/IEC 24/90, Single weight matte paper, CAD/Line Drawing, Speed, High Speed = Off, Finest Detail = On. *2 Addressable. *4 Max supported size depends on the max supported width of printer. *5 Not supported for USB memory with an encryption or security function. Not-guarantee connected through USB memory reader/writer or extension cable. *6 T3730E/T3730DE: Epson Scanned PDF, TIFF, JPEG, HP-GL/2, HP RTL *7 T3730DE: ISC/P raster, HP-GL/2, HP RTL. *8 It is recommended to do test before purchasing printer if HP-GL/2 or HP RTL direct print is used, because whether supported or not depends on application or data.

EPSON INDIA PVT. LTD.

11th Floor, Godrej Centre, Hebbal, Survey No. 26, Bellary Road, Sahakar Nagar, Byatarayanapura, Bangalore 560 092, Karnataka.

Regional Offices:

Ahmedabad 4037 0075, Chennai 4905 5177, Coimbatore 98942 19200, Ernakulam 4012 315, Hyderabad 4857 0032, Jaipur 4923 119, Kolkata 4603 4714/15/29/30, Mumbai 3079 8200, New Delhi 4107 3101, 4752 2414, Pune 2998 0641

Information correct as of April 2025.

Tel: 080-6939 5000 Fax: 080-6939 5005



EPSON

Epson Helpline: For product info or service - 1800 425 0011 For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon - Sat) Email: Ifp@epson-india.in