

**HIGH BRIGHTNESS  
LASER PROJECTOR  
EB-L1755UNL**

**EPSON**  
EXCEED YOUR VISION



The EB-L1755UNL projector utilises a laser light source and Epson's revolutionary 3LCD technology for true impact. Compact in design, this large-venue projector provides an equal white and colour brightness of 15,000 lumens. This projector also features 4K enhancement for images of unmatched sharpness. Technologies such as Edge Blending and seamless integration provide the firepower to take arenas by storm.



EB- L1755UNL



Beyond Full HD Resolution



Flexible Installation



Edge Blending



Camera Calibration

**Cutting-edge Technologies**

4K-enhanced for breathtaking images. Innovations such as Edge Blending, Image Warping and Curved-surface Correction.

**360° Flexible Positioning**

360° flexibility for easy installation and placement without affecting image quality. Portrait mode for added versatility.

**Easy Maintenance**

Designed to run maintenance-free for 20,000 hours and can operate even in tough outdoor conditions.



\*Source: Futuresource Consulting.

<b>Projection Technology</b>	RGB Liquid Crystal Shutter System
<b>Specifications of Main Parts</b>	
LCD	Size: 1.03-inch
	Driving Method: Poly-silicon TFT Active Matrix
	Projection Method: Front / rear / ceiling mount
	Aspect Ratio: 16:10
	Native Resolution: WUXGA (1920 x 1200) w/ 4K Enhancement Technology
Lightsource	Type: Laser Diode
	Life (Normal / Extended): 20,000 / 30,000 hours
Projection Lens <sup>4</sup>	Type <sup>5</sup> : Power Zoom / Power Focus / Power Shift
	F-Number: 1.8 - 2.3
	Focal Length: 36.00 - 57.35 mm
	Zoom Ratio <sup>6</sup> : 1 - 1.61
	Throw Ratio <sup>6</sup> : 1.57 - 2.56 (Wide to Tele)
	Lens Change: Optional lens available for purchase
Lens Shift	Mode: Powered
	Vertical (Up/Down): ±60% (H center) (Powered)
	Horizontal (Left/Right): ±18% (Vertical ±31%) (Powered)
<b>Screen Size (Projected Distance)</b>	
Zoom: Wide	60" - 500" [1.99 - 17.17 m]
Zoom: Tele	60" - 500" [3.26 - 27.77 m]
<b>Brightness<sup>1</sup></b>	
White Light Output (Normal / Extended)	15,000lm / 10,500lm
Colour Light Output	15,000lm
<b>Contrast Ratio</b>	2,500,000:1
<b>Geometric Correction</b>	
Vertical / Horizontal Keystone	±45° / ±30° (Zoom: Tele) (with Standard Lens <sup>4</sup> )
Quick Corner	Yes
Arc	Yes
Curve Surface	Yes
Point Correction	Yes
Corner Wall	Yes
Geometry Correction Memory	Yes
<b>Connectivity</b>	
Analog Input	D-Sub 15Pin: 1
	5-BNC: 1
Digital Input	DVI-D: 1
	HDMI: 1
	SDI: 1
	HDBaseT: 1
Output Terminal	D-Sub 15Pin: 1
Audio Input	Stereo Mini Jack: 3
Audio Output	Stereo Mini Jack: 1
Others	USB Type A: 1 (for Wireless LAN, Firmware Update, Copy OSD Settings)
	USB Type B: 1 (for Firmware Update, Copy OSD Settings)
Control I/O	RS-232C: D-Sub 9Pin x 1
	Remote Control Input: Stereo Mini Jack x 1
Network	Wired LAN: RJ45 x 1
	Wireless: Optional x 1
<b>Wireless Specification</b>	
Supported Speed For Each Mode	IEEE 802.11b: 11Mbps <sup>2</sup> IEEE 802.11g: 54Mbps <sup>2</sup> IEEE 802.11n: 130Mbps <sup>2</sup>
Wireless LAN Security	Quick Mode: OPEN, WPA2-PSK Advanced Mode: OPEN, WPA/WPA2-PSK, WPA/WPA2-EAP Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS, EAP-Fast, LEAP
<b>Operating Temperature</b>	
	0 - 50 °C <32 - 122 °F> (Below 1,500m / 4,921ft)
	0 - 45 °C <32 - 113 °F> [Above 1,500m / 4,921ft - 3,048m / 10,000ft (with high altitude mode)]
<b>Operating Altitude</b>	
	0 - 3,048 m <0 - 10,000 ft> (over 1,500m / 4,921ft : with high altitude mode)
<b>Direct Power On / Off</b>	
	Yes
<b>Start-Up Period</b>	
	Less than 7 seconds, Warm-up Period: 30 seconds
<b>Cool Down Period</b>	
	Instant Off
<b>Air Filter</b>	
Type	High Efficiency Filter
Maintenance Cycle (Normal / Extended)	20,000 / 30,000 hours <sup>3</sup>
<b>Power Supply Voltage</b>	
	100 - 240 V AC ±10%, 50/60 Hz
<b>Power Consumption (220V)</b>	
Laser Diode (Normal / Extended)	1024W / 647W
Standby (Network / Energy Saving)	2.0W / 0.3 W
<b>Dimension Excluding Feet (D X W X H)</b>	
	492 x 586 x 185 mm
<b>Weight (Including Standard Lens)</b>	
	Approx. 24.1 kg
<b>Weight (Excluding Standard Lens)</b>	
	Approx. 22.3 kg
<b>Fan Noise (Normal / Quiet)</b>	
	40dB / 30dB

**Accessories**

Remote Control  
Battery for Remote Control  
Cable Cover  
HDMI Cable Clamp

**Optional Lenses**

ELPLX02  
ELPLU03  
ELPLU04  
ELPLW05  
ELPLW06  
ELPLM10  
ELPLM11  
ELPLM15  
ELPLL08  
ELPLR04

EB-L1755UNL



<sup>1</sup> Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with IDMS 15:4; white light output measured in accordance with ISO 21118.

<sup>2</sup> Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.

<sup>3</sup> When used in the general office environment (the amount of floating dust: 0.04 - 0.2 mg/m<sup>3</sup>). Based on the Epson's in-house test results.

<sup>4</sup> Lens are optional and not provided with the projector.

<sup>5</sup> Indicated values for lens ELPLM15 (informally known as standard throw lens).

©2018 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Information correct as at June 2018

**EPSON INDIA PVT. LTD.**

12th Floor, The Millenia, Tower A, No.1,  
Murphy Road, Ulsoor, Bangalore - 560 008.  
Tel: 080-30515000 Fax: 080-30515005

**Regional Offices:**

Ahmedabad - 26407176/77, Chennai - 30277500/11, Cochin - 4012315,  
Coimbatore - 98942 19200, Kolkata - 65009370/77, Mumbai - 28261515/17,  
New Delhi - 46585444, Pune - 30286000, Secunderabad - 40359898



**Epson Helpline:**

For product info, service or to order a ribbon cartridge - 1800 425 0011  
For service - 1860 3000 1600 (9AM - 6PM) (Mon - Sat)

[www.epson.co.in](http://www.epson.co.in)

Dealer's Stamp